

NOTICE OF PESTICIDE: REGISTRATION
 REREGISTRATION
(Under the Federal Insecticide, Fungicide,
and Rodenticide Act, as amended)

TERM OF ISSUANCE

NAME OF PESTICIDE PRODUCT

Dixichlor Lite

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

DPC Industries, Inc.
P.O. Box 130410
Houston, TX 77219

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

Based on your response to the Reregistration Eligibility Document, EPA has reregistered the above named product subject to the comments recorded in the succeeding paragraph. This action is taken under the authority of section 4(g)(2)(C) of the Federal Insecticide, Fungicide, and Rodenticide Act, as amended. Reregistration under this section does not eliminate the need for continual reassessment of pesticides. EPA may require submission of data at any time to maintain the registration of your product.

Make the following labeling changes before you release the product for shipment:

1. In the Ingredient Statement, you must total the Active and Inert Ingredients to "100%":

Active Ingredient:
Sodium hypochlorite..... 5.25%
Inert Ingredients:..... 94.75%
Total..... 100.0%

2. The Storage and Disposal Statements must appear in the Directions For Use section of the label but somewhere after the Misuse Statement ("It is a violation...").

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL

DATE

2924

3. The Ingestion Statement must be corrected in the supplemental product booklet to be the same statement as the one that appears on the product label.

A stamped copy of the product label is enclosed for your records.

Submit one copy of the final printed label before releasing the product in channels of trade with the revised labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

Sincerely,



Ruth G. Douglas
Product Manager (32)
Antimicrobial Program Branch
Registration Division (H7504C)

Enclosure

39

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS
AND DOMESTIC ANIMALS**

DANGER: Corrosive. May cause severe skin irritation or chemical burns to broken skin. Causes eye damage. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves (PVC or Nitrile) when handling this product. Wash after handling. Avoid breathing vapors. Vacate poorly ventilated areas as soon as possible. Do not return until odors have dissipated.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, estuaries, oceans, or public waters unless this product is specifically identified and addressed in a NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS: STRONG OXIDIZING AGENT: Mix only with water according to label directions. Mixing this product with gross litter such as feces, urine, etc. or with ammonia, acids, detergents or other chemicals will release hazardous gases irritating to eyes, lungs and mucous membranes.

NO WARRANTY, EXPRESS OR IMPLIED OR MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE, IS MADE, EXCEPT THAT THE PRODUCT CONFORMS TO SELLER SPECIFICATIONS. BUYER ASSUMES ALL RISK OF USE, STORAGE AND HANDLING. SELLER SHALL NOT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING DIRECTLY OR INDIRECTLY IN CONNECTION WITH THE PURCHASE, USE, STORAGE OR HANDLING OF THE PRODUCT.

NET CONTENTS:

15 GALLONS

**DIXICHLOR
LITE
SANITIZER, DISINFECTANT**

SANITIZER, DISINFECTANT

**ACTIVE INGREDIENT:
SODIUM HYPOCHLORITE 5.25%
INERT INGREDIENTS 94.75%**

KEEP OUT OF REACH OF CHILDREN

DANGER

**STATEMENT OF PRACTICAL TREATMENT
NOTE TO PHYSICIAN**

- IF SWALLOWED:** Drink promptly a large quantity of water. Do not induce vomiting. Avoid alcohol. Get medical attention.
- IF IN EYE:** Flush with plenty of water for 15 minutes. Get medical attention.
- IF ON SKIN:** Wash with plenty of soap and water. Get medical attention if irritation persists.

DIRECTION

STORAGE AND DISPOSAL

Store in a cool, dry area away from sources of heat. In case of spill, flood area with water and rinse empty container. Then reuse for conditioning, or puncture and dispose of in a landfill, or incineration, or other method approved by local authorities, by burning. Do not burn. Product or residue that cannot be disposed of in water and disposed of in a container that does not contaminate food or feed by its equipment.

**IT IS A VIOLATION OF FEDERAL LAW
INCONSISTENT WITH ITS LABELING.**

**Brand Strength
Available Colors of Plastic**

- 100% PPG
- 100% PPG
- 100% PPG
- 100% PPG
- 100% PPG
- 100% PPG
- 100% PPG
- 100% PPG
- 100% PPG
- 100% PPG
- 100% PPG

IMPORTANT! ALL SURFACES FOR ALL FOOD CONTACT SURFACES: Wash, scrape and, when necessary, detergent or compatible cleanser and the SODIUM HYPOCHLORITE solution. Wash with SODIUM HYPOCHLORITE solution by immersion of at least 2 minutes. Drain solution and sanitize SODIUM HYPOCHLORITE solution. Prepare a fresh solution daily.

SANITIZATION OF FOOD CONTACT SURFACES: SPRAY/FOG METHOD — Prepare all surfaces with a chlorine solution of sufficient strength to control bacteria. Use a rate of 15 oz. product with 10 gallons of water to make hypochlorite solution. Always use potable water after use. Thoroughly spray surfaces to clean. Vacuum area for at least 30 minutes. Sanitize by thoroughly misting 5 oz. of product with 10 gallons of water. Prepare a fresh solution daily.

EPA REG. NO. 813-14

EPA EST. NO. 00813-MN-001

Manufactured by

DPC INDUSTRIES, INC.

12800 Pine Bend Trail Rosemount, MN 55068-2612

FOR EMERGENCY CALL: (713) 474-3271

**ACCEPTED
with CONDITIONS
in EPA Letter Dated:**

JUN 30 1993

**Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for this pesticide
registered under EPA Reg. No.**

813-14

BEST AVAILABLE

DIXICHLOR LITE

SANITIZER, DISINFECTANT

SANITIZER, DISINFECTANT

ACTIVE INGREDIENT:
SODIUM HYPOCHLORITE 5.25%
INERT INGREDIENTS 94.75%

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT
NOTE TO PHYSICIAN

- IF SWALLOWED: Drink promptly a large quantity of water. Do not induce vomiting. Avoid alcohol. Get medical attention.
- IF IN EYE: Flush with plenty of water for 15 minutes. Get medical attention.
- IF ON SKIN: Wash with plenty of soap and water. Get medical attention if irritation persists.

NECESSARY FOR A PARTICULAR PURPOSE OR OTHERWISE, IS MADE, EXCEPT THAT THE MANUFACTURER SHALL NOT BE LIABLE FOR ANY INJURY OR DAMAGE DIRECTLY OR INDIRECTLY IN CONNECTION WITH THE PURCHASE, USE, STORAGE OR HANDLING

EPA REG. NO. 813-14

EPA EST. NO. 00813-MN-001

Manufactured by
INDUSTRIES, INC.

Trail Rosemount, MN 55068-2612

EMERGENCY CALL: (713) 474-3271

ACCEPTED
with COMMENTS
In EPA Letter Dated:

JUN 30 1993

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide
registered under EPA Reg. No.

813-14

DIRECTIONS FOR USE

STORAGE AND DISPOSAL:

Store in a cool, dry area away from direct sunlight. In case of spill, flood area with large quantities of water. Thoroughly rinse empty container. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning - if burned, stay out of smoke. Product or rinsate that cannot be used should be diluted with water and disposed of in a sanitary sewer. Do not contaminate food products by storage, disposal or cleaning of equipment.

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

Standard Strength Available Chlorine by Weight	Chlorine Residual	Liquid Quaternary Ammonium Compounds
5 ppm	100	15
10 ppm	100	15
15 ppm	100	15
20 ppm	100	15
25 ppm	100	15
30 ppm	100	15
40 ppm	100	15
50 ppm	100	15
60 ppm	100	15
70 ppm	100	15
80 ppm	100	15
90 ppm	100	15
100 ppm	100	15
1200 ppm	100	15

IMPORTANT! ALL SANITIZING APPLICATIONS

FOR ALL FOOD CONTACT SURFACES AND OBJECTS—Remove food particles by brushing, scraping and, when necessary, soaking. Wash thoroughly with a good detergent or compatible cleaner and rinse with potable water before application of SODIUM HYPOCHLORITE solution. Wet all surfaces thoroughly with SODIUM HYPOCHLORITE solution by immersion, flooding or spraying. Contact time must be at least 2 minutes. Drain solution and air-dry. Do not wash with potable water after sanitizing. SODIUM HYPOCHLORITE solutions must not be re-used for sanitizing purposes. Prepare a fresh solution daily if the old solution becomes diluted or soiled.

SANITIZATION OF PORED FOOD CONTACT SURFACES

SPRAY/FOG METHOD — Pre-clean all surfaces after use. Prepare a 600 ppm available chlorine sanitizing solution of sufficient size by thoroughly mixing the product in a ratio of 15 oz. product with 10 gallons of water. Use spray or fogging equipment which can resist hypochlorite solutions. Always empty and rinse spraying equipment with potable water after use. Thoroughly spray or fog all surfaces until wet, allowing excess solution to drain. Vacuum area for at least 2 hours. Prior to using equipment, rinse all surfaces with a 200 ppm available chlorine solution. Prepare a 200 ppm sanitizing solution by thoroughly mixing 5 oz. of this product with 10 gallons of water.

SANITIZATION OF NONPORED FOOD CONTACT SURFACES

SPRAY/FOG METHOD — Pre-clean all surfaces after use. Use a 200 ppm available chlorine solution to control bacteria, mold or fungi and a 600 ppm solution to control

bacteriophage. Prepare a 200 ppm sanitizing solution of sufficient size by thoroughly mixing the product in a ratio of 15 oz. product with 10 gallons of water. Use spray or fogging equipment which can resist hypochlorite solutions. Always empty and rinse spraying equipment with potable water after use. Thoroughly spray or fog all surfaces until wet, allowing excess solution to drain. Vacuum area for at least 2 hours. Prior to using equipment, rinse all surfaces with a 200 ppm sanitizing solution.

SWIMMING POOL WATER DISINFECTION

For a new pool or spring start-up, superchlorinate with 122 to 241 10,000 gallons of water to yield 5 to 10 ppm available chlorine level of available chlorine with a test kit. Adjust and maintain pH to 7.2 and 7.6. Adjust and maintain the salinity of the pool to be 250 to 350 ppm. To maintain the pool, add manually or by a feeder device 25 oz. 10,000 gallons of water to yield an available chlorine residual of 1.0 by weight. Sanitized pools should maintain a residual of 1.0 chlorine. Test the pH, available chlorine residual and salinity with appropriate test kits. Frequency of water treatment will depend on number of swimmers.

Every 7 days, or as necessary, superchlorinate the pool with 122 for each 10,000 gallons of water to yield 5 to 10 ppm available chlorine with a test kit. Do not re-enter the pool until the residual is between 1.0 to 3.0 ppm.

At the end of the swimming pool season or when water is to be discharged, the pool must be allowed to dissipate from treated pool water chlorine the pool within 24 hours prior to discharge.

WATERIZING POOLS — While water is still clear & clean, apply 1000 gallons, while filter is running, to obtain a 3 ppm available chlorine residual by a suitable test kit. Cover pool, prepare heater, pumps for winter by following manufacturer's instructions.

DISINFECTION OF SWIMMING WATER (POT.)

PUBLIC SYSTEMS: Mix a ratio of 2.5 oz. of this product to 100 gallons of water with a hypochlorinator until a free available chlorine level of 0.2 ppm and no more than 0.6 ppm is attained throughout. Check water frequently with a chlorine test kit. Bacteriological control at a frequency no less than that prescribed by the National Sanitation Code. Contact your local Health Department for further details.

INDIVIDUAL SYSTEMS: DIG WELLS Upon completion of the construction of the casing (string) with a 100 ppm available chlorine level. This solution can be made by thoroughly mixing 2.5 oz. of product with 100 gallons of water. After covering the well, pour the solution through both the pipe-rope opening and the pump. Wash 1 cubic yard of water is used. Stop pump and wait at least 24 hours until all traces of chlorine have been removed from the well. Contact your local Health Department for further details.

NOTE: This product degrades with age. Use a chlorine test kit necessary to obtain the required level of available chlorine.

REFER TO THE OTHER SUPPLEMENTAL SHEETS FOR ADDITIONAL DIRECTIONS AND

BEST AVAILABLE COPY

DRAFT

DIXICHLOR

Sodium Hypochlorite

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JUN 30 1993

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide
registered under EPA Reg. No.

DIRECTIONS FOR USE *813-14*

Manufactured by

DPC INDUSTRIES, INC.

DXI INDUSTRIES, INC.

1919 JACINTOPORT BLVD.
HOUSTON, TEXAS 77015

BEST AVAILABLE COPY

TABLE OF CONTENTS

Page

DODDCHLOR Products

Statement of Practical Treatment

Precautionary Statements

Storage and Disposal

Directions For Use

III. Dilution Conversion Chart

Formula Definition

IV. Agricultural Uses

A. Post Harvest Protection

B. Food Egg Sanitization

C. Fruit and Vegetable Washing

V. Artificial Sand Beaches

VI. Asphalt or Wood Roofs and Sidings

VII. Aquacultural Uses

A. Fish Ponds

B. Fish Pond Equipment

C. Main Lobster Ponds

D. Conditioning Live Oysters

E. Control of Scavengers in Fish Hatchery Ponds

VIII. Boat Bottoms

IX. Cooling Tower/Evaporative Condenser Water

A. Slug Feed Method

B. Intermittent Feed Method

C. Continuous Feed Method

D. Cooling Tower/Evaporative Condenser Water Treatment Chart

X. Emergency Disinfection After Droughts

A. Supplementary Water Supplier

B. Water Shipped in By Tanks, Tank Cars, Trucks, Etc.

XI. Emergency Disinfection After Fires

A. Cross Connections or Emergency Connections

XII. Emergency Disinfection After Floods

A. Wells

B. Reservoirs

C. Basins, Tanks, Flumes, Etc.

D. Filters

E. Distribution System

ACCEPTED
with **COMMENTS**
in EPA Letter Dated:

JUN 30 1993

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the Pesticide
Registered under EPA Reg. No.

813-14

BEST AVAILABLE COPY

	B. Individual Systems	13
	1. Dug Wells	13
	C. Individual Water Systems	13
	1. Drilled, Driven and Bored Well	13
	2. Flowing Artesian Wells	13
	D. Emergency Disinfection	13
	E. Meat and Poultry Plant Treatment	13
XV.	Public Water System	13
	A. Reservoirs - Algae Control	13
	B. Mains	13
	C. New Tanks, Basins, Etc.	14
	D. New Filter Sand	14
	E. New Wells	14
	F. Existing Equipment	14
XVI.	Farm Premises	14
XVII.	Laundry Sanitizer	14
	A. Household Laundry Sanitizers	14
	1. In Soaking Suds	14
	2. In Washing Suds	14
	B. Commercial Laundry Sanitizers	14
XVIII.	Pulp and Paper Mill Process Water System	15
	A. Slug Feed Method	15
	B. Intermittent Feed Method	15
	C. Continuous Feed Method	15
	D. Pulp and Paper Mill Process Water Systems Treatment Chart	15
XIX.	Sanitization of Nonporous Food Contact Surfaces	16
	A. Rinse Method	16
	B. Immersion Method	16
	C. Flow/Pressure Method	16
	D. Clean-in Place Method	16
	E. Spray/Fog Method	16
XX.	Sanitization of Porous Food Contact Surfaces	17
	A. Rinse Method	17
	B. Immersion Method	17
	C. Spray/Fog Method	17

ACCEPTED
with COMMENTS
in EPA Letter Dated:
2

JUN 30 1993

Under the Federal Insecticide,
Fungicide, and Plant Growth Regulator
Act

813-19

BEST AVAILABLE COPY

	Page
XXI. Sanitization of Nonporous Non-Food Contact Surfaces	17
A. Rinse Method	17
B. Immersion Method	17
C. Spray/Fog Method	17
XXII. Disinfection of Non-Food Contact Surfaces	17
A. Rinse Method	17
B. Immersion Method	17
XXIII. Sanitization of Porous Non-Food Contact Surfaces	18
A. Rinse Method	18
B. Immersion Method	18
C. Spray/Fog Method	18
XXIV. Sewage and Wastewater Effluent Treatment	18
XXV. Sewage and Wastewater Treatment	18
A. Effluent Slime Control	18
B. Filter Beds - Slime Control	18
XXVI. Sanitization of Dialysis Machines	19
XXVII. Spas, Hot-Tubs, Immersion Tanks, Etc.	19
A. Spas/Hot Tubs	19
1. Maintaining the Water	19
2. After Each Use	19
3. Periods of Disuse	19
B. Hubbard and Immersion Tanks	19
B. Hydrotherapy Tanks	19
XXVIII. Swimming Pool Water Disinfection	20
A. New Pool or Spring Start-Up	20
B. Maintaining the Pool	20
C. Superchlorination	20
D. End of Swimming Pool Season	20
E. Winterizing Pools	20
F. Swimming Pool Disinfection Chart	20

ACCEPTED
with COMMENTS
in EPA File # 813-14

JUN 30 1993

Under the authority of the
Fungicide, Disinfectant, and
Antimicrobial Products Act,
Registered under EPA Reg. #

813-14

DIXICHLOR PRODUCTS

DIXICHLOR MAX

EPA Reg. No. 813-15

ACTIVE INGREDIENT:

Sodium Hypochlorite 12.5%

INERT INGREDIENT: 87.5%

DIXICHLOR

EPA Reg. No. 813- 16

ACTIVE INGREDIENT:

Sodium Hypochlorite 10.0%

INERT INGREDIENT: 90.0%

DIXICHLOR SPECIAL

EPA Reg. No. 813-13

ACTIVE INGREDIENT:

Sodium Hypochlorite 8.0%

INERT INGREDIENT: 92.0%

DIXICHLOR LITE

EPA Reg. No. 813-14

ACTIVE INGREDIENT:

Sodium Hypochlorite 5.25%

INERT INGREDIENT: 94.75%

FOR EMERGENCY CALL: (713) 474-3271

ACCEPTED
with COMMENTS
in EPA Letter Dated:
JUN 30 1993

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, this pesticide
is registered under EPA Reg. No.

813-14

DIXICHLOR PRODUCTS

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT (FIRST AID):

IF CONTACT WITH EYES OCCURS, flush with water for at least 15 minutes. Get prompt medical attention.

IF CONTACT WITH SKIN OCCURS, wash with plenty of soap and water.

IF SWALLOWED, drink large quantities of milk or gelatin solution. If these are not available, drink large quantities of water. DO NOT give vinegar or other acids. DO NOT induce vomiting. Get prompt medical attention.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive, may cause severe skin and eye irritation or chemical burns to broken skin. Causes eye damage. Wear safety glasses or goggles and rubber gloves (PVC, Nitrile) when handling these products. Wash after handling. Avoid breathing vapors. Vacate poorly ventilated areas as soon as possible. DO NOT return until strong odors have dissipated.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JUN 30 1993

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
and under the pesticide
registered under EPA Reg. No.

813-14

BEST AVAILABLE COPY

PHYSICAL OR CHEMICAL HAZARDS

STRONG OXYDIZING AGENT: Mix only with water according to Label or Directions For Use (see Directions). Mixing either of these products with chemicals (e.g. ammonia, acids, detergents, etc.) or organic matter (e.g. urine, feces, etc.) will release chlorine gas which is irritating to eyes, lungs and mucous membranes.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

IMPORTANT! ALL SANITIZING APPLICATIONS

FOR ALL FOOD CONTACT SURFACES AND OBJECTS—Remove food particles by rinsing, scraping and, when necessary, soaking. Wash thoroughly with a good detergent or compatible cleaner and rinse with potable water before application of SODIUM HYPOCHLORITE solution. Wet all surfaces thoroughly with SODIUM HYPOCHLORITE solution by immersion, flooding or spraying. Contact time must be at least 2 minutes. Drain solution and air-dry. Do not wash with potable water after sanitizing. SODIUM HYPOCHLORITE solutions must not be re-used for sanitizing purposes. Prepare a fresh solution daily if the old solution becomes diluted or soiled.

STORAGE AND DISPOSAL

Store this product in a cool dry area, away from direct sunlight and heat to avoid deterioration. In case of spill, flood area with large quantities of water. Product or residues that cannot be used should be diluted with water before disposal in a sanitary sewer. DO NOT reuse container but place in trash collection. DO NOT contaminate food or feed by storage, disposal or cleaning of equipment.

NOTE: This product degrades with age. Use a chlorine test kit and increase dosage as necessary, to obtain the required level of available chlorine.

ACCEPTED
with CORRECTION
in EPA Letter

7.

JUN 30

Under the Federal
Fungicide, and Herbicide
Amended, for use
registered under F

813-14

BEST AVAILABLE C

DIXICHLOR SODIUM HYPOCHLORITE

The DILUTION CONVERSION CHART provided below covers the DDXCHLOR Sodium Hypochlorite Products manufactured by DXI Industries, Inc. and DPC Industries, Inc. It is designed to serve as a guide and may not cover all PPM ranges or dilution as required to satisfy a particular use or need.

III. DILUTION CONVERSION CHART

Desired Strength Avail. Chlorine (by Weight)	Gallons Water	Liquid Oz. Sodium Hypochlorite			
		12.5%	10%	5%	5.25%
5 PPM	100	.5	.75	1.0	1.5
10 PPM	100	1.0	1.5	1.5	2.5
15 PPM	100	1.5	2.0	2.5	4.0
25 PPM	100	2.5	3.5	4.0	6.0
35 PPM	100	3.5	4.5	5.5	8.5
50 PPM	100	5.0	6.5	8.0	12.0
100 PPM	10	1.0	1.5	2.0	2.5
200 PPM	10	2.0	2.5	3.5	5.0
500 PPM	10	5.0	6.5	8.0	12.0
600 PPM	10	6.0	8.0	10.0	15.0
1000 PPM	10	10.0	13.0	16.0	24.0
2000 PPM	10	20.0	26.0	32.0	48.0
10000 PPM	10	100.0	130.0	160.0	240.0

Should other available chlorine strengths or dilution volumes be desired, the following formula must be used to adjust the dosage:

$$\text{Ounce of Product} = \frac{(\text{PPM avail. Cl}_2) (\text{Gal. Water}) (128)}{(\% \text{ Active Ingredient}) (10,000)}$$

Formula Definitions:

- Ounce of Product = Ounces of DDXCHLOR Product to Use
- PPM Available Cl₂ = What is Required
- Dilution Gallons Water = You Specify Quantity
- 128 oz./gal. = Constant 128
- (%) Percent Active Ingredient = Sodium Hypochlorite Strength
- 10,000 = Constant

BEST AVAILABLE COPY

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JUN 30 1993
Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide
registered under EPA Reg. No.

813-14

IV. AGRICULTURAL USES

A. Post-Harvest Protection

Potatoes can be sanitized after cleaning and prior to storage by spraying with a 500 ppm available chlorine sanitizing solution at a level of 1 gallon of sanitizing solution per ton of potatoes.

Disinfect hatching bee cells and bee boards by immersion in a solution containing 1 ppm available chlorine for 3 minutes. Allow cells to drain for 2 minutes and dry for 4 to 5 hours or until no chlorine odor can be detected. The bee domicile is disinfected by spraying with a 0.1 ppm solution until all surfaces are thoroughly wet. Allow the domicile to dry until all chlorine odor has dissipated.

B. Feed Egg Sanitization

Thoroughly clean all eggs. Thoroughly mix DDOCHLOR product with 10 gallons of warm water to produce a 200 ppm available chlorine solution. The sanitizer temperature should not exceed 130°F. Spray the warm sanitizer so that the eggs are thoroughly wetted. Allow the eggs to thoroughly dry before casing or breaking. Do not apply a potable water rinse. The solution should not be reused to sanitize eggs.

C. Fruit and Vegetable Washing

Thoroughly clean all fruits and vegetables in a wash tank. Thoroughly mix DDOCHLOR in water to make a sanitizing solution of 25 ppm available chlorine. After draining the tank, submerge fruit or vegetables for 2 minutes in a second wash tank containing the recirculating sanitizing solution. Spray rinse vegetables with the sanitizing solution prior to packaging. Rinse fruit with potable water only prior to packaging.

V. ARTIFICIAL SAND BEACHES

To sanitize the sand, spray a 500 ppm available chlorine solution at frequent intervals. Small areas can be sprinkled with a watering can.

VI. ASPHALT OR WOOD ROOFS AND SIDINGS

To control fungus and mildew, first remove all physical soil by brushing and hosing with clean water. Apply a 5000 ppm available chlorine solution by brushing or spraying roof or siding. After 30 minutes, rinse by hosing with clean water.

VII. AQUACULTURAL USES

A. Fish Ponds

Remove fish from ponds prior to treatment. Add appropriate amount of DDOCHLOR to 10,000 gallons of water to obtain 10 ppm available chlorine. Add more DDOCHLOR to the water if the available chlorine level is below 1 ppm after 5 minutes. Return fish to pond after the available chlorine level reaches zero.

B. Fish Pond Equipment

Thoroughly clean all equipment prior to treatment. Thoroughly mix DDOCHLOR with 10 gallons of water to obtain 200 ppm available chlorine. Porous equipment should soak for one hour.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JUN 30 1993

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, this pesticide
registered under Reg. No.

813-14

9
BEST AVAILABLE COPY

C. Main Lobster Ponds

Remove lobsters, seaweed, etc. from ponds prior to treatment. Drain the pond. Thoroughly mix DDDCHLOR to 10,000 gallons of water to obtain at least 600 ppm available chlorine. Apply so that all burrows, gates, rock and dam are treated with product. Permit high tide to fill the pond and then close gates. Allow water to stand for 2 to 3 days until the available chlorine level reaches zero. Open gates and allow 2 tidal cycles to flush the pond before returning lobsters to pond.

D. Conditioning Live Oysters

Thoroughly mix DDDCHLOR to 10,000 gallons of water at 80 to 70°F to obtain 0.5 ppm available chlorine. Expose oysters to this solution for at least 15 minutes, monitoring the available chlorine level so that it does not fall below 0.05 ppm. Repeat entire process if the available chlorine level drops below 0.05 ppm or the temperature falls below 50°F.

E. Control of Scavengers in Fish Hatchery Ponds

Prepare a solution containing 200 ppm of available chlorine by mixing DDDCHLOR with 10 gallons of water. Pour into drained pond potholes. Repeat if necessary. Do not put desirable fish back into refilled ponds until chlorine residual has dropped to 0 ppm, as determined by a test kit.

VIII. BOAT BOTTOMS

To control slime on boat bottoms, sling a plastic tarp under boat, retaining enough water to cover the fouled bottom area, but not allowing water to enter enclosed area. This envelope should contain approximately 500 gallons of water for a 14 foot boat. Add DDDCHLOR to this water to obtain a 35 ppm available chlorine concentration. Leave immersed for 8 to 12 hours. Repeat if necessary. Do not discharge the solution until the free chlorine level has dropped to 0 ppm, as determined by a swimming pool test kit.

IX. COOLING TOWER/EVAPORATIVE CONDENSER WATER

A. Slug Feed Method

Initial Dose: When system is noticeably fouled, add appropriate amount of DDDCHLOR per 10,000 gallons of water in the system to obtain from 5 to 10 ppm available chlorine. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add appropriate amount of DDDCHLOR per 10,000 gallons of water in the system daily, or as needed to maintain control and keep the chlorine residual at 1 ppm. Badly fouled systems must be cleaned before treatment is begun.

B. Intermittent Feed Method

Initial Dose: When system is noticeably fouled, add appropriate amount of DDDCHLOR per 10,000 gallons of water in the system to obtain 5 to 10 ppm available chlorine. Apply half (or 1/3, 1/4, or 1/5) of this initial dose when half (or 1/3, 1/4, or 1/5) of the water in the system has been lost by blowdown.

Subsequent Dose: When microbial control is evident, add appropriate amount of DDDCHLOR per 10,000 gallons of water in the system to obtain a 1 ppm residual. Apply half (or 1/3, 1/4, or 1/5) of this initial dose when half (or 1/3, 1/4, or 1/5) of the water in the system has been lost by blowdown. Badly fouled systems must be cleaned before treatment is begun.

C. Continuous Feed Method

Initial Dose: When system is noticeably fouled, add appropriate amount of DDDCHLOR per 10,000 gallons in the system to obtain 5 to 10 ppm available chlorine.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

BEST AVAILABLE COPY

JUN 30 1993

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide
registered under EPA Reg. No.

813-19

Subsequent Dose: Maintain this treatment level by starting a continuous feed of 1 oz. of DIOCHLOR per 1,000 gallons water lost by blowdown to maintain a 1.0 ppm residual. Badly fouled systems must be cleaned before treatment is begun.

D. Cooling Tower/Evaporative Condenser Water Treatment Chart

Method	Ounce DIOCHLOR/10,000 Gallons Water			
	12.5%	10%	8%	5.25%
Slug Feed To obtain 5-10 ppm	52-104	66-135	84-88	130-280
Subsequent Dose Maintain 1 ppm residual	11	13	16	25
Intermittent Feed To obtain 5-10 ppm	52-104	66-135	84-108	130-280
Subsequent Dose Maintain 1 ppm residual	11	13	16	25
Continuous Feed To obtain 5-10 ppm	52-104	66-135	84-108	130-280
Subsequent Dose* Maintain 1 ppm residual	1	1.5	2.0	2.5

(*per 1000 gal.)

X. EMERGENCY DISINFECTION AFTER DROUGHTS

A. Supplementary Water Supplies

Gravity or mechanical hypochlorite feeders should be set up on a supplementary line to dose the water to a minimum chlorine residual of 0.2 ppm after a 20 minute contact time. Use a chlorine test kit.

B. Water Shipped in By Tanks, Tank Cars, Trucks, Etc.

Thoroughly clean all containers and equipment. Spray a 50 ppm available chlorine solution and rinse with potable water after 5 minutes. During the filling of the containers, dose with sufficient amounts of DIOCHLOR to provide at least a 0.2 ppm chlorine residual. Use a chlorine test kit.

XI. EMERGENCY DISINFECTION AFTER FIRES

A. Cross Connections or Emergency Connections

Hypochlorination or gravity feed equipment should be set up near the intake of the untreated water supply. Apply sufficient product to give a chlorine residual of at least 0.1 to 0.2 ppm at the point where the untreated supply enters the regular distribution system. Use a chlorine test kit.

XII. EMERGENCY DISINFECTION AFTER FLOODS

A. Wells

Thoroughly flush contaminated casing with a 500 ppm available chlorine solution. Backwash the well to increase yield and reduce turbidity, adding sufficient chlorinating solution to the backwash to produce a 10 ppm available chlorine residual, as determined by a chlorine test kit. After the turbidity has been reduced and the casing has been treated, add sufficient chlorinating solution to produce a 50 ppm available chlorine residual. Agitate the well water for several hours and take a representative water sample. Retreat well if water samples are biologically unacceptable.

BEST AVAILABLE COPY

ACCEPTED
with COMMENTS
in EPA Letter Docket

JUN 30 1993

B. Reservoirs

In case of contamination by overflowing streams, establish hypochlorinating stations upstream of the reservoir. Chlorinate the inlet water until the entire reservoir obtains a 0.2 ppm available chlorine residual, as determined by a suitable chlorine test kit. In case of contamination from surface drainage, apply sufficient product directly to the reservoir to obtain a 0.2 ppm available chlorine residual in all parts of the reservoir.

C. Basins, Tanks, Flumes, Etc.

Thoroughly clean all equipment, then add 20 oz. of 12.5% DDOCHLOR to 5 cu. ft. of water to obtain 800 ppm available chlorine, as determined by a suitable test kit. After 24 hours drain, flush, and return to service. If the previous method is not suitable, spray or flush the equipment with a solution containing 1000 ppm available chlorine. Allow to stand for 2 to 4 hours, flush and return to service. (Using ratio method to calculate concentration, 5.25%, 8 or 10% DDOCHLOR can be used)

D. Filters

When the sand filter needs replacement, apply 80 oz. of 12.5% DDOCHLOR for each 150 to 200 cubic feet of sand. When the filter is severely contaminated, additional product should be distributed over the surface at the rate of 80 oz. per 20 sq. ft. Water should stand at a depth of 1 foot above the surface of the filter bed for 4 to 24 hours. When filter beds can be backwashed of mud and silt, apply 80 oz. of 12.5% DDOCHLOR per each 50 sq. ft., allowing the water to stand at a depth of 1 foot above the filter sand. After 30 minutes, drain water to the level of the filter. After 4 to 6 hours, drain and proceed with normal backwashing. (Using ratio method to calculate concentration, 5.25%, 8 or 10% DDOCHLOR can be used.)

E. Distribution System

Flush repaired or replaced section with water. Establish a hypochlorinating station and apply sufficient product until a consistent available chlorine residual of at least 10 ppm remains after a 24 hour retention time. Use a chlorine test kit.

XIII. EMERGENCY DISINFECTION AFTER MAIN BREAKS

A. Mains

Before assembly of the repaired section, flush out mud and soil. Permit a water flow of at least 2.5 feet per minute to continue under pressure while injecting this product by means of a hypochlorinator. Stop water flow when a chlorine residual test of 50 ppm is obtained at the low pressure end of the new main section after a 24 hour retention time. When chlorination is completed, the system must be flushed free of all heavily chlorinated water.

**XIV. DISINFECTION OF DRINKING WATER (POTABLE)
(Emergency/Public/Individual Systems)**

A. Public System

Mix a ratio of DDOCHLOR to water to produce a 10 ppm available chlorine by weight. Begin feeding this solution with a hypochlorinator until a free available chlorine residual of at least 0.2 ppm and no more than 0.8 ppm is attained throughout the distribution system. Check water frequently with a chlorine test kit. Bacteriological sampling must be conducted at a frequency no less than that prescribed by the National Interim Primary Drinking Water Regulations. Contact your local Health Department for further details.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

BEST AVAILABLE COPY

JUN 30 1993

as free from turbidity as possible. Pour a 100 ppm available chlorine sanitizing solution into the well. Add 5 to 10 gallons of clean, chlorinated water to the well in order to force the sanitizer into the rock formation. Wash the exterior of pump cylinder with the sanitizer. Disconnect pipeline into well, start pump and pump water until strong odor of chlorine in water is noted. Stop pump and wait at least 24 hours. A 24 hours flush well until all traces of chlorine have been removed from the water. Deep wells with high water levels may necessitate the use of special methods for introduction of the sanitizer into the well. Consult your local Health Department for further details.

2. FLOWING ARTESIAN WELLS: Artesian wells generally do not require disinfection. If analysis indicates persistent contamination, the well should be disinfected. Consult your local Health Department for further details.

D. Emergency Disinfection

When boiling of water for 1 minute is not practical, water can be made potable by using this product. Prior to addition of the sanitizer, remove all suspended material by filtration or by allowing it to settle to the bottom. Decant the clarified contaminated water to a clean container and add 1 to 3 drops, (dependent on product strength) to 20 gallon water. Allow the treated water to stand for 30 minutes. Properly treated water should have a slight chlorine odor. If not, repeat dosage and allow the water to stand an additional 15 minutes. The treated water can then be made palatable by pouring it between clean containers several times.

E. Meat and Poultry Plant Treatment

For the treatment of drinking water and water which may be incorporated into food products or directly contact food, use the following concentrations. Chlorine may be present in the process water of meat plants at concentrations of up to 5 ppm. Chlorine may be present in process water of poultry plants at levels up to 20 ppm. Levels calculated in ppm of available chlorine. Use dilution conversion chart to calculate the proper ratio of Hypochlorite solution to water. **SODIUM HYPOCHLORITE** must be dispensed at a constant and uniform flow rate to insure that a controlled rate is maintained.

XV. PUBLIC WATER SYSTEM

A. Reservoirs - Algae Control

Hypochlorite streams feeding the reservoir. Suitable feeding points should be selected on each stream at least 50 yards upstream from points of entry into the reservoir.

B. Mains

Thoroughly flush section to be sanitized by discharging from hydrant. Permit a water flow of at least 2.5 feet per minute to continue under pressure while injecting this product by means of a hypochlorite pump. Stop water flow when a chlorine residual test of 50 ppm is obtained at the low pressure end of the new main section after a 24 hour retention time. When chlorination is completed, the system must be flushed of all heavily chlorinated water.

C. New Tanks, Basins, Etc.

Remove all physical soil from surfaces. Place 20 oz. of 12-1 **SODIUM HYPOCHLORITE** for each 5 cubic feet of working capacity (500 ppm available chlorine). Fill to working capacity and allow to stand for at least 4 hours. Drain and flush with potable water and return to service. (Using ratio method to calculate concentration, 5.25% or **SODIUM HYPOCHLORITE** can be used.)

13

ACCEPTED
with COMMENTS
In EPA Letter Dated:

JUN 30 1993

BEST AVAILABLE COPY

Under the Federal Insecticide,
Fungicide, and Herbicide Act as
amended, for the pesticide
Registered under EPA Reg. No.

813-14

D. New Filter Sand

Apply 80 oz. of 12 1/4% DDOCHLOR for each 150 to 200 cubic feet of sand. The action of the product dissolving as the water passes through the bed will aid in sanitizing the new sand. (Using ratio method to calculate concentration, 5.25%, 8, or 10% DDOCHLOR can be used.)

E. New Wells

Flush the casing with a 80 ppm available chlorine solution. The solution should be pumped or fed by gravity into the well after thorough mixing with agitation. The well should stand for several hours or overnight under chlorination. It may then be pumped until a representative raw water sample is obtained. Bacterial examination of the water will indicate whether further treatment is necessary.

F. Existing Equipment

Remove equipment from service, thoroughly clean surfaces of all physical soil. Sanitize by placing 21 oz. of this product for each 5 cubic feet capacity (approximately 500 ppm available chlorine). Fill to working capacity and let stand at least 4 hours. Drain and place in service. If the previous treatment is not practical, surfaces may be sprayed with a 1000 ppm available chlorine solution. After drying, flush with water and return to service.

XVI. FARM PREMISES

Remove all animals, poultry, and feed from premises, vehicles, and enclosures. Remove all litter and manure from floors, walls and surfaces of barns, pens, stalls, chutes and other facilities occupied or traversed by animals or poultry. Empty all troughs, racks and other feeding and watering appliances. Thoroughly clean all surfaces with soap or detergent and rinse with water. To disinfect, saturate all surfaces with a solution of at least 1000 ppm available chlorine for a period of 10 minutes. Immerse all halter, ropes, and other types of equipment used in handling and restraining animals and poultry, as well as the cleaned forks, shovels, and scrapers used for removing litter and manure. Ventilate buildings, cars, boats and other closed spaces. Do not house livestock or poultry or employ equipment until chlorine has been dissipated. All treated feed racks, mangers, troughs, automatic feeders, fountains and waterers must be rinsed with potable water before reuse.

XVII. LAUNDRY SANITIZERS

A. Household Laundry Sanitizers

1. **IN SOAKING SUDS:** Thoroughly mix DIXICHLOR in wash water to provide 200 ppm available chlorine. Wait 5 minutes, then add soap or detergent. Immerse laundry for at least 11 minutes prior to starting the wash/rinse cycle.

2. **IN WASHING SUDS:** Thoroughly mix DDOCHLOR in wash water containing clothes to provide 200 ppm available chlorine. Wait 5 minutes, then add soap or detergent and start the wash/rinse cycle.

B. Commercial Laundry Sanitizers

Wet fabrics or clothes should be spun dry prior to sanitization. Thoroughly mix DDOCHLOR with water to yield 200 ppm available chlorine. Promptly after mixing the sanitizer, add the solution into the prewash cycle prior to washing fabrics/clothes in the regular wash cycle with a good detergent. Test the level of available chlorine, if solution has been allowed to stand. Add more DDOCHLOR if the available chlorine level has dropped below 200 ppm.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

BEST AVAILABLE COPY JUN 30 1993

XVII. PULP AND PAPER MILL PROCESS WATER SYSTEMS

A. Slug Feed Method

INITIAL DOSE: When system is noticeably fouled, add appropriate amount of DDOCHLOR per 10,000 gallons of water in the system to obtain from 5 to 10 ppm available chlorine. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add appropriate amount of DDOCHLOR per 10,000 gallons of water in the system daily, or as needed, to maintain control and keep the chlorinated residual at 1 ppm. Badly fouled systems must be cleaned before treatment is begun.

B. Intermittent Feed Method

INITIAL DOSE: When system is noticeably fouled, add appropriate amount of DDOCHLOR per 10,000 gallons of water in the system to obtain 5 to 10 ppm available chlorine. Apply half (or 1/3, 1/4, or 1/5) of this initial dose when half (or 1/3, 1/4, or 1/5) of the water in the system has been lost by blowdown.

SUBSEQUENT DOSE: When microbial control is evident, add appropriate amount of DDOCHLOR per 10,000 gallons of water in the system to obtain a 1 ppm residual. Apply half (or 1/3, 1/4, or 1/5) of this initial dose when half (or 1/3, 1/4, or 1/5) of the water in the system has been lost by blowdown. Badly fouled systems must be cleaned before treatment is begun.

C. Continuous Feed Method

INITIAL DOSE: When system is noticeably fouled, add appropriate amount of DDOCHLOR per 10,000 gallons of water in the system to obtain 5 to 10 ppm available chlorine.

SUBSEQUENT DOSE: Maintain this treatment level by starting a continuous feed of 1 oz. of this product per 1,000 gallons of water lost by blowdown to maintain a 1 ppm residual. Badly fouled systems must be cleaned before treatment is begun.

D. Pulp and Paper Mill Process Water Systems Treatment Chart

Method	Ounce DDOCHLOR/10,000 Gallons Water			
	12.5%	10%	8%	5.25%
Slug Feed To obtain 5-10 ppm	52-104	66-132	84-168	130-260
Subsequent Dose Maintain 1 ppm residual	11	13	16	25
Intermittent Feed To obtain 5-10 ppm	52-104	66-132	84-168	130-260
Subsequent Dose Maintain 1 ppm residual	11	13	16	25
Continuous Feed To obtain 5-10 ppm	52-104	66-132	84-168	130-260
Subsequent Dose* Maintain 1 ppm residual	1	1.5	2.0	2.5

(* per 1000 gal.)

ACCEPTED
with COMMENTS
in EPA Letter Datab

BEST AVAILABLE COPY

JUN 30 1993

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No.

SANITIZATION OF NONPOROUS FOOD CONTACT SURFACES**A. Rinse Method**

A solution of 100 ppm available chlorine may be used in the sanitizing solution if a chlorine test kit is available. Solutions containing an initial concentration of 100 ppm available chlorine must be tested and adjusted periodically to insure that the available chlorine does not drop below 50 ppm. Prepare a 100 ppm sanitizing solution by thoroughly mixing required quantity of DODCHLOR with 10 gallons of water. If no test kit is available, prepare a sanitizing solution to provide approximately 200 ppm available chlorine by weight.

Clean equipment surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for at least 2 minutes. If solution contains less than 50 ppm available chlorine as determined by a suitable test kit, either discard the solution or add sufficient product to reestablish a 200 ppm residual. Do not rinse equipment with water after treatment and do not soak equipment overnight.

Sanitizers used in automated systems may be used for general cleaning but may not be reused for sanitizing purposes.

B. Immersion Method

A solution of 100 ppm available chlorine may be used in the sanitizing solution if a chlorine test kit is available. Solutions containing an initial concentration of 100 ppm available chlorine must be tested and adjusted periodically to insure that the available chlorine does not drop below 50 ppm. If no test kit is available, prepare a sanitizing solution to provide approximately 200 ppm available chlorine by weight.

Clean equipment in the normal manner. Prior to use, immerse equipment in the sanitizing solution for at least 2 minutes and allow the sanitizer to drain. If solution contains less than 50 ppm available chlorine, as determined by a suitable test kit, either discard the solution or add sufficient product to reestablish a 200 ppm residual. Do not rinse equipment with water after treatment.

Sanitizers used in automatic systems may be used for general cleaning but may not be reused for sanitizing purposes.

C. Flow/Pressure Method

Disassemble equipment and thoroughly clean after use. Assemble equipment in operating position prior to use. Prepare a volume of a 200 ppm available chlorine sanitizing solution equal to 110% of volume capacity of the equipment. Pump solution through the system until full flow is obtained at all extremities, the system is completely filled with the sanitizer and all air is removed from the system. Close drain valves and hold under pressure for at least 2 minutes to insure contact with all internal surfaces. Remove some cleaning solution from drain valve and test with a chlorine test kit. Repeat entire cleaning/sanitizing process if effluent contains less than 50 ppm available chlorine.

D. Clean-In Place Method

Thoroughly clean equipment after use. Prepare a volume of a 200 ppm available chlorine sanitizing solution equal to 110% of volume capacity of the equipment. Pump solution through the system until full flow is obtained at all extremities, the system is completely filled with the sanitizer and all air is removed from the system. Close drain valves and hold under pressure for at least 10 minutes to insure contact with all internal surfaces. Remove some cleaning solution from drain valve and test with a chlorine test kit. Repeat entire cleaning/sanitizing process if effluent contains less than 50 ppm available chlorine.

E. Spray/Fog Method

Preclean all surfaces after use. Use a 200 ppm available chlorine solution to control bacteria, mold or fungi and a 600 ppm solution to control bacteriophages. Use spray or fogging equipment which can resist hypochlorite solutions. Always empty and rinse spray/fog equipment with potable water after use. Thoroughly spray or fog all surfaces until wet, allowing excess sanitizer to drain. Vacate area for at least 2 hours. Prior to using equipment, rinse all surfaces treated with a 600 ppm solution with a 200 ppm solution.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JUN 30 1993

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide
registered under EPA Reg. No.

813-14

XX.

SANITIZATION OF POROUS FOOD CONTACT SURFACES

- A. Rinse Method**
Clean surfaces in the normal manner. Rinse all surfaces thoroughly with the 600 ppm solution, maintaining contact for at least 2 minutes. Prior to using equipment rinse all surfaces with a 200 ppm available chlorine solution. Do not rinse and do not soak equipment overnight.
- B. Immersion Method**
Clean equipment in the normal manner. Immerse equipment in the 600 ppm solution for at least 2 minutes. Prior to using equipment, immerse all surfaces in a 200 ppm available chlorine solution. Do not rinse and do not soak equipment overnight.
- C. Spray/Fog Method**
Pre-clean all surfaces after use. Prepare a 600 ppm available chlorine sanitizing solution of the required quantity and apply using spray or fogging equipment which can resist hypochlorite solutions. Always empty and rinse spray/fog equipment with potable water after use. Thoroughly spray or fog all surfaces until wet, allowing excess sanitizer to drain. Vacate area for at least 2 hours. Prior to using equipment, rinse all surfaces with a 200 ppm available chlorine solution.

XXI.

SANITIZATION OF NON-POROUS NON-FOOD CONTACT SURFACES

- A. Rinse Method**
Prepare a sanitizing solution to provide approximately 200 ppm available chlorine by weight. Clean equipment surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for at least 2 minutes. Do not rinse equipment with water after treatment and do not soak equipment overnight.
- B. Immersion Method**
Prepare a sufficient quantity of sanitizing solution in an immersion tank, to provide approximately 200 ppm available chlorine by weight. Clean equipment in the normal manner. Prior to use, immerse equipment in the sanitizing solution for at least 2 minutes and allow the sanitizer to drain. Do not rinse equipment with water after treatment.
- C. Spray/Fog Method**
Pre-clean all surfaces after use. Prepare a 200 ppm available chlorine sanitizing solution of sufficient size and apply using spray or fogging equipment which can resist hypochlorite solutions. Prior to using equipment, thoroughly spray or fog all surfaces until wet, allowing excess sanitizer to drain. Vacate area for at least 2 hours.

XXII.

DISINFECTION OF NON-POROUS NON-FOOD CONTACT SURFACES

- A. Rinse Method**
Prepare a disinfecting solution to provide approximately 600 ppm available chlorine by weight. Clean equipment surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the disinfecting solution, maintaining contact with the solution for at least 10 minutes. Do not rinse equipment with water after treatment and do not soak equipment overnight.
- B. Immersion Method**
Prepare a disinfecting solution in an immersion tank, to provide approximately 600 ppm available chlorine by weight. Clean equipment in the normal manner. Prior to use, immerse equipment in the disinfecting solution for at least 10 minutes and allow the sanitizer to drain. Do not rinse equipment with water after treatment.

ACCEPTED

WITH COMMENTS

BEST AVAILABLE COPY with COMMENTS
in EPA Library Catalog

JUN 30 1993

XXIII. SANITIZATION OF POROUS NON-FOOD CONTACT SURFACES

A. Rinse Method

Prepare a sanitizing solution to provide approximately 600 ppm available chlorine by weight. Clean surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for at least 2 minutes. Do not rinse equipment with water after treatment and do not soak equipment overnight.

B. Immersion Method

Prepare a sanitizing solution, in an immersion tank, to provide approximately 600 ppm available chlorine by weight. Clean equipment in the normal manner. Prior to use, immerse equipment in the sanitizing solution for at least 2 minutes and allow the sanitizer to drain. Do not rinse equipment with water after treatment.

C. Spray/Fog Method

After cleaning, sanitize non-food contact surfaces with 600 ppm available chlorine, using spray or fogging equipment which can reslet hypochlorite solutions. Always empty and rinse spray/fog equipment with potable water after use. Prior to using equipment, thoroughly spray or fog all surfaces until wet, allowing excess sanitizer to drain. Vacate area for at least 2 hours.

XXIV. SEWAGE AND WASTEWATER EFFLUENT TREATMENT

The disinfection of sewage effluent must be evaluated by determining the total number of coliform bacteria and/or fecal coliform bacteria, as determined by the Most Probable Number (MPN) procedure, if the chlorinated effluent has been reduced to or below the maximum permitted by the controlling regulatory jurisdiction.

On the average, satisfactory disinfection of secondary wastewater effluent can be obtained when the chlorine residual is 0.5 ppm after 15 minutes contact. Although the chlorine residual is the critical factor in disinfection, the importance of correlating chlorine residual with bacterial kill must be emphasized. The MPN of the effluent, which is directly related to the water quality standards requirements, should be the final and primary standard and the chlorine residual should be considered an operating standard valid only to the extent verified by the coliform quality of the effluent.

The following are critical factors affecting wastewater disinfection:

1. **Mixing:** It is imperative that the product and the wastewater be instantaneously and completely flash mixed to assure reaction with every chemically active soluble and particulate component of the wastewater.
2. **Contacting:** Upon flash mixing, the flow through the system must be maintained.
3. **Dosage/Residual Control:** Successful disinfection is extremely dependent on response to fluctuating chlorine demand to maintain a predetermined, desirable chlorine level. Secondary effluent should contain 0.2 to 1.0 ppm chlorine residual after a 15 to 30 minute contact time. A reasonable average of residual chlorine is 0.5 ppm after 15 minutes contact time.

XXV. SEWAGE AND WASTEWATER TREATMENT

A. Effluent Slime Control

Apply a 100 to 1000 ppm available chlorine solution at a location which will allow complete mixing. Once control is evident, apply a 15 ppm available chlorine solution.

B. Filter Beds - Slime Control

Remove filter from service, drain to a depth of 1 ft. above filter sand, and add 80 oz. of 12% DDOCHLOR per 20 sq./ft. evenly over the surface. Wait 30 minutes before draining water to a level that is even with the top of the filter. Wait for 4 to 6 hours before completely draining and backwashing filter. (Using ratio method to calculate concentration, 5.25%, 8 or 10% DDOCHLOR can be used.)

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JUN 30 1993

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide
registered under EPA Reg. No.

813-14

XXVI.

SANITIZATION OF DIALYSIS MACHINES

Flush equipment thoroughly with water prior to using this product. Thoroughly mix DDXCHLOR TO 10 gallons of water to obtain at least 600 ppm available chlorine. Immediately use this product in the hemodialysis system allowing for a minimum contact time of 15 minutes at 20°C. Drain the system of the sanitizing solution and thoroughly rinse with water. Discard and DO NOT reuse the spent sanitizer. Residuals must be monitored with a suitable test kit to insure that no available chlorine remains in the system.

This product is recommended for decontaminating single and multipatient hemodialysis systems. This product has been shown to be an effective disinfectant (virucide, fungicide, bactericide, pseudomonocide) when tested by APAC and EPA test methods. This product may not totally eliminate all vegetative microorganisms in hemodialysis delivery systems due to the construction and/or assembly, but can be relied upon to reduce the number of microorganisms to acceptable levels when used as directed. This product should be used in a disinfectant program which includes bacteriological monitoring of the hemodialysis delivery system. This product is NOT recommended for use in hemodialysis or reverse osmosis (RO) membranes.

Consult the guidelines for hemodialysis systems which are available from the Hepatitis Laboratories, DCD, Phoenix, AR 65021.

XXVII.

SPAS, HOT-TUBS, IMMERSION TANKS, ETC.

A. Spas/Hot-Tubs

Using Chart or Formula, calculate and approximate an amount of DDXCHLOR per 1000 gallons of water to obtain a free available chlorine concentration of 5 ppm, as determined by a suitable chlorine test kit. Adjust and maintain pool water pH to between 7.2 and 7.8. Some oils, lotions, fragrances, cleansers, etc. may cause foaming or cloudy water as well as reduce the efficiency of the product.

1. *Maintaining the Water:* To maintain the water, apply DDXCHLOR solution over the surface to maintain a chlorine concentration of 5 ppm.
2. *After Each Use:* Shock treat to control odor and algae, using DDXCHLOR at a rate of 8 ounces of 12½% to 500 gallons of water. (Use chart or formula when using 5.25, 8 or 10% DDXCHLOR.)
3. *Periods of Closure:* During periods of closure, add DDXCHLOR daily to maintain a 3 ppm chlorine concentration.

B. Hubbard and Immersion Tanks

Before patient use add DDXCHLOR to obtain a chlorine residual of 25 ppm, as determined by a suitable test kit. Adjust and maintain the water pH to between 7.2 and 7.8. After each use drain the tank. Add 5 ounces of 12½% DDXCHLOR to a bucket of water and circulate this solution through the agitator of the tank for 15 minutes and then rinse out the solution. Clean tank thoroughly and dry with clean cloths. (Use chart or formula when using 5.25, 8 or 10% DDXCHLOR.)

C. Hydrotherapy Tanks

Add DDXCHLOR to the water to obtain a chlorine residual of 1 ppm, as determined by a suitable chlorine test kit. Pool should not be entered until the chlorine residual is below 3 ppm. Adjust and maintain the water pH to between 7.2 and 7.8. Operate pool filter continuously. Drain pool weekly, and clean before refilling.

BEST AVAILABLE COPY

ACCEPTED
with COMMENTS
in EPA Letter D-111

JUN 30 1993

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended for the pesticide
registered under EPA Reg. No.

XXVII. SWIMMING POOL WATER DISINFECTION

A. New Pool or Spring Start-Up

For a new pool or spring start-up, superchlorinate with DDOCHLOR to yield a 5 to 10 ppm available chlorine by weight. Check the level of available chlorine with a test kit. Adjust and maintain pool water pH to between 7.2 to 7.8. Adjust and maintain the alkalinity of the pool to between 50 to 100 ppm.

B. Maintaining the Pool

To maintain the pool, add manually or by a feeder device a sufficient quantity of DDOCHLOR to yield an available chlorine residual between 0.5 to 1.0 ppm by weight. Stabilized pools should maintain a residual of 1.0 to 1.5 ppm available chlorine. Test the pH, available chlorine residual, and alkalinity of the water frequently with appropriate test kits. Frequency of water treatment will depend upon temperature and number of swimmers.

C. Superchlorination

Every 7 (seven) days, or as necessary, superchlorinate the pool with DDOCHLOR to yield a 5 to 10 ppm available chlorine by weight. Check the level of available chlorine with a test kit. Do not reenter pool until the chlorine residual is between 1.0 to 3.0 ppm.

D. End of Swimming Pool Season

At the end of the swimming pool season or when the water is to be drained from the pool, chlorine must be allowed to dissipate from treated pool water before discharge. Do not chlorinate the pool within 24 hours prior to discharge.

E. Winterizing Pool

While water is still clear, and while filter system is in service, apply DDOCHLOR in quantities to obtain a 3 ppm available chlorine residual, as determined by a suitable test kit. Cover pool, prepare heater, filter and heater components for winter by following manufacturers' instructions.

F. Swimming Pool Disinfection Chart

Method	Ounce DDOCHLOR/10,000 Gallons Water			
	12.5%	10%	8%	5.25%
Start-Up	52-104	64-128	80-160	122-244
Maintenance	11	13	16	25
Superchlorination	52-104	64-128	80-160	122-244
Winterizing	30	30	16	75

ACCEPTED
with COMMENTS
in EPA 600/3-93/011

JUN 30 1993

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, this pesticide is
registered under EPA Reg. No.

813-14