

PM 31

875-138

1 of 3

Please read instructions on reverse before completing form.

Form Approved. OMB No. 2070-0060. Approval expires 05-31-98

	United States	<input type="checkbox"/> Registration	OPP Identifier Number 246753
	Environmental Protection Agency	<input type="checkbox"/> Amendment	
	Washington, DC 20460	<input checked="" type="checkbox"/> Other	

875 Application for Pesticide - Section I

1. Company/Product Number 805-138	2. EPA Product Manager	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) Gax-26	PM#	
5. Name and Address of Applicant (Include ZIP Code) Diversey Corp. 12025 Tech Center Drive Livonia, MI 48150-2193 <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

Notification: Compliance with P.R. Notice 95-1. See attached certification and product label.

Section - III

1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes* <input type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No		<input type="checkbox"/> Metal	<input type="checkbox"/> Plastic
* Certification must be submitted		If "Yes" Unit Packaging wgt.	No. per container	<input type="checkbox"/> Glass	<input type="checkbox"/> Paper
		If "Yes" Package wgt	No. per container	<input type="checkbox"/> Other (Specify) _____	
3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container		5. Location of Label Directions <input type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product	
6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled				<input type="checkbox"/> Other _____	

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)

Name Henry P. Katstra	Title Manager, Regulatory Affairs	Telephone No. (Include Area Code) (313) 458-2444
---------------------------------	---	--

Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.			6. Date Application Received (Stamped)
2. Signature <i>Henry P. Katstra</i>	3. Title Manager, Regulatory Affairs		
4. Typed Name Henry P. Katstra	5. Date 8/21/95		

Sept

NPDES Statement Modified to
PR-93-10 language

Precautionary Statements
Hazards to Humans and Domestic Animals
KEEP OUT OF REACH OF CHILDREN.
DANGER:

CORROSIVE. Causes eye damage and skin burns. May cause allergic skin reaction. May be harmful if inhaled. May be fatal if swallowed or absorbed through the skin. Do not get in eyes, on skin, or clothing. Wear goggles or face shield and rubber gloves when handling. Avoid breathing vapor or mist. Avoid contamination of food. Do not take internally. Wash thoroughly after handling.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL:

- Do not contaminate water, food, or feed by storage or disposal.
- Open dumping is prohibited.
- Do not reuse container.

Pesticide Disposal: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

Container Disposal: Metal Containers – Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

Plastic Containers – Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke.

General: Consult Federal, State or local disposal authorities for approved alternative procedures.



For Industry Use

Controls Bacteria, Algae and Fungi in Industrial Recirculating Water Cooling Towers and Air Washer Systems and Bacteria and Fungi in Metalworking Fluids.

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one	1.15%
2-Methyl-4-isothiazolin-3-one	0.35%
INERT INGREDIENTS	98.50%
	TOTAL 100.00%

KEEP OUT OF REACH OF CHILDREN.
DANGER

STATEMENT OF PRACTICAL TREATMENT:

IF SWALLOWED: Do not induce vomiting. Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

IF INHALED: Remove immediately to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen and call a physician.

IF ON SKIN: Wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse.

IF IN EYES: Flush with plenty of water for at least 15 minutes. Call a physician.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be needed.

See left side panel for additional precautionary statements.

Diversey Corp. • Livonia MI 48150-2193 • 313 458 5000
24 HOUR EMERGENCY TELEPHONE • Medical: (Call Collect)
303 592 1024 • Transportation: (CHEMTREC) 800 424 9300

Net Contents 55 Gal (208.2 L);

PMS Pantone Yellow • 8.5" x 17"

BEST AVAILABLE COPY



06166472

3013



DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

Initial Dose: When the system is noticeably fouled apply 2.46 to 7.46 lbs. (37 to 113 fluid ounces) of GAX-26 per 1000 gallons of water in the system. Repeat until control is achieved. For the control of bacteria and fungi add GAX-26 to the lower basin, distribution box or some other point to insure uniform mixing.

Subsequent Dose: When microbial control is evident, add 1.26 to 1.86 lbs. (19 to 28 fluid ounces) of GAX-26 per 1000 gallons of water in the system weekly or as needed to maintain control. Badly fouled system must be cleared before treatment is begun. GAX-26 weighs 8.4 lbs. per gallon.

AIR WASHER SYSTEMS

Add to the air washer sump or chill water sump to insure uniform mixing 35 to 883 ppm (0.3 to 7.46 lbs. or 4.5 to 113 fluid ounces per 1000 gallons of water in the system) depending upon the severity of contamination to control bacteria, fungi and algae which cause fouling in industrial air washer systems.

INTERMITTENT OR SLUG METHOD

Initial dose: When the system is noticeably fouled, apply 148 to 883 ppm (1.26 to 7.46 lbs. or 19 to 113 fluid ounces per 1000 gallons of water in the system). Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 35 to 219 ppm (0.3 to 1.86 lbs. or 4.5 to 28 fluid ounces per 1000 gallons of water) weekly or as needed to maintain control.

CONTINUOUS FEED METHOD

Initial dose: When the system is just noticeably fouled, apply 148 to 883 ppm (1.26 to 7.46 lbs. or 19 to 113 fluid ounces per 1000 gallons of water in the system).

Badly fouled systems must be cleaned before initial treatment.

Subsequent Dose: Maintain this treatment level by adding a continuous feed of 35 to 219 ppm (0.3 to 1.86 lbs. or 4.5 to 28 fluid ounces per 1000 gallons of makeup water).

METALWORKING FLUIDS:

GAX-26 is recommended for the control of bacteria and fungi in soluble and emulsifiable type aqueous metalworking

fluids, such as emulsified petroleum oils, and formulations containing alcoholic fatty acid, sulfonated red oil, or naphthalene sulfonate. These fluids are usually prepared by diluting the product concentrates 1.40 to 1.60 with water. For the maintenance of a nonfouled system, use GAX-26 at 32 fluid ounces per 1000 gallons of emulsion (2 lbs.) every 4 weeks or 32 to 154 fluid ounces per 1000 gallons emulsion (2 to 10 lbs.) every 8 to 12 weeks. For a noticeably fouled system use an initial dose of 64 to 154 fluid ounces per 1000 gallons emulsion, (4 to 10 lbs.) to be allowed by subsequent maintenance dosages, depending upon the treatment interval noted above. A higher dosage range and/or increased frequency of treatment may be required depending upon rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. The preservative should be dispensed into the use-dilution of the metalworking fluid using a metering pump.

PAPER MILLS

GAX-26 is recommended for the control of bacteria and fungal slime in the production of paper.

Point of Addition: GAX-26 should be added to a point in the system to insure uniform mixing such as the Beater, Hydropulper, Fan or Broke Storage Pumps.

Dosage: Apply 0.44 to 1.5 Lbs. (7 to 23 fluid ounces) of GAX-26 per ton (dry basis) of pulp or paper produced as a slug dose. If needed, repeat daily. Badly fouled systems should be cleaned before initial treatment.

NOTICE: Seller warrants that the product conforms to its chemical description and is reasonably fit for the purposes stated on the label when used in accordance with directions under normal conditions of use, but neither this warranty nor any other warranty of MERCHANTABILITY OF FITNESS FOR A PARTICULAR PURPOSE, express or implied, extends to the use of this product contrary to label instructions or under abnormal conditions, or under conditions not reasonably foreseeable to seller and buyer assumes the risk of any such use.



EPA Registration No.: 875-138

EPA Establishment No.:

875-WI-1[1] 875-OH-1[5]

875-TX-3[3] 875-PA-1[8]

875-CA-2[4]

Bracketed number is the first digit of the batch number

A(952108)cp.1

**CORROSIVE LIQUID,
BASIC, ORGANIC,
N.O.S., (ISOTHIAZOLONE
COMPOUNDS),
UN3267**

BEST AVAILABLE COPY

