# **CAUTION: COMBUSTIBLE M'XTURE**

#### N.Y.F.D. C. of A. No. 4178

#### WARNING

May be fatal if swallowed! Do not use near heat or open flame. Do not use as a space spray (AEROSOL or Fogging). Do not breathe vapor or spray mist. Keep out of reach of children. Do not get on skin. In case of contact, wash immediately with soap and water. Store this product at temperatures above 50 F. Do not contaminate feed and foodstuffs.

This product is toxic to fish, birds and other wildlife. Birds feeding on treated areas may be killed. Keep out of lakes, streams or ponds. Do not apply where runoff is likely to occur. Do not apply when weather conditions favor drift from areas treated. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

DO NOT USE, POUR, SPILL OR STORE NEAR HEAT OR OPEN FLAME.

#### ANTIDOTE

**EXTERNAL** — In case of spillage on skin, wash promptly with soap and water.

**INTERNAL** — Emetic of 1 tablespoonful mustard in tumbler of water. Call a physician.

#### **CONTAINER DISPOSAL**

Rinse equipment and containers and dispose of wastes by burying in noncroplands away from water supplies. Containers should be disposed of by punching holes in them and burying with wastes, or by burning. Keep out of smoke.

**NOTICE** — Because Velsicol Chemical Corporation has no control over storage. handling, and conditions of use, which are of critical importance, Velsicol Chemical Corporation makes no representation or warranty, either express or implied, for results due to misuse, improper handling or storage of this material. Nor does Velsicol Chemical Corporation assume any responsibility for injury to persons. crops, animals, soil or property arising out of misuse, improper handling or storage of this material.

# **Directions For Use**

#### **GOLD CREST H-72 TERMITE CONTROL**

To meet FHA termite proofing requirements, consult the latest editions of the Housing and Urban Development (HUD) Minimum Property Standards or send for Velsicol Bulletin Number 01-053-502.

Add 1 gallon of Gold Crest H-72 emulsifiable to 71 gallons of water for a 0.5% emulsion. Apply the 0.5% emulsion as follows.

When application is by rodding, rods should be inserted one foot apart to the base of the footings. Applications should be made by pressure applied through the tube.

#### CONCRETE SLAB-ON-GROUND CONSTRUCTION

- **1** Apply an over-all treatment under entire surface of floor slab. Apply at the rate of 1 gallon per 10 square feet, except that if fill under slab is gravel or other coarse absorbent material, apply at the rate of  $1\frac{1}{2}$ gallons per 10 square feet.
- 2 Under slab-on-ground porch floors and entrance platforms apply an overall treatment at the rate of 1 gallon per 10 square feet.
- 3 Along both sides of foundation walls, along interior toundation walls, and around plumbing, rod or dig a narrow trench to a depth of 1 foot, but not

.

02178 303AD







Manufactured and distributed by

# **INSECTICIDE FOR USE ONLY BY** PROFESSIONAL APPLICATORS

E.P.A. Reg. No. 876-101-AA E.P.A. Est. No. 876-TN-1

in Street, Shicago, Illinois 60611

- below t should | linear f€ being re
- 4 Treat all least 1 c the footi

#### BUILDIN

- 1 Rod or the four 2 gallon
- be mixe 2 Rod or (
- the four inches.
- foot of c per 5 lin
- as it is t
- 3 Under a situatior 10 squar
- 4 Treat al 1 gallon footing.

## BUILDIN

- **1** Apply a under at situation per 10 : cinders half. Wh
- 2 Rod or ( foundati of soluti with the
- 3 Along th trench ti A de thi . plof th app'y an fee with a
- to the top soil and the back depth re greater t narrow t 4 Treat all 1 gallon

### PRECON

footing.

If soil is tru the same d be placed where four have alreac Premises tr mum of five

# **CAUTION: COMBUSTIBLE MIXTURE**

N.Y.F.D. C. of A. No. 4178

#### WARNING

May be fatal if swallowed! Do not use near heat or open flame. Do not use as a space spray (AEROSOL or Fogging). Do not breathe vapor or spray mist. Keep out of reach of children. Do not get on skin. In case of contact, wash immediately with soap and water. Store this product at temperatures above 50 F. Do not contaminate feed and foodstuffs.

This product is toxic to fish, birds and other wildlife. Birds feeding on treated areas may be killed. Keep out of lakes, streams or ponds. Do not apply where runoff is likely to occur. Do not apply when weather conditions favor drift from areas treated. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

DO NOT USE, POUR, SPILL OR STORE NEAR HEAT OR OPEN FLAME.

#### **ANTIDOTE**

EXTERNAL --- In case of spillage on skin, wash promptly with soap and water.

**INTERNAL** — Emetic of 1 tablespoonful mustard in tumbler of water. Call a physician.

#### CONTAINER DISPOSAL

Rinse equipment and containers and dispose of wastes by burying in noncroplands away from water supplies. Containers should be disposed of by punching holes in them and burying with wastes, or by burning. Keep out of smoke.

**NOTICE -- Because Velsicol Chemical Corporation has no control over storage.** handling, and conditions of use, which are of critical importance, Velsicol Chemical Corporation makes no representation or warranty, either express or implied, for results due to misuse, improper handling or storage of this material. Nor does Velsicol Chemical Corporation assume any responsibility for injury to persons, crops, animals, soil or property arising out of misuse, improper handling or storage of this material.

# **Directions For Use**

#### **GOLD CREST H-72 TERMITE CONTROL**

To meet FHA termite proofing requirements, consult the latest editions of the Housing and Urban Development (HUD) Minimum Property Standards or send for Velsicol Bulletin Number 01-053-502.

Add 1 gallon of Gold Crest H-72 emulsifiable to 71 gallons of water for a 0.5% emulsion. Apply the 0.5% emulsion as follows.

When application is by rodding, rods should be inserted one foot apart to the base of the footings. Applications should be made by pressure applied through the tube.

#### **CONCRETE SLAB-ON-GROUND CONSTRUCTION**

- **1** Apply an over-all treatment under entire surface of floor slab. Apply at the rate of 1 gallon per 10 square feet, except that if fill under slab is gravel or other coarse absorbent material, apply at the rate of  $1\frac{1}{2}$ galions per 10 square feet.
- 2 Under slab-on-ground porch floors and entrance platforms apply an overall treatment at the rate of 1 gallon per 10 square feet.
- 3 Along both sides of foundation walls, along interior foundation walls, and around plumbing, rod or dig a narrow trench to a depth of 1 foot, but not

02178-303AD

<u>6 1976</u> FEB Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 876-101

ACCEPTED

Manufactured and distributed by







EMULSIFIABLE CONCENTRATE

# **INSECTICIDE FOR USE ONLY BY PROFESSIONAL APPLICATORS**

E.P.A. Reg. No. 876-101-AA E.P.A. Est. No. 876-TN-1

- below t should I linear fe being re
- 4 Treat all least 1 c the footi

### BUILDIN

- 1 Rod or the four 2 gallon
- be mixe 2 Rod or (
- the four inches. foot of c
- per 5 lin as it is t
- 3 Under al situatior 10 squar
- 4 Treat all 1 gallon footing.

### BUILDIN

- 1 Apply a under at situation per 10 1 cinders half. Wh
- 2 Rod or c foundati of solutio with the
- 3 Along th trench te wider the top of th apply an fill with a to the to soil and the back
- depth re greater t narrow t 4 Treat all
- 1 gallon footing.

### PRECON

If soil is tri the same d be placed where foul have alread Premises ti mum of five



s, and out not

VELSICOL CHEMICAL CORPORATION 341 E. Ohio Street, Chicago, Illinois 60611

#### **Use Directions (Continued)**

below the top of the footing. Along outside foundation walls, trench should be no wider than six inches. Apply at the rate of 2 gallons per 5 linear feet of trench. The chemical should be mixed with the soil as it is being replaced in the trench.

4 Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. Apply the emulsion so as to reach the footing.

#### **BUILDINGS WITH CRAWL SPACES**

- 1 Rod or dig a narrow trench to the top of the footing along the inside of the foundation walls, around piers, sewers, pipes and conduits. Apply 2 gallons of solution per 5 linear feet. When trenching, chemical should be mixed with the soil as it is being replaced in the trench.
- 2 Rod or dig a narrow trench to the top of the footing along the outside of the foundation wall. If a trench is dug, it should be no wider than six inches. Apply 2 gallons of solution per 5 linear feet of trench per each foot of depth. Rodding or trenching 3 feet deep would require 6 gallons per 5 linear feet. When trenching, chemical should be mixed with the soil as it is being replaced in the trench.
- 3 Under attached porches, entrance platforms, utility entrances and similar situations where slab or fill is at the same grade level apply 1 gallon per 10 square feet of soil surface.
- 4 Treat all voids in hollow masonry units of the foundation at the rate of 1 gallon per 5 linear feet of wall. Apply the emulsion so as to reach the footing.

#### **BUILDINGS WITH BASEMENTS**

- 1 Apply an over-all treatment under the basement floorings, as well as under attached porches, entrance platforms, utility entrances and similar situations where slab fill is at the grade level. Apply at the rate of 1 gallon per 10 square feet, except that if fill under slab is of washed gravel, cinders or similar coarse material, increase the dosage by at least onehalf. Where crawl spaces exist, treat as described in part 2 below.
- 2 Rod or dig a narrow trench to the top of the footing along the inside of foundation walls, around piers, sewer pipes and conduits. Apply 2 gallons of solution per 5 linear feet. When trenching, chemical should be mixed with the soil as it is being replaced in the trench.
- 3 Along the outside of foundation walls, rod or dig a narrow trench, such trench to be dug no deeper than the top of the footings and to be no wider than six inches. If the trench is less than 15 inches in depth to the top of the footings, apply 1 gallon per 5 linear feet. Replace the soil and apply another 1 gallon per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply 2 gallons per linear feet. Replace the soil and apply another 2 gallons per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. A trench 30 inches deep is a maximum depth required alongside foundations where the top of the footings is greater than 30 inches deep. In lieu of trenching to a 30" depth. make a narrow trench and rod to footing, spacing the holes about 1 foot apart.
- 4 Treat all voids in hollow masonry units of the foundation at the rate of 1 gallon per 5 linear feet of wall. Apply the emulsion so as to reach the footing.

#### PRECONSTRUCTION TREATMENT

If soil is treated and the concrete slab is not poured shortly thereafter on the same day, a polyethylene sheeting or other waterproof material should be placed over the treated soil. However, this procedure is not required where foundation cinder blocks or bricks surrounding the treated area have already been installed.

611 Premises treated with Gold Crest H-72 will give residual control for a minimum of five years.