

PRE-SLAB TREATMENT: Apply one gallon of dilute material to each 10 square feet as an overall treatment under the slab and basement floor, as well as under attached porches and entrance platforms. Make application to the graded area. On washed gravel, cinders, or similar coarse material, increase dosage to 1 gallon per 7 square feet.

WARNING! Hazardous If Swallowed, Inhaled, or Absorbed through Skin! Do not breathe spray mist. Do not get in eyes, on skin or on clothing. In case of contact, immediately remove contaminated clothing and flush skin or eyes with plenty of water; for eyes, get medical attention. Wash thoroughly with soap and water after handling and before eating or smoking; wear clean clothing. During commercial or prolonged exposures in spray-mixing and loading operations, wear clean synthetic rubber gloves and a mask or respirator of a type passed by the U. S. Department of Agriculture for Dieldrin protection. Keep out of reach of children. Keep container closed. **STORE AWAY FROM HEAT AND OPEN FLAME.**

This product is highly toxic to fish and wildlife. Keep out of any body of water. Do not contaminate any body of water by direct application, cleaning of equipment, or disposal of wastes or containers.

Apply this product only as specified on this label.

NOTICE: Buyer assumes all risks of use, storage, or handling of this material not in strict accordance with directions given herewith.

U.S.D.A. Registration No. 904-172

B. G. PRATT COMPANY, PATERSON, N. J. 07509

©1970 B.G.P. Co.



FOR USE IN CONTROL OF SUBTERRANEAN TERMITES

ACTIVE INGREDIENTS	By Weight
Dieldrin*	18.0%
Aromatic Petroleum Derivative	77.0%
INERT INGREDIENTS	5.0%
	TOTAL 100.0%

*Equivalent to 15.3% Hexachloroepoxyoctahydro-endo, exo-dimethanonaphthalene and 2.7% related compounds.

WARNING: KEEP OUT OF REACH OF CHILDREN

See side panel for complete caution statement

NET CONTENTS: 1 LIQUID GALLON

For Use By Professional Pest Control Operators Only

CONTAINS: 1.5 LBS. DIELDRIN PER GALLON

One gallon dilutes with water to treat 75 linear feet of full foundation wall or 150 linear feet of slab construction wall. One gallon treats 600 square feet of graded area before pouring slab or basement floor.

DIRECTIONS

DILUTION: Mix 1 gallon with 60 gallons of water (8 fluid ounces in 3¾ gallons of water). Agitate frequently while using to assure uniformity.

Dig an 8 inch trench along the exterior of foundation, exposing wall to a depth of 15 inches. For deep foundations, dig trench to a maximum depth of 30 inches or make 1 inch holes 15 inches deep at 8 inch intervals in the bottom of a 15 inch trench. **DO NOT DIG BELOW FOOTINGS.** If the depth of the trench to the top of the footings does not exceed 15 inches, apply 1 gallon of dilute solution to each 5 linear feet of trench. Replace the soil and repeat the 1 gallon per 5 linear feet treatment to the back fill. Apply 1 gallon per 5 linear feet to the bottom of the 30 inch trench or double that to the bottom of a 15 inch trench with additional 15 inch holes. Repeat the application of 1 gallon per 5 linear feet to each 10 inch depth of the back fill. Cover treated area with thin layer of soil. Treat all voids in hollow masonry units and other points of entry such as pipes and conduits.

For buildings or portions of buildings with only a crawl space, treat only the areas under the house such as along inside walls, around sewer pipes and conduits. Use 2 gallons of dilute solution per 5 linear feet of trench as directed above.

