

PM-32

Reg # 935-71

195

TOWERBROM® 60M GRANULES**ACTIVE INGREDIENTS:**

Sodium Dichloro-s-triazinetriene 90%

Sodium Bromide 7%

INERT INGREDIENTS 3%

100%

Provides 57% available Chlorine

Provides up to 128% available Bromine with continued use in accordance with the
Directions for UseWhen used as directed, this product is a high performance bromine microblocker which aids in the control of organic
slimes of algae, bacteria and fungi in water systems.**KEEP OUT OF REACH OF CHILDREN****DANGER****STATEMENT OF PRACTICAL TREATMENT (FIRST AID)****IF SWALLOWED**, drink large amounts of water. **DO NOT** induce vomiting. Avoid
alcohol. Call a physician or poison control center immediately.**FOR EYES**: OBJECT IS TO FLUSH MATERIAL OUT IMMEDIATELY THEN SEEK
MEDICAL ATTENTION. IMMEDIATELY flush eyes with large amounts of water for at
least 15 minutes forcibly holding lids apart to ensure complete irrigation of all eye and
lid tissue. Washing eyes within one (1) minute is essential to achieve maximum
effectiveness. SEEK MEDICAL ATTENTION IMMEDIATELY.**FOR SKIN**: Immediately brush off excess chemical and flush with plenty of water.
Remove contaminated clothing. Wash clothing before reuse. GET MEDICAL
ATTENTION if irritation persists.**IF INHALED**: Remove to fresh air. If breathing is difficult, have trained person
administer oxygen. If respiration stops, give mouth-to-mouth resuscitation. GET
MEDICAL ATTENTION.**NOTE TO PHYSICIAN**: Probable mucosal damage may contraindicate the use of
gastric lavage.

See side panel for DIRECTIONS FOR USE

EPA Est. No. 58401-MO-1

EPA Reg. No. 935-71

Occidental Chemical Corporation

Basic Chemicals Group

Dallas, Texas 75380

214-404-3800

24 Hour Emergency Phone: 1-800-733-3665

ACCEPTED**MAY 30 1995**Under Federal Insecticide,
Rodenticide Act, as amended, for the
pesticide registered under
EPA Reg. No. 935-71

NET WT. 50 LBS./22.7 KG.

HMIS RATING SYSTEM: HEALTH 3 FLAMMABILITY 1 REACTIVITY 2

195

235

PRECAUTIONARY STATEMENTS**HAZARD TO HUMANS AND DOMESTIC ANIMALS****DANGER**

CORROSIVE. CAUSES EYE AND SKIN DAMAGE. IRRITATING TO NOSE AND THROAT. HARMFUL OR FATAL IF SWALLOWED. Prolonged ingestion of large amounts may cause adverse central nervous system effects.

Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid breathing dust or fumes. Wash thoroughly with soap and water after handling. Remove and wash contaminated clothing before reuse.

ENVIRONMENTAL HAZARD

This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product into sewer systems without previously notifying the sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of EPA.

PHYSICAL OR CHEMICAL HAZARD

STRONG OXIDIZING AGENT. Contact with water slowly liberates irritating and hazardous chlorine and bromine containing gases. Decomposes at temperatures above 464°F with liberation of harmful gases. When ignited, will burn with the evolution of chlorine and equally toxic gases.

NEVER add water to product. Always add product to large quantities of water. Use clean, dry utensils. **DO NOT** add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to fire or explosion. Contamination with moisture, organic material, or other chemicals may start a chemical reaction with generation of heat, liberation of hazardous gases, and possible fire and explosion. **DO NOT** add this product to a tablet feeder. Use a pot or shock feeder for granules only if high water flow rates can be assured. Mixtures of this product with 10-50% water in a confined space may result in destructive over pressurization.

IN CASE OF FIRE OR SMOKE:

Call the fire department. Do not attempt to extinguish the fire without a self contained breathing apparatus (SCBA). Do not let the fire burn. **Flood with copious amounts of water.** **DO NOT** use ABC or other dry chemical extinguishers since there is the potential for a violent reaction.

IN CASE OF CONTAMINATION OR DECOMPOSITION: DO NOT reseal container. Follow disposal instructions on label.

395

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

FOR CONTROL OF BACTERIA, FUNGI AND ALGAE IN RECIRCULATING WATER SYSTEMS, SEWAGE WASTEWATER SYSTEMS, PULP AND PAPER MILL WATER SYSTEMS AND ONCE-THROUGH WATER SYSTEMS

FOR RECIRCULATING WATER SYSTEMS

This product is intended for use in the following aquatic sites: Air Washer Water Systems, Commercial/Industrial Water Cooling Systems, Evaporative Condenser Water Systems, Ornamental Ponds and Aquaria, Heat Exchange Water Systems, Lakes/Ponds/Reservoirs (Without Human or Wildlife Use), Industrial Scrubbing Systems, Industrial Auxiliary Water Systems, Industrial Process Water, Industrial Waste Disposal Systems, Pasteurizer/Warmer/Cannery Cooling Water Systems.

This product may be added to the system by direct placement into the water at a point where the product will be uniformly mixed with water. The frequency of feeding and duration of the treatment will depend on the severity of the contamination. Badly fouled systems must be cleaned before treatment begins.

Intermittent or slug method

Initial Dose: When the system is noticeably fouled, add this product at the rate of 0.15 to 0.75 pounds per 1000 gallons (18 to 90 grams per 1000 liters) in the system to achieve 0.5-10 mg/L total available halogen as chlorine, as measured by a suitable test kit. Repeat dosage until residual is achieved.

Subsequent Dose: When microbial control is evident, add this product at the rate of 0.03 to 0.15 pounds per 1000 gallons (3.6 to 18 grams per 1000 liters) in the system to achieve 0.5-1 mg/L total available halogen as chlorine, as measured by a suitable test kit. Repeat periodically as needed to maintain control.

Continuous feed method

Initial Dose: When the system is noticeably fouled, add this product at the rate of 0.15 to 0.75 pounds per 1000 gallons (18 to 90 grams per 1000 liters) in the system to achieve 0.5-10 mg/L total available halogen as chlorine, as measured by a suitable test kit. Repeat dosage until residual is achieved.

Subsequent Dose: When microbial control is evident, add this product at the rate of 0.03 to 0.15 pounds per day per 1000 gallons (3.6 to 18 grams per day per 1000 liters) in the system to maintain 0.5-1 mg/L total available halogen as chlorine, as measured by a suitable test kit.

495

FOR SEWAGE WASTEWATER SYSTEMS

This product is intended for use in sewage wastewater systems. This product provides rapid disinfection of primary, secondary and tertiary wastewater treatment systems.

Dose Rate: Add this product at the rate of 0.03 to 0.75 pounds per 1000 gallons (3.6 to 90 grams per 1000 liters) in the system to achieve 0.2-3 mg/L total available halogen as chlorine, as measured by a suitable test kit, at the injection point in the disinfection contact chamber. Adjust the dosage to achieve disinfection and minimize the halogen concentration at the exit of the contact chamber.

FOR PULP AND PAPER MILL WATER SYSTEMS

This product is intended for use in pulp and paper mill water systems.

Initial Dose: When the system is noticeably fouled, add this product at the rate of 0.06 to 3.0 pounds per ton (0.03 to 1.5 kg. per metric ton) of dry pulp or paper produced to achieve 0.1-5 mg/L total available halogen as chlorine, as measured by a suitable test kit, in the water treated. Repeat dosage until residual is achieved.

Subsequent Dose: When microbial control is evident, add this product at the rate of 0.06 to 2.0 pounds per ton (0.03 to 1.0 kg. per metric ton) of dry pulp or paper produced to achieve 0.1-5 mg/L total available halogen as chlorine, as measured by a suitable test kit, in the water treated. Repeat periodically as needed to maintain control.

FOR ONCE-THROUGH WATER SYSTEMS

This product is intended for use in open or closed cycle, fresh or salt water, once-through cooling systems.

Initial Dose: When the system is noticeably fouled, add this product at the rate of 0.03 to 0.75 pounds per 1000 gallons (3.6 to 90 grams per 1000 liters) of water treated to achieve 0.2-10 mg/L total available halogen as chlorine, as measured by a suitable test kit, in the water treated. Repeat dosage until residual is achieved.

Subsequent Dose: When microbial control is evident, add this product at the rate of 0.03 to 0.15 pounds per 1000 gallons (3.6 to 18 grams per 1000 liters) of water treated to achieve 0.2-5 mg/L total available halogen as chlorine, as measured by a suitable test kit, in the water treated. Repeat periodically as needed to maintain control.

4

5 2 5

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE: Keep material dry and in a dry area. Store in original container where temperatures do not exceed 125°F (52 °C) for 24 hours. Keep container tightly closed.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. The preferred disposal methods are incineration or chemical treatment in accordance with Federal, State and Local regulations.

Do not put product, spilled product, or filled or partially filled containers into the trash or waste compactor. Contact with incompatible materials could cause a reaction and fire. DO NOT transport wet or damp material.

CONTAINER DISPOSAL:

BULK BIN: Return empty bulk bin for reuse. Do not vacuum, wash, or clean inside of bin.

PLASTIC BULK BAG: Completely empty bag into application equipment. Remove and triple rinse polyethylene liner. Dispose of empty bag and liner in a sanitary landfill or by incineration, or, if allowed by State and local authorities, by burning. If burned, stay out of smoke. Do not reuse bag.

FIBER DRUM: Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Remove and triple rinse polyethylene liner. Then dispose of liner in a sanitary landfill or by incineration as allowed by state and local authorities. If drum is contaminated and cannot be reused, dispose of in the same manner.

PLASTIC DRUM: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by State and local authorities, by burning. If burned, stay out of smoke.

5