

WARNING

Hazardous if swallowed, inhaled, or absorbed through skin! Do not breathe spray mist. Do not get in eyes, on skin or on clothing. In case of contact immediately remove contaminated clothing and flush skin or eyes with plenty of water; for eyes get medical attention. Wash thoroughly with soap and water after handling and before eating or smoking; wear clean synthetic rubber gloves and a mask or respirator of a type passed by the U.S. Bureau of Mines for Dieldrin protection. Do not apply or allow to drift to areas occupied by unprotected humans or beneficial animals.

This product is toxic to fish, birds, and other wildlife. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

KEEP CONTAINER CLOSED.

DO NOT LEAVE IN SUNSHINE.

WARNING — FLAMMABLE!

KEEP AWAY FROM HEAT OR OPEN FLAME. DESTROY THIS CONTAINER WHEN EMPTY.

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place away from water supplies.

NOTICE: Recommendations for the use of this product are based upon information believed to be reliable at time of printing. The use of this product being beyond the control of LOS ANGELES CHEMICAL COMPANY, no guarantee, expressed or implied is made as to the effects of such or the results to be obtained if not used in accordance with directions or established safe and sound practice. The BUYER must assume all responsibility including injury and/or damage, resulting from its misuse as such or in combination with other products.

RECEIVED
962-362



DIEL MULSION 1.5

CONTAINS 1.5 LBS. DIELDRIN PER GALLON

ACTIVE INGREDIENTS:	% BY WT.
*Dieldrin	19.5%
Petroleum Distillate	20.6%
Xylene	54.6%
INERT INGREDIENTS	5.3%
*Hexachloroepoxyoctahydro-endo, exodimethanonaphthalene	16.6%
Related Compounds	2.9%

WARNING!

KEEP OUT OF REACH OF CHILDREN

LOT No.

NET CONTENTS

GALLONS

CTTTB474

MANUFACTURED BY

LOS ANGELES CHEMICAL COMPANY

DIRECTIONS

TERMITE CONTROL: Mix 1 gallon of LACCO DIEL MULSION 1.5 with 60 gallons of water (0.3% emulsion).

(A) BUILDINGS WITH CRAWL SPACES:

- (1) Apply 2 gallons finished emulsion per 5 linear feet to critical areas only under the house, such as along the inside of foundation walls, around piers, sewer pipes, conduits, etc. Trench according to directions in (2) below.
- (2) Along the outside of foundation walls dig a narrow trench with a band no wider than six inches, and to be dug no deeper than the top of the footings. If the trench is less than 15 inches in depth to the top of the footings, apply 1 gallon per 5 linear feet. Replace the soil and apply another 1 gallon per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply 2 gallons per 5 linear feet. Replace the soil and apply another 2 gallons per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. A trench 30 inches deep is a maximum depth required alongside those foundations where the top of the footings is greater than 30 inches deep. In lieu of trenching to a 30 inch depth, make the trench 12 to 15 inches deep and rod to footing, spacing the holes about 1 foot apart.
- (3) Apply 1 gallon per 10 square feet of soil surface under attached porches, entrance platforms, utility entrances and similar situations where slab or fill is at the grade level. Where crawl spaces exist, treat as described in (1).
- (4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footing.

(B) BUILDINGS WITH CONCRETE SLAB ON THE GROUND:

- (1) Apply 1 gallon finished emulsion per 10 square feet as an overall treatment under the slab as well as under attached porches, entrance platforms, utility entrances, and similar situations where slab or fill is at grade level. If soil is treated and the concrete slab is not poured shortly thereafter on the same day, a polyethylene sheeting or other waterproof material shall be placed over the treated soil. In case of washed gravel, cinders, or similar coarse material, increase the dosage by at least one-half.
- (2) Apply 2 gallons finished emulsion per 5 linear feet to critical areas only under the slab, such as along the inside foundation walls, around

DIRECTIONS

sewer pipes, conduits, etc. Trench as in part (3) below.

- (3) Along the outside of foundation walls, dig a narrow trench with a band no wider than six inches, and no deeper than 15 inches unless the footing is much deeper in some places on account of the slope of the land, cover with a layer of soil, then treat as under (A) (2).
- (4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footings.

(C) BUILDINGS WITH BASEMENTS:

- (1) Apply 1 gallon finished emulsion per 10 square feet as on an overall treatment under the basement flooring, as well as under attached porches, entrance platforms, utility entrances, and similar situations where slab fill is at the grade level. If soil is treated and the concrete slab is not poured shortly thereafter on the same day, a polyethylene sheeting or other waterproof material shall be placed over the treated soil. In the case of washed gravel, cinders, or similar coarse material, increase the dosage by at least one-half. Where crawl spaces exist, treat as described in (2) below.
- (2) Apply 2 gallons per 5 linear feet to critical areas only under the basement floorings as well as porches and entrances having crawl spaces, such as along the inside of foundation walls, around sewer pipes, conduits, piers, etc. Trench according to directions in (3) below.
- (3) Along the outside of foundation walls, dig a narrow trench with a band no wider than six inches, such trench to be dug no deeper than the top of the footings. If the trench is less than 15 inches in depth to the top of the footings, apply 1 gallon per 5 linear feet. Replace the soil and apply another 1 gallon per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply 2 gallons per 5 linear feet. Replace the soil and apply another 2 gallons per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. A trench 30 inches deep is a maximum depth required alongside foundations where the top of the footing is greater than 30 inches deep. In lieu of trenching to a 30 inch depth, make the trench 12 to 15 inches deep and rod to footing, spacing the holes about 1 foot apart.
- (4) Treat all voids in hollow masonry units of the foundation at the rate of 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footing.