

CAUTION:

KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Keep out of reach of children and pets. Contact with skin can cause toxic symptoms. Avoid breathing of spray mists. Do not contaminate foods, dishes or cooking utensils. In case of skin contact, wash with soap and water. If swallowed, give emetic and call physician.

ENVIRONMENTAL CAUTION

This product is toxic to fish, birds and other wildlife. Keep out of any body of water. Do not apply where runoff is likely to occur. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

DILUTION CHART

For a 2% solution, dilute 5 oz. (10 tbsp.) per gallon of water.

For a 1% solution, dilute 2-1/2 oz. (5 tbsp.) per gallon of water.

Do not reuse empty container or drum. Return drum for reconditioning or destroy drum or container by crushing or perforating, and burying in safe place away from water supplies.

DIRECTIONS

TERMITE CONTROL — SOIL TREATMENT: A 1% solution is acceptable, although for longer lasting results a 2% solution is recommended. See dilution chart for mixing.

PRE-CONSTRUCTION SOIL TREATMENT: Apply 1 gallon mixed solution per 10 square feet, under slab type construction and under attached porches.

Apply 2 gallons per 5 lineal feet to critical areas such as along the inside of foundation walls, and around utility entrances and interior partition foundation walls, and around utility entrances and interior partition foundation walls.

SLAB TYPE CONSTRUCTION: Apply 2 gallons per 5 lineal feet along the outside of the foundation, which should not be dug below top of footing. If trench is more than 18" see below for dosage. Saturate backfill soil as well as trench.

CRAWL SPACE HOMES AND HOMES WITH BASEMENT: Apply 2 gallons per 5 lineal feet in a trench along the outside of foundation walls, including entrance platforms and porches, where foundation is not over 15 to 18 inches deep. If over 18 inches, but not over 30 inches, then use 4 gallons per 5 linear feet. Saturate backfill soil as well as trench.

Apply same treatment along inside foundation walls, around piers and entrances. Where crawl-space is dirt, also apply solution over the entire area using 1 gallon per 10 sq. feet.

SLAB-ON-GROUND CONSTRUCTION

(1) Apply an over-all treatment under entire surface of floor slab. Apply at the rate of 1 gallon per 10 square feet, except that if fill under slab is gravel or other coarse absorbent material, apply at the rate of 1-1/2 gallons per 10 square feet.

(2) Under slab-on-ground porch floors and entrance platforms, apply an over-all treatment at the rate of 1 gallon per 10 square feet.

(3) Along both sides of foundation wall, along interior foundation walls, and around plumbing dig a narrow trench to a depth of 1 foot, but not below the top of the footing. Apply at the rate of 2 gallons per 5 linear feet of trench. The chemical should be mixed with the soil as it is being replaced in the trench.

(4) Treat all voids in hollow masonry units of foundation at the rate of at least 1 gallon per 5 linear feet of wall. Apply the emulsion so as to reach the footing.

ACCEPTED

NOV 24 1976

Under the Federal Insecticide, Fungicide, and Rodenticide Act, or amended, for the pesticide registered under 748-55 EPA Reg. No.

SUP

TERMIC

CONTAINS 4 LBS.

FOR THE CON

ACTIVE INGREDIENTS

Technica Chlordane* _____
Petroleum distillate _____

INERT INGREDIENTS _____

*Equivalent to 27.6% Octachlor and related compounds.

CAUTION: KEEP FOR ADDITION

SUPERIOR CHEM
3942 FRANKFORD AVENUE

Apply same treatment along inside foundation walls, around piers and entrances. Where crawl-space is dirt, also apply solution over the entire area using 1 gallon per 10 sq. feet.

SLAB-ON-GROUND CONSTRUCTION

(1) Apply an over-all treatment under entire surface of floor slab. Apply at the rate of 1 gallon per 10 square feet, except that if fill under slab is gravel or other coarse absorbent material, apply at the rate of 1-1/2 gallons per 10 square feet.

(2) Under slab-on-ground porch floors and entrance platforms, apply an over-all treatment at the rate of 1 gallon per 10 square feet.

(3) Along both sides of foundation wall, along interior foundation walls, and around plumbing dig a narrow trench to a depth of 1 foot, but not below the top of the footing. Apply at the rate of 2 gallons per 5 linear feet of trench. The chemical should be mixed with the soil as it is being replaced in the trench.

(4) Treat all voids in hollow masonry units of foundation at the rate of at least 1 gallon per 5 linear feet of wall. Apply the emulsion so as to reach the footing.

ACCEPTED

NOV 24 1975

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under FIF-S-55 EPA Reg. No. 998-58



Est. No. 998-P-1
EPA Reg. No. 998-58

SUPERIOR

TERMICIDE # 460

CONTAINS 4 LBS. CHLORDANE PER GALLON

FOR THE CONTROL OF TERMITES

ACTIVE INGREDIENTS

Technica Chlordane* _____ 45.3%
Petroleum distillate _____ 49.7%

INERT INGREDIENTS _____ 5.0%

*Equivalent to 27.6% Octachloro -4,7- methano tetrahydroindane and related compounds.

NET CONTENTS 1 GALLON

CAUTION: KEEP OUT OF REACH OF CHILDREN!
FOR ADDITIONAL CAUTIONS SEE LEFT PANEL

SUPERIOR CHEMICAL PRODUCTS INC.

3942 FRANKFORD AVENUE

PHILADELPHIA, PA. 19124

BUILDING WITH CRAWL SPACES

(1) Dig a narrow trench to the top of the footing along the **inside** of foundation walls, around piers, sewer pipes and conduits. Apply 2 gallons of emulsion per 5 linear foot of trench. The chemical should be mixed with the soil as it is being replaced in the trench.

(2) Dig a narrow trench to the top of the footing along the **outside** of the foundation wall. Apply 2 gallons of emulsion per 5 linear feet of trench per each foot of depth. A trench 3 feet deep would require 6 gallons per 5 linear feet. The chemical should be mixed with the soil as it is being replaced in the trench.

(3) Under attached porches, entrance platforms, utility entrances, and similar situations where slab or fill is at the same grade level apply 1 gallon per 10 square feet of soil surface.

(4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. Apply the emulsion so as to reach the footing.

BUILDINGS WITH BASEMENTS

(1) Apply an over-all treatment under the basement floorings, as well as under attached porches, entrance platforms, utility entrances, and similar situations where slab fill is at the grade level. Apply at the rate of 1 gallon per 10 square feet, except that if fill under slab is of washed gravel, cinders, or similar coarse

material, in half. When described in

(2) Dig a narrow trench to the top of the footing along the **inside** of foundation walls, around piers, sewer pipes and conduits. Apply 2 gallons of emulsion per 5 linear feet of trench. The chemical should be mixed with the soil as it is being replaced in the trench.

(3) Along both sides of foundation wall, along interior foundation walls, and around plumbing dig a narrow trench to a depth of 1 foot, but not below the top of the footing. Apply at the rate of 2 gallons per 5 linear feet of trench. The chemical should be mixed with the soil as it is being replaced in the trench.

(4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. Apply the emulsion so as to reach the footing.

(4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. Apply the emulsion so as to reach the footing.

ACCEPTED

GV 24 1975

Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
classified under FIFRA-SS
E. No.



Est. No. 998-P-1
EPA Reg. No. 998-58

SUPERIOR

TERMICIDE #460

CONTAINS 4 LBS. CHLORDANE PER GALLON

FOR THE CONTROL OF TERMITES

ACTIVE INGREDIENTS

Technica Chlordane*	_____	45.3%
Petroleum distillate	_____	49.7%

INERT INGREDIENTS _____ 5.0%

*Equivalent to 27.6% Octachloro -4,7- methano tetrahydroindane and related compounds.

NET CONTENTS 1 GALLON

CAUTION: KEEP OUT OF REACH OF CHILDREN!
FOR ADDITIONAL CAUTIONS SEE LEFT PANEL

SUPERIOR CHEMICAL PRODUCTS INC.

3942 FRANKFORD AVENUE

PHILADELPHIA, PA. 19124

BUILDING WITH CRAWL SPACES

(1) Dig a narrow trench to the top of the footing along the **inside** of foundation walls, around piers, sewer pipes and conduits. Apply 2 gallons of emulsion per 5 linear foot of trench. The chemical should be mixed with the soil as it is being replaced in the trench.

(2) Dig a narrow trench to the top of the footing along the **outside** of the foundation wall. Apply 2 gallons of emulsion per 5 linear feet of trench per each foot of depth. A trench 3 feet deep would require 6 gallons per 5 linear feet. The chemical should be mixed with the soil as it is being replaced in the trench.

(3) Under attached porches, entrance platforms, utility entrances, and similar situations where slab or fill is at the same grade level apply 1 gallon per 10 square feet of soil surface.

(4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. Apply the emulsion so as to reach the footing.

BUILDINGS WITH BASEMENTS

(1) Apply an over-all treatment under the basement floorings, as well as under attached porches, entrance platforms, utility entrances, and similar situations where slab fill is at the grade level. Apply at the rate of 1 gallon per 10 square feet, except that if fill under slab is of washed gravel, cinders, or similar coarse

material, increase the dosage by at least one-half. Where crawl spaces exist, treat as described in part (2) below.

(2) Dig a narrow trench to the top of the footing along the **inside** of foundation walls, around piers, sewer pipes and conduits. Apply 2 gallons of emulsion per 5 linear feet of trench. The chemical should be mixed with the soil as it is being replaced in the trench.

(3) Along the outside of foundation walls, dig a narrow trench, such trench to be dug no deeper than the top of the footings. If the trench is less than 15 inches in depth to the top of the footings, apply **1 gallon per 5 linear feet**. Replace the soil and apply another **1 gallon per 5 linear feet** to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply **2 gallons per 5 linear feet**. Replace the soil and apply another **2 gallons per 5 linear feet** to the back fill. Cover the back fill with a thin layer of soil. A trench 30 inches deep is a maximum depth required alongside foundations where the top of the footings is greater than 30 inches deep. In lieu of trenching to a 30" depth, make the trench 12" to 15" deep and rod to footing, spacing the holes about 1 foot apart.

(4) Treat all voids in hollow masonry units of the foundation at the rate of **1 gallon per 5 linear feet** of wall. Apply the emulsion so as to reach the footing.