

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460

OFFICE OF PREVENTION, PESTICIDES AND TOXIC SUBSTANCES

MAR 9 2009

Mr. Michael Kellogg, Agent, Pyxis Regulatory Consulting, Inc. For Douglas Products and Packaging Company 4110 13th. St. NW Gig Harbor, WA 98332

SUBJECT:

Application for Pesticide Notification (PRN 98-10)

Request Alternate Brand Name "Vaporooter Tri-Pak"

EPA Reg. No. 1015-72

Application Dated February 12, 2009

Dear Mr. Kellogg:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 dated 02/12/09 for the above product. The Registration Division (RD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action(s) requested fall within the scope of PRN 98-10. The label submitted with the application has been stamped "Notification" and will be placed in our records.

If you have any questions, please call me directly at 703-305-6249 or Owen F. Beeder of my staff at 703-308-8899.

Sincerely,

Linda Arrington

Notifications & Minor Formulations Team Leader Registration Division (7505P)

Office of Pesticide Programs

2/2

Please read instruction	18 ON I	everse before comple	ting form.			Form Apr	pevore	I. OMB No	. 2070-008	O. Approval expires 2-28-9
		(Jnited States					Regist	ration	OPP Identifier Number
SEPA		Environmenta	l Protection	on Age	ncy			Amen		
			ington, DC 20	_	•		1	Other		
			Application	n for l	Pesticid	e - Seci	tion			
1. Company/Broduce A	b		Application	,,, ,,,,	7			<u> </u>	2.0-	
1. Company/Product N 1015-72	umbei				J. Tom	roduct Man okins	ager		3. Fr	oposed Classification
					·	JKIIIS				None ✓ Restricted
4. Company/Product (I Douglas Products and		ging Company / ROO-	PRU Super Tri	Pak	PM#	2	25			
5. Name and Address					e Evas					FIEDA Cassian 2(a)(2)
Douglas Products an			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		(h)(i) m	uiteu nev v product i	is sim	in accord	MOTIFIE	FIFRA Section 3(c)(3)
c/o Pyxis Regulatory					to:	, p. 0000.			Alas	MON
4110 136th St. NW Gig Harbor, WA 9833	32				EPA R	eg. No		···	MAR 09	2000
Check	if this	is a new address			Produc	t Name				2003
				Soc	tion - II					
				Sec	11011 - 11					
Amendment - E	xplain	below.				Final printed			nse to	
Resubmission in	n resp	onse to Agency letter	dated			Agency lett "Me Too" A				
	·	.					•			
Notification - Ex	kplain 	below.				Other - Exp	lain be	Blow.	· · · · · · · · · · · · · · · · · · ·	
Explanation: Use ac	ddition	al page(s) if necessar	ry. (For sectio	n I and Se	ction II.)					
Notification of an alterna	ate bra	nd name per PR Notic	e 98-10. The a	Iternate br	and name i	s "Vaporoote	er Tri-F	Pak". This	notification is	consistent with the
										ential statement of formula of and that if this notification is
not consistent with the t										
penalties under sections	s 12 ar	nd 14 of FIFRA.								
	-			Sect	ion - III			···········		
1. Material This Produc	ct Will	Be Packaged In:						···	· · · · · · · · · · · · · · · · · · ·	
Child-Resistant Packag	ing	Unit Packaging		Water	Soluble Pa	ckaging		2. Type	of Container	
Yes		Yes			Yes				Metal	
√ No		√ No		1	No			_	/ Plastic Glass	
		If "Yes"	No. per	If "Yes		No. per		1 }	Paper	
* Certification mu be submitted	st	Unit Packaging wgt.		Packag		container	7		Other (S	Specify)
		<u> </u>	ļ			L		<u> </u>		
3. Location of Net Con	tents !	nformation	4. Size(s) Re				5. Lo	cation of L	abel Directio	ons
✓ Label	c	ontainer	2	x2.5 gal /	2x10 oz.			On Labe	ling accompanyi	ng product
6. Manner in Which La	bel is .	Affixed to Product	Lithog	raph glued		Other	'			
			Paper Stenc							
				Sect	ion - IV	<u></u>				
1. Contact Point (Con	plete	items directly below I	for identification	n of indivi	idual to be	contacted,	if nec	essary, to	process this	application.)
Name				Title					Telephon	e No. (Include Area Code)
Michael Kellogg Age		Agent	gent (253		(253) 8	53-7369				
			Certifica	tion						6. Date Application
		nents i have made on	this form and	all attach						Recoived
i acknowledge the both under applic		/ knowlinglly false or aw.	misleading sta	tement m	ay be puni	shable by fi	ne or i	imprisonm	entor E	်(Stamped)
2. Signature //	7	11	 1	3. Title						ن در ر ز
- /) ,	Al Jas							(ر	
Thursd	L	ULLEYY		Agent					• (((, , ,
4. Typed Name				5. Date					ددد, ر	
Michael Kellogg			-	. / .	100					(((,
			1	-011	つれくりつ					· · ·

Phone: 253-853-7369 Fax: 253-853-5516 www.PyxisRC.com

February 12, 2009

COURIER DELIVERY

Jim Tompkins (PM 25)
Document Processing Desk (NOTIF)
Office of Pesticide Programs (7504P)
U.S. Environmental Protection Agency
Room S-4900, One Potomac Yard
2777 S. Crystal Drive
Arlington, VA 22202

RE: Douglas Products and Packaging Company – ROO-PRU Super Tri Pak (EPA Reg. No. 1015-72) Notification of an Alternate Brand Name per PRN 98-10

Dear Mr. Tompkins,

On behalf of Douglas Products and Packaging Company, please find the enclosed notification of an alternate brand name per PRN 98-10 for ROO-PRU Super Tri Pak. The alternate brand name is "Vaporooter Tri-Pak".

In support of this notification submission, we submit the following documents:

- 1. Completed Application for Registration (EPA Form 8570-1)
- 2. One (1) copy of the Vaporooter Tri-Pak labeling with changes tracked
- 3. One (1) copy of the Vaporooter Tri-Pak labeling with changes incorporated

Please feel free to contact me by phone (253) 853-7369 or by email at Mike@PyxisRC.com if you have any questions or need any additional information.

Sincerely.

Michael Kellogg

Enclosures

cc: Wes Long; Douglas Products and Packaging Company

RESTRICTED USE PESTICIDE

Due to Acute Toxicity

For retail sale to and use only by Certified Applicators or persons under their direct supervision and only for those uses covered by the Certified Applicator's certification.

ROO-PRU® SUPERVAPOROOTER TRI-PAK

Only for use in a combination of metam-sodium, dichlobenil, and foaming agent as directed.

This product contains:

MAR 0 9 2009

1. ROO-PRUVAPOROOTER MS-32.7S

ACTIVE INGREDIENT:	% By Weight
Metam-sodium (sodium methyldithiocarbamate)	32.7%
OTHER INGREDIENTS:	
TOTAL:	100.0%

Contains 3.18 lbs. active ingredient per gallon.

2. ROO-PRUVAPOROOTER DCB-85W

ACTIVE INGREDIENT:	% By Weight
Dichlobenil (2,6-dichlorobenzonitrile)	85.0%
OTHER INGREDIENTS:	<u>15.0%</u>
TOTAL:	100.0%

3. ROO-PRUVAPOROOTER WFA (Wetting-Foaming Agent)

DANGER - PELIGRO

Si usted no entiende la etiqueta, busque a alguien para que se la explique a usted en detalle. (If you do not understand the label, find someone to explain it to you in detail.)

STATEMENT OF PRACTICAL TREATMENT

FIRST AID:

Immediately start the procedures given below and contact a Poison Control Center, a physician, or the nearest hospital. Report the type and extent of exposure, describe the victim's symptoms, and follow the advice

aiven.

IF ON SKIN:

Immediately flush skin with large amounts of running water for at least 15

minutes while removing contaminated clothing and shoes. Get medical

attention immediately.

IF IN EYES:

Immediately flush eyes with large amounts of running water for at least 15 minutes. Hold eyelids apart to ensure rinsing of the entire surface of the

eye and lids with water. Get medical attention immediately:

IF INHALED:

Remove victim to fresh air. If not breathing, clear the victim's airway and

start mouth-to-mouth artificial respiration. If breathing is difficult, give oxygen preferably with a physician's advice. Get medical attention

immediately.

IF SWALLOWED:

Immediately give several glasses of water but do not induce vomiting. If vomiting does occur, give fluids again. Have a physician determine if condition of patient will permit induction of vomiting or evacuation of stomach. Do not give anything by mouth to an unconscious or convulsing person.

EPA Reg. No. 1015-72

EPA Est. No.

Manufactured for:

Douglas Products and Packaging Company 1550 East Old 210 Highway Liberty, MO 64068

Net Contents:

1. Metam-Sodium: ROO-PRUVAPOROOTER MS-32.7S 5 (2x2 ½) gal.

2. Dichlobenil:

ROO-PRUVAPOROOTER DCB-85W 20 (2x10) oz.

3. Wetting-Foaming Agent: ROO-PRUVAPOROOTER WFA 2 (2x1) pt.

5 CMG* Total

*Chemical mix gallon


Left Panel – Outer Box Label

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS DANGER

CORROSIVE: CAUSES SKIN DAMAGE. MAY BE FATAL IF ABSORBED THROUGH THE SKIN. Do not get on skin or clothing. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Harmful if swallowed. Harmful if inhaled. Irritating to eyes, nose, and throat. Avoid breathing vapor or spray mist. Irritating to eyes. Do not get in eyes.

PROTECTIVE CLOTHING AND EQUIPMENT REQUIREMENTS

- 1. The following protective clothing and equipment are required to be used by persons actually engaged in carrying out any operations that are likely to involve direct contact with metamsodium including mixing, loading, equipment calibrations or adjustments, cleaning and repair of application equipment, entering into treated areas, sampling, clean up of spills, rinsate disposal, or any other activities likely to result in direct contact with the product. This protective equipment must also be used for any operations that are carried out within six feet of unshielded, pressurized hoses containing metam-sodium solutions.
 - Splash resistant eye protection
 - Body covering including shirt and long pants or long-sleeved clothing. When a closed system is not used, mixers and loader must also wear a chemical-resistant apron or cloth coveralls.
 - Chemical-resistant boots and gauntlet-type gloves.
- 2. The following protective equipment must be worn at all times by persons operating or monitoring application equipment.
 - Chemical-resistant footwear
 - Body covering including shirt and long pants or long-sleeved clothing
- 3. The following protective clothing and equipment must be immediately available at all times for use by persons operating or monitoring application equipment.
 - A proper fit tested NIOSH- or MSHA- approved half face respirator with organic vapor cartridge(s) plus splash resistant eye protection or NIOSH- or MSHA- approved full face respirator with organic vapor cartridge(s). This equipment must be worn in case of emergencies or leaks when the pungent, rotten egg, or sulfur-like odor of metam-sodium is detected.
 - Chemical-resistant gauntlet-type gloves. These must be worn when a person is engaged in carrying out any operation that is likely to involve direct contact with the product, including the operations listed in paragraph No. 1 above.



Left Panel - Outer Box Label (cont.)

USE PRECAUTIONS

Consideration must be given to all sewer service lines and building elevations and basements for the possibility of foam coming up out of drains. Consideration must be given to distance between houses and sewers to be treated, depth of sewers compared to drains in buildings, line obstructions, broken and empty traps and drains with no traps that would allow foam to easily emerge. Building drains may be plugged to protect against backup and flooding. Follow the directions for measurement and use carefully to avoid using excess foam that may be forced up lateral lines to building drains. Lateral lines may be treated, but do not force excessive foam into service lines which may cause it to be forced up lateral lines into building drains. Building occupants should exit structures if the pungent, rotten egg or sulfur-like odor of metam-sodium is detected. Open windows and ventilate with fans. Flush drains with ample water if the odor comes from them. Use a squeegee, dust pan or wet vacuum and garbage bags for spills or backups and dispose of foam and liquid in an open drain or manhole. After removal of foam and liquid, wash area of spill or backup with water and detergent and flush down drain. If rugs or cloth are contacted, take outside and dry before laundering separately.



Right Panel – Outer Box Label

ENVIRONMENTAL HAZARDS

Keep out of lakes, ponds or streams. Toxic to fish and aquatic life. Do not apply directly to water, to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment washwaters. Equipment washwaters and wastes resulting from the use of this product may be disposed of on site according to label directions for use or at an approved waste disposal facility. Do not use in potable water systems. Do not use in storm, field or other drains unless effluent is treated in a sanitary sewer system. Keep off lawns and plants as they may be severely injured. Foam should be shoveled off planted areas immediately rather than washing off with water.

In case of chemical emergencies involving a spill, leaks, fire, exposure, or accident, contact CHEMTREC 1-800-424-9300.

USE PRECAUTIONS: High concentrations of these chemical in wastewater may adversely affect the biological sewage breakdown process in wastewater treatment plants. Large scale applications to sewage collection systems in proximity to a treatment plant should be divided into smaller sectional treatments done at one or two day intervals to minimize effects on the sewage treatment process. Inform appropriate wastewater treatment plant officials prior to use so they may check for any unusual rotten egg or sulfur-like odor of metam-sodium above that of sewage and monitor the performance of filter beds or digesters. If the odor is detected at the sewage treatment plant or the biological breakdown process is adversely affected, root control applications should cease until normal conditions are established. Subsequent treatments should be reduced in size or volume and spread over greater time intervals.

PHYSICAL OR CHEMICAL HAZARDS

Do not use or store near heat or open flames.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Refer to the protective clothing and equipment information under PRECAUTIONARY STATEMENTS and use all required protective clothing and equipment. The metam-sodium and dichlobenil may be used only in combination and with a foaming agent to control roots in sewer systems according to the directions for use. They may be used only where wastewater treated for root control will be processed through a wastewater treatment facility.

Refer to booklet label on inner package of metam-sodium for detailed directions for use.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Refer to booklet label on inner package of metam-sodium for detailed directions for use.

PESTICIDE STORAGE: Do not store near food or feed, seeds, bulbs, tubers, nursery stock or other vegetation matter. Do not store near pet or livestock quarters. Store in a well ventilated area. Keep containers tightly closed when not in use. Do not store below 0°F. The liquid components of this TRI-PAK become cloudy or crystallize at lower temperatures. Warm or store at higher temperatures and mix to dissolve crystals and assure uniformity before use.

PESTICIDE DISPSOAL: Pesticide wastes are toxic. Improper disposal of ဆင်နေ့ pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of according to label instructions, contact your State Pesticide or Environmental ઉարդայ Agency or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL:

ROO-PRUVAPOROOTER MS-32.7S container: Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.


ROO-PRUVAPOROOTER DCB-85W container: Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

Outer Box: Dispose of empty box in a sanitary landfill or by incineration or, if allowed by state and local law, by burning. If burned, stay out of smoke.

LIMITATION OF LIABILITY...READ CAREFULLY

See enclosed booklet.

ROO-PRU is a registered trademark of Douglas Products and Packaging Company.



Inner Metam-Sodium Booklet Label

RESTRICTED USE PESTICIDE

Due to Acute Toxicity

For retail sale to and use only by Certified Applicators or persons under their direct supervision and only for those uses covered by the Certified Applicator's certification.

ROO-PRU® VAPOROOTER

MS-32.7S

A Nonsystemic Fumigant Solution for pruning roots in wastewater collecting sytems

Only for use as a combination of metam-sodium, dichlobenil and foaming agent as directed.

ACTIVE INGREDIENT:	% By Weight
Metam-sodium (sodium methyldithiocarbamate)	32.7%
OTHER INGREDIENTS:	<u>67.3%</u>
TOTAL:	100.0%

Contains 3.18 lbs. active ingredient per gallon.

DANGER - PELIGRO

Si usted no entiende la etiqueta, busque a alguien para que se la explique a usted en detalle. (If you do not understand the label, find someone to explain it to you in detail.)

STATEMENT OF PRACTICAL TREATMENT

FIRST AID:

Immediately start the procedures given below and contact a Poison Control Center, a physician, or the nearest hospital. Report the type and extent of exposure, describe the victim's symptoms, and follow the advice given.

IF ON SKIN:

Immediately flush skin with large amounts of running water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately.

IF IN EYES:

Immediately flush eyes with large amounts of running water for at least 15 minutes. Hold eyelids apart to ensure rinsing of the entire surface of the eye and lids with water. Get medical attention immediately.

IF INHALED:

Remove victim to fresh air. If not breathing, clear the victim's airway and start mouth-to-mouth artificial respiration. If breathing is difficult, give oxygen, preferably with a physician's advice. Get medical attention immediately.

IF SWALLOWED:

Immediately give several glasses of water but do not induce vomiting. If vomiting does occur, give fluids again. Have a physician determine if condition of patient will permit induction of vomiting or evacuation of stomach. Do not give anything by mouth to an unconscious or

convulsing person.

FOR ADDITIONAL PRECAUTIONARY STATEMENTS: See Inside Booklet In case of significant spills call CHEMTREC 1-800-424-9300

EPA Reg. No. 1015-72

EPA Est. No.

Manufactured for:

Douglas Products and Packaging Company 1550 East Old 210 Highway Liberty, MO 64068

Net Contents: 2.5 Gallons

PRECAUTIONARY STATEMENTS HAZARDS TO HUMAN AND DOMESTIC ANIMALS DANGER

CORROSIVE: CAUSES SKIN DAMAGE. MAY BE FATAL IF ABSORBED THROUGH THE SKIN. Do not get on skin or clothing. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Harmful if swallowed. Harmful if inhaled. Irritating to eyes, nose, and throat. Avoid breathing vapor or spray mist. Irritating to eyes. Do not get in eyes.

PROTECTIVE CLOTHING AND EQUIPMENT REQUIREMENTS

- 1. The following protective clothing and equipment are required to be used by persons actually engaged in carrying out any operations that are likely to involve direct contact with metam-sodium including mixing, loading, equipment calibrations or adjustments, cleaning and repair of application equipment, entering into treated areas, sampling, clean up of spills, rinsate disposal, or any other activities likely to result in direct contact with the product. This protective equipment must also be used for any operations that are carried out within six feet of unshielded, pressurized hoses containing metam-sodium solutions.
 - Splash resistant eye protection
 - Body covering including shirt and long pants or long-sleeved clothing. When a closed system is not used, mixers and loader must also wear a chemical-resistant apron or cloth coveralls.
 - Chemical-resistant boots and gauntlet-type gloves.
- 2. The following protective equipment must be worn at all times by persons operating or monitoring application equipment.
 - Chemical-resistant footwear
 - Body covering including shirt and long pants or long-sleeved clothing
- 3. The following protective clothing and equipment must be immediately available at all times for use by persons operating or monitoring application equipment.
 - A properly fit tested NIOSH- or MSHA- approved half face respirator with organic vapor cartridge(s) plus splash resistant eye protection or NIOSH- or MSHA- approved full face respirator with organic vapor cartridge(s). This equipment must be worn in case of emergencies or leaks when the pungent, rotten egg, or sulfur-like odor of metam-sodium is detected.
 - Chemical-resistant gauntlet-type gloves. These must be worn when a person is engaged in carrying out any operation that is likely to involve direct contact with the product, including the operations listed in paragraph No. 1 above.

USE PRECAUTIONS: Consideration must be given to all sewer service lines and building elevations and basements for the possibility of foam coming up out of drains. Consideration must be given to distance between houses and sewers to be treated, depth of sewers compared to drains in buildings, line obstructions, broken and empty traps and drains with no traps that would allow foam to easily emerge. Building drains may be plugged to protect against backup and flooding. Follow the directions for measurement and use carefully to avoid using excess foam that may be forced up lateral lines to building drains. Lateral lines may be treated, but do not force excessive foam into service lines which may cause it to be forced up lateral lines into building drains. Building occupants should exit structures if the pungent, rotten egg or sulfur-like odor of metam-sodium is detected. Open windows and ventilate with fans. Flush drains with

ample water if the odor comes from them. Use a squeegee, dust pan or wet vacuum and garbage bags for spills or backups and dispose of foam and liquid in an open drain or manhole. After removal of foam and liquid, wash area of spill or backup with water and detergent and flush down drain. If rugs or cloth are contacted, take outside and dry before laundering separately.

ENVIRONMENTAL HAZARDS

Keep out of lakes, ponds or streams. Toxic to fish and aquatic life. Do not apply directly to water, to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment washwaters. Equipment washwaters and wastes resulting from the use of this product may be disposed of on site according to label directions for use or at an approved waste disposal facility. Do not use in potable water systems. Do not use in storm, field or other drains unless effluent is treated in a sanitary sewer system. Keep off lawns and plants as they may be severely injured. Foam should be shoveled off planted areas immediately rather than washing off with water.

In case of chemical emergencies involving a spill, leaks, fire, exposure, or accident, contact CHEMTREC 1-800-424-9300.

USE PRECAUTIONS: High concentrations of these chemical in wastewater may adversely affect the biological sewage breakdown process in wastewater treatment plants. Large scale applications to sewage collection systems in proximity to a treatment plant should be divided into smaller sectional treatments done at one or two day intervals to minimize effects on the sewage treatment process. Inform appropriate wastewater treatment plant officials prior to use so they may check for any unusual rotten egg or sulfur-like odor of metam-sodium above that of sewage and monitor the performance of filter beds or digesters. If the odor is detected at the sewage treatment plant or the biological breakdown process is adversely affected, root control applications should cease until normal conditions are established. Subsequent treatments should be reduced in size or volume and spread over greater time intervals.

PHYSICAL OR CHEMICAL HAZARDS

Do not use or store near heat or open flames.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Refer to the protective clothing and equipment information under PRECAUTIONARY STATEMENTS and use all required protective clothing and equipment. The metam-sodium may be used only in combination ROO-PRUVAPOROOTER DCB 85W and ROO-PRUVAPOROOTER WFA wetting/foaming agent to control roots in sewer systems according to the directions for use. They may be used only where wastewater treated for root control will be processed through a wastewater treatment facility.

GENERAL

- 1. Determine which collection system lines have known root problems and require treatment with root control chemicals.
- 2. Best results are obtained if the pipe to be treated is cleaned with a high pressure jet cleaner prior to the chemical treatment. When roots are mechanically cut or severely damaged by the cleaning process allow 60 to 90 days for root regrowth to start prior to chemical treatment.
- 3. Following treatment allow 60 to 90 days for the roots to die and decompose prior to assessing the effectiveness of the treatment.

- 4. Establish your treatment sequence. In order not to affect previously treated sections, start with the uppermost manhole section of the line to be treated.
- 5. Check all safety equipment for serviceability. USE THE EQUIPMENT and follow the procedures as described under the, "Protective Clothing and Equipment Requirements" on this label and as prescribed by OSHA for confined space entry.
- 6. Equipment Calibration: It is recommended that equipment calibration be checked daily or any time conditions of operation change. Due to variation in equipment and conditions, consult and follow the equipment manufacturer's recommendations on calibration procedures. Contact your chemical supplier for the nonpesticidal formulation to use for calibration purposes.
- 7. Calculate quantity of ROO-PRUVAPOROOTER/water mix to prepare.

NOTE: FUTURE REFERNCE IN THIS BOOKLET WILL BE MADE TO CHEMICAL MIX (mixture of the three components of the Tri Pak and water) AND CHEMICAL MIX GALLON [CMG] – (mixture of the three chemical components, i.e., 1 gallon MS 32.7S + 4 ounces DCB-85W + 0.4 pints WFA = slightly more than 1 gallon).

The following table provides the recipe for the ROO-PRUVAPOROOTER chemical mix for Foam Fill application:

1 gallon MS 32.7S + 4 oz. DCB-85W + 0.4 pt. WFA = 1 CMG 2 gallon MS 32.7S + 8 oz. DCB-85W + 0.8 pt. WFA = 2 CMG 2 ½ gallon MS 32.7S + 10 oz. DCB-85W = 1.0 pt. WFA = 2.5 CMG

1 Tri-Pak = 2.5 CMG 1 Super Tri-Pak = 5 CMG

Tests show that the chemical mix is stable for at least 7 days prior to use.

Chemical Preparation: Prior to diluting chemical with water, mix the three ingredients together by adding the contents of one (1) 10 oz. bottle of ROO-PRUVAPOROOTER DCB-85W and one (1) pint bottle of ROO-PRUVAPOROOTER WFA to one (1) 2 ½ gallon container of ROO-PRUVAPOROOTER MS 32.7S.

Replace 2 ½ gallon cap and invert repeatedly until thoroughly mixed then pour contents into chemical/water mix tank or blend chemical mix and water just prior to the foam equipment. DO NOT store the mixed chemical for more than 7 days. Remix chemical prior to use. DO NOT prepare more chemical/water mix than can be used in one day.

- A. Determine total footage of pipe by pipe diameter and method of treatment, i.e., foam fill or foam spray to be treated in a given day. Use promptly after mixing. DO NOT allow chemical/water mix to stand overnight. DO NOT allow solution to stand (mild agitation is necessary to keep the DCB-85W in suspension). Flush all equipment with water after each days use. Disassemble valves and clean thoroughly.
- B. The two methods of calculating the ROO-PRUVAPOROOTER mix ratio and amount of chemical mix/water solution to prepare are dependent on pipe diameter and method of application. Pipe diameter 10" or less require filling the entire pipe void with foam (Foam Fill). Pipe diameters of 12" or larger are more economically treated by using a nozzle designed to place foam directly on the root masses and pipe surface (Foam Spray). In addition to pipe size, other factors may dictate the method of application, i.e., wastewater level and velocity of flow, root density, etc,

Foam Fill: Four (4) Inch (+) Pipe (entire pipe void)

Foam characteristics desired: dry, dense, and cohesiveness similar to shaving cream.

Application Procedures for Foam Fill Requirements, Mixing and Calculations Sewer Pipe Capacities are:

Diameter/Inch	Gal./Foot	Diameter/Inch	Gal./Foot
4	0.7	16	10.5
6	1.5	18	13.5
8	2.5	20	16.3
10	4.0	21	18.0
12	6.0	24	23.5

- 1. Check sewer pipe capacity table above to determine total foam required. Pipe capacity (foam/foot) x (length of section) + (10-25%) = foam volume required.
- 2. After determining foam volume in gallons required to fill the section(s) of sewer line to be treated with foam, use the following table to determine the ROO-PRUVAPOROOTER/water solution required.

Foam Produced Per Gallon of Solution:

To Water	Add ROO-	Amount of Foam Produced
	PRUVAPOROOTER	
25.0 Gal.	1.0 CMG	540 gal.
50.0 Gal.	2.0 CMG	1,080 gal.
62.5 Gal.	2.5 CMG	1,350 gal. (1 Tri-Pak)
125.0 Gal.	5.0 CMG	2,700 gal. (1 Super Tri-Pak)
200.0 Gal.	7.5 CMG	4,050 gal. (1 ½ Super Tri Pak)

- 3. Main Line: Insert chemical discharge hose through the entire section of pipe to be treated. Start foam generating equipment and withdraw discharge hose at a rate calibrated to fill the line to capacity until foam appears at input manhole. Refer to equipment manual for the specific calibrated rate of hose retraction.
- 4. Building Service Lines: USE EXTREME CAUTION. Always plug building side of cleanout to prevent backup into building. Always treat from cleanout closest to building down to sewer main. Attach the chemical discharge hose to a pneumatic type by-pass pumping plug. Insert and position the plug in the service line cleanout and inflate in the cleanout to prevent foam from overflowing and/or the plug blowing out. CAUTION: CHEMICAL OVERFLOWING OR SPILLED ON GROUND ADJACENT TO THE CLEANOUT MAY CAUSE DAMGE TO DESIRABLE PLANTS AND LANDSCAPING.

Once the plug has been securely inflated, pump foam into the line until required amount has been discharged into the service line. Refer to the equipment manual for specific calibration rate.

FOAM SPRAY: Twelve (12) Inch and Larger Pipe (directed to roots and pipe surface).

Foam characteristics desired: Wet, dense, noncohesive. Splatters when applied to manhole walls.

1. Reduce the amount of ROO-PRUVAPOROOTER WFA (wetting/foaming adjuvant) to one half (1/2) when preparing chemical mix, i.e.:

1.0 CMG	=	0.2 pt. WFA
2.0 CMG	=	0.4 pt. WFA
2.5 CMG	=	0.5 pt. WFA

The excess WFA may be kept and used as a calibration agent.

2. See the table below to determine the reference quantity of foam spray needed per foot of pipe, then multiply by the length of pipe to be treated to determine the total amount of finished foam needed.

Pipe Diameter	Foam Gal./Ft.	Pipe Diameter	Foam Gal./Ft.
12"	4	32-36"	12
14"	8	40-42"	14
16"	10	44-48"	16

These reference quantities of foam may be adjusted to account for varying root and flow conditions within the pipe. Foam Gal./Foot x Total = Finished Foam Needed

3. In order to determine the amount of chemical mix solution to prepare from the total amount of foam spray required, divide foam spray required by 20 (20 gallons of foam spray are produced from 1 gallon of chemical mix solution) refer to the following table for solution mixing instructions to obtain the proper chemical mix to water (volume/volume).

To Water Coat	Add ROO-	Total Solution	Foam Spray
	PRUVAPOROOTER		
14 gal.	1 CMG	15 gal.	300 gal.
28 gal.	2 CMG	30 gal.	600 gal.
35 gal.	2.5 CMG	37.5 gal.	750 gal.
70 gal.	5 CMG	75 gal.	1500 gal.

4. Foam Spray Application: Insert the chemical discharge hose through the entire section of pipe to be treated, install foam spray nozzle and position about 2 inches above the flow line of the pipe. Start foam generating equipment and withdraw the chemical hose at rate calibrated to foam spray the specified diameter. Refer to equipment manual for specific calibration rate.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

PESTICIDE STORAGE: Do not store near food or feed, seeds, bulbs, tubers, nursery stock or other vegetation matter. Do not store near pet or livestock quarters. Store in a well ventilated area. Keep containers tightly closed when not in use. Do not store below 0°F. The liquid components of this TRI-PAK become cloudy or crystallize at lower temperatures. Warm or store at higher temperatures and mix to dissolve crystals and assure uniformity before use.

PESTICIDE DISPSOAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

container Disposal: Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ½ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

LIMITATION OF LIABILITY...READ CAREFULLY

Seller disclaims all liability, tort or otherwise, and all warranties, expressed or implied, including merchantability, seller shall not be liable for any damages, whether they be direct, consequential, special or indirect, which result from the use or handling of this product. Seller's sole liability and buyer's and user's sole remedy shall be limited to the refund of the purchase price.

Center Front Panel - Inner Dichlobenil Label

ROO-PRU®VAPOROOTER DCB-85W

Only for use as a combination of metam-sodium, dichlobenil and foaming agent as directed.

ACTIVE INGREDIENT:	% By Weight
Dichlobenil (2,6-dichlorobenzonitrile)	85.0%
OTHER INGREDIENTS:	
TOTAL:	100.0%

KEEP OUT OF REACH OF CHILDREN CAUTION

	FIRST AID
If swallowed:	Call a poison control center or doctor immediately for treatment advice.
	Have person sip a glass of water if able to swallow.
	Do not induce vomiting unless told to do so by a poison control center or doctor.
	 Do not give anything by mouth to an unconscious person.
lf on skin or	Take off contaminated clothing.
clothing:	Rinse skin immediately with plenty of water for 15-20 minutes.
	Call a poison control center or doctor for treatment advice.
If in eyes:	Hold eye open and rinse slowly and gently with water for 15-20 minutes.
	• Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
	Call a poison control center or doctor for treatment advice.
If inhaled:	Move person to fresh air.
	If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible.
	Call a poison control center or doctor for further treatment advice.
	HOT LINE NUMBER
	formation in case of emergency call toll free (1-800-858-7378). Have ainer or label with you when calling a poison control center or doctor, or

See additional precautionary statements on side panels.

EPA Reg. No. 1015-72

going for treatment.

EPA Est. No.

Manufactured for:

Douglas Products and Packaging Company 1550 East Old 210 Highway Liberty, MO 64068

Net Weight: 10 oz.

Left Front Panel – Inner Dichlobenil Label

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS CAUTION

Harmful if swallowed or absorbed through skin or inhaled. Causes moderate eye irritation. Avoid contact with eyes, skin or clothing. Avoid breathing spray mist.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Mixers, loaders, applicators and all other handlers must wear:

- Long-sleeved shirt and long pants
- Socks and shoes
- Chemical-resistant gloves made of any waterproof material
- In addition to the requirements above, mixers and loaders must also wear a chemical-resistant apron

User Safety Requirements

Follow manufacturer's instructions for cleaning/maintaining PPE. If there are not such instructions for washable PPE, use detergent and hot water. Keep and wash PPE separately from other laundry.

USER SAFETY RECOMMENDATIONS

Users should:

- Wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet.
- Remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.
- Remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.

Right Front Panel - Inner Dichlobenil Label

ENVIRONMENTAL HAZARDS

Keep out of lakes, ponds or streams. Do not apply directly to water, to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment washwaters. Equipment washwaters and wastes resulting from the use of this product may be disposed of on site according to label directions for use or at an approved waste disposal facility. Do not use in potable water systems or storm, field or other drains from which untreated water is discharged.

This chemical has properties and characteristics associated with chemicals detected in ground water. The use of this chemical in areas where soils are permeable, particularly where the water table is shallow may result in ground-water contamination.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Refer to the protective clothing and equipment information under PRECAUTIONARY STATEMENTS and use all required protective clothing and equipment. The dichlobenil may be used only in combination with the metam-sodium and with a foaming agent to control roots in sewer systems according to the directions for use. They may be used only where wastewater from root control is processed through a wastewater treatment facility. Refer to specific mixing and use directions and associated calculations on the inner package labeling of the metam-sodium product. Do not use this product without these specific directions and full precautionary labeling.

When used in inhabited buildings (residences, offices, hospitals, etc.) windows must be open or an exhaust fan must be operating during the application.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

PESTICIDE STORAGE: Do not store near food or feed, seeds, bulbs, tubers, nursery stock or other vegetation matter. Keep containers tightly closed when not in use. Store in dry place.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

LIMITATION OF LIABILITY...READ CAREFULLY

Seller disclaims all liability, tort or otherwise, and all warranties, expressed or implied, including merchantability, seller shall not be liable for any damages, whether they be direct, consequential, special or indirect, which result from the use or handling of this product. Seller's

sole liability and buyer's and user's sole remedy shall be limited to the refund of the purchase price.

NOTIFICATION MAR 0 9 2009