



AMEROCIDE

LIQUID PESTICIDE CONCENTRATE FOR CONTROL OF
WOOD DESTROYING BEETLES IN LUMBER AND STORAGE PILES

Net Contents _____ gal.

FOR INDUSTRIAL USE ONLY

INGREDIENT STATEMENT

GENERAL DANGER STATEMENTS
HAZARD TO HUMANS &
DOMESTIC ANIMALS
WARNING

ENVIRONMENTAL HAZARDS

PHYSICAL & CHEMICAL HAZARDS

Keep Out Of Reach Of Children
WARNING

ACCEPTED

AUG - 5 1986

Under the FIFRA Act.
Fungicide and wood preservative.
as amended for the pesticide
registered under
EPA Reg. No. 1022-6

DIPPING LUMBER

STORAGE AND DISPOSAL

BEST AVAILABLE COPY

DIRECTIONS FOR USE

SPRAY APPLICATIONS

EPA Reg. No. 1022-6; EPA EST. No. 1022-18-1

Manufactured by
CHAPMAN CHEMICAL COMPANY
P.O. Box 9150
Memphis, TN 38107

WARRANTY STATEMENT AND DISCLAIMER

FOR INDUSTRIAL USE ONLY

INGREDIENT STATEMENT

ACTIVE INGREDIENTS:

Lindane (gamma isomer of benzene hexachloride) 11.57%
Xylene 53.53%

INERT INGREDIENTS:

2.90%

AMBROCIDE weighs approximately 7.7 pounds per gallon and contains approximately 0.57 pounds of lindane per gallon.

Keep Out of Reach of Children

WARNING

STATEMENT OF PRACTICAL TREATMENT

If swallowed, call a physician or Poison Control Center immediately. Gastric lavage is indicated, if the material was taken internally.

If inhaled, remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.


If on skin, wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse.

If in eyes, flush eyes with plenty of water. Get medical attention.

**SEE LEFT PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS**

EPA Reg. No. 1022-6, EPA Est. No. 1022-TN-1

**Manufactured by
CHAPMAN CHEMICAL COMPANY
P.O. BOX 9158
MEMPHIS, TN 38109**



ACCEPTED
AUG - 5 1986
Un...icide.
Fung... : Pesticide Act.
as amended, for the pesticide
registered under
EPA Reg. No. 1022-6

Exhibit 3:

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS & DOMESTIC ANIMALS
WARNING**

May be fatal if swallowed, inhaled, or absorbed through the skin. Do not get in eyes, on skin or on clothing. Do not breathe spray mist or vapor.

Applicators and persons handling this pesticide must wear water resistant but, lightweight protective suit or coveralls, unlined waterproof gloves (natural rubber, nitrile or polyethylene), and unlined lightweight boots. Mixers/handlers must wear goggles or a face shield, waterproof apron, and unlined lightweight gloves.

Wash thoroughly after handling and before eating, drinking, using tobacco products, and before using restrooms.

Do not allow drift to areas occupied by unprotected humans or beneficial animals. Treated sawdust and other wood wastes should not come in contact with domestic animals or be used so that they come in contact with desirable plants or food crops.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish, birds, and other wildlife. Do not apply directly to water or wetlands. Drift and runoff from treated areas may be hazardous to fish in neighboring areas. Do not contaminate water by cleaning of equipment or disposal of wastes.


PHYSICAL & CHEMICAL HAZARDS

Do not use or store near heat or open flame.

BEST AVAILABLE COPY

EXHIBIT 4:

496



DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its label.

Ambroside is intended for use on lumber and wood logs in industrial wood processing facilities. This product is a concentrate and must be diluted with oil or water prior to use. Oil dilutions are more effective and provide longer residual protection than water dilutions, oil is the recommended diluent for spraying logs.

SPRAY APPLICATIONS

Add one gallon of Ambroside to 25 gallons of kerosene, diesel fuel, No. 2 fuel oil or water, and mix thoroughly. If water is used, the emulsion should be agitated frequently when in the mixing or sprayer tank. Make sure that the mixture is free of sediment or debris, which may clog the spray nozzle. Strain the solution if necessary.

Incoming logs should be sprayed promptly. Spray thoroughly all parts of the log, wetting bark and ends. Unsprayed portions of the log are points of entry for insects. One gallon of spray per 100 square feet of log surface is usually required. For added sapstain control when spraying logs, add one gallon Penta Plus 40 to 27 gallons oil diluent and add this mixture to one gallon of Ambroside.

For added sapstain control of lumber when spraying with water dilutions, mix 1 and 1/2 gallons of PQ-57 with 27 gallons of water, and add this mixture to one gallon of Ambroside.

Ambrosia Beetle Control: Add one gallon of Ambroside to each 100 gallons of antistain solution. Ambroside may be added after the Permatox or PQ stain/mold control solutions are prepared.

Consult your Chapman representative to determine suitability for use in ultra-low volume spray equipment.

DIPPING LUMBER


Ambrosia Beetle Control: Add one gallon of Ambroside to each 100 gallons of solution in the dip tank. Ambroside may be added after the Permatox or PQ stain/mold control solutions are prepared. Add directly to the mixing tank or dip tank and agitate to form an emulsion.

Lycetus Beetle Control: Add 4 gallons of Ambroside to each 100 gallons of antistain solution as described above.

Dipping solutions containing Ambroside should be agitated after standing overnight or for several hours undisturbed.

BEST AVAILABLE COPY

Exhibit 5:



STORAGE AND DISPOSAL

PROHIBITIONS: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

STORAGE: Store in a secure, well-ventilated area protected from extreme temperatures.


PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your state Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

DISPOSAL OF DIPS: Used dip solutions must be disposed of in accordance with the Resource Conservation and Recovery Act (RCRA). If the applicator generates more than 1000 kg of used dip solution per month or more than 1000 kg used dip solution in combination with other hazardous waste, the material must be treated as a hazardous waste subject to subpart C of RCRA. Any user who wishes to treat, store or dispose of hazardous waste must obtain a permit to serve as a hazardous waste facility pursuant to RCRA.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

BEST AVAILABLE COPY

6
EXHIBIT 8:



WARRANTY STATEMENT AND DISCLAIMER

Proper application is critical to the effectiveness of the product, however, when applied and used according to this label. A brand of this product is capable of protecting lumber and stored logs from wood destroying beetles. The actual life of the treatment will be affected by the condition of the wood when treated, the species of wood, the type of exposure, and previous and subsequent treatments.

WARNING: READ THE LABEL THOROUGHLY BEFORE USE, COMPLY WITH ALL DIRECTIONS AND WARNINGS GIVEN, AND USE COMMON SENSE IN HANDLING.

CHAPMAN MAKES NO WARRANTIES, EITHER EXPRESS OR IMPLIED, OTHER THAN AS SET FORTH ON THIS LABEL, AND CHAPMAN DISCLAIMS ANY IMPLIED WARRANTY OR MERCHANTABILITY NOT SPECIFICALLY SET FORTH ON THIS LABEL. CHAPMAN SHALL NOT BE RESPONSIBLE FOR ANY PERSONAL INJURY OR PROPERTY DAMAGE OR OTHER TYPE OF LOSS RESULTING FROM FAILURE TO FOLLOW THE DIRECTIONS FOR USE, WARNINGS AND PRECAUTIONARY LANGUAGE GIVEN ON THIS LABEL. CHAPMAN SHALL NOT BE RESPONSIBLE FOR DAMAGE TO PROPERTY BEYOND THE PURCHASE PRICE OF THIS PRODUCT; HOWEVER, SOME STATES DO NOT ALLOW THE INCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THIS LIMITATION MAY NOT APPLY TO YOU.

BEST AVAILABLE COPY