



PENTA-W'R

CONCENTRATE 1 TO 5

WATER REPELLENT WOOD PRESERVATIVE

Not For Use On Broad Interior Surfaces Such As Walls Or Floors

Net Contents

Gallons

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS &

DOMESTIC ANIMALS

WARNING

May be fatal if swallowed, inhaled or absorbed through the skin.

Causes eye and skin irritation. May produce delayed chemical burn.

Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling.

PHYSICAL AND CHEMICAL HAZARDS

Do not use or store near heat or open flame.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

Keep container closed when not in use.

PROHIBITIONS: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide sprays, mixtures or rinse water that cannot be used according to label instructions must be disposed of according to applicable Federal, State or local regulations.

CONTAINER DISPOSAL: Triple rinse, preferably. Then offer for recycling or reuse, if available, or dispose of in a sanitary and fireproof container approved by State and local procedures.

GENERAL: Consult Federal, State or local health authorities for approved alternative procedures.

Recommended for use on: Posts, interior trim, sills, trim, pickets, stairs, fence rails, plates, railing strips, porches, arbors, shingles, window sashes, doors, steps, and flooring, window frames, beverage cases.

When diluted according to label instructions, Penta WR complies with Federal Specification TT W 572B.

Powder post beetles are killed by application of Penta WR. These insects will not attack wood treated with Penta WR.

WATER REPELLENT—CLEAR PAINTABLE—STOPS ROT CONTROLS WARPING—SWELLING

INGREDIENTS:

ACTIVE INGREDIENTS:	
Pentachlorophenol*	21.50%
Other Chlorinated Phenols*	2.53%
INERT INGREDIENTS	
TOTAL	100.00%

*Equivalent to 2,5-Dichloro-4-Pentachlorophenol as defined by Fed. Spec. TT W 570.

Contains Petroleum Distillates

KEEP OUT OF REACH OF CHILDREN WARNING

STATEMENT OF PRACTICAL TREATMENT

If swallowed, do not induce vomiting. CALL A PHYSICIAN.

In case of eye contact, flush eyes immediately with plenty of water and get medical attention.

In case of skin contact, wash with soap and plenty of water. Wash contaminated clothing before reuse.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

ACCEPTED

EPA Est. No. 1022 TN 1
EPA Reg. No. 1022-68

MAY 14 1982

the Federal Insecticide, Fungicide, and Rodenticide Act

In addition to preventing decay, blue stain, and insect attack on wood, Penta WR controls warping, swelling, shrinking and end checking caused by changes in moisture content of lumber and plywood products.

MIXING INSTRUCTIONS:

Dilute one volume of Penta WR Concentrate with 5 volumes of mineral spirits and agitate well for several minutes to insure uniformity. When Penta WR Concentrate is stored at near freezing temperatures, it increases in viscosity as do all liquids. This does not injure the product, but the container should be allowed to warm up before attempting to remove contents from container. Container should not be stored outdoors in winter in cold climates.

APPLICATION INSTRUCTIONS:

The best results will be obtained if wood to be treated is immersed in Penta WR for 3 minutes or longer. If dipping is not possible, 2 liberal brush or spray applications should be applied. Allow at least 1 hour between applications. Make certain all areas are fully treated to get the maximum benefits. Where wood has been soaked for 3 minutes, it should be allowed to dry for at least 24 hours before being painted or varnished. Where drying conditions are poor, in humid or damp weather or where longer soaking periods are used, drying time may have to be increased before painting.

Fence posts, poles, foundation timbers and heavy wooden members should be free of bark, dry, and well seasoned and immersed in the product for a period of 12 to 24 hours to be an effective wood preserver.

Wood should be treated before use in construction.

Be sure to keep drip vats free of water from condensation or other sources. Solutions in iron vats contaminated with water may darken in color.

Lumber wet with solution should be handled with rubber gloves. Avoid contamination of feed or foodstuff.

Do not use on wood that may come in contact with food, feed or livestock.

Do not use Penta WR or wood treated with Penta WR inside any human or animal dwelling or in any confined area where spray mist and vapors may concentrate.

Treated saw dust and other wood waste should not come in contact with plants and should be used so they come in contact with soil, not plants.

WARRANTY STATEMENT

Chapman Chemical Company, or the seller, makes no representation of warranty, expressed or implied, for the use of this material, other than indicated on the label. Neither shall be held responsible in any manner for personal injury or property damage or other losses resulting from the improper handling, application or use of this material. The buyer accepts and understands these terms.