NET CONTENTS

GALLONS

ceo!

S

-0

と

PENTA PLUS 40 WOOD PRESERVATIVE

DIRECTIONS

HAPMAN

To make a 5% ready-to-use solution, mix one part of this concentrate with ten parts by volume of a suitable petroleum solvent such as mineral spirits or kerosene.

As Penta Plus 40 is a concentrate do not use without diluting.

WOOD PRESERVATION

After diluting as indicated above the readyto-use Penta Plus 40 solution can be applied to lumber, poles, post and other wood products by a hot-cold bath process, by soaking, spraying.or brushing. The most effective treatment is obtained where deep penetration and high absorptions result. Soaking or a hotcold bath process gives better results than does spraying or brushing and should be used where possible. Fence posts should be barked and air seasoned until dry and then soaked 34 to 48 hours. The butts should be well treated. Lumber for steps. sills. etc. should be soaked for at least 12 hours. When the wood is not in ground contact, brushing or swabbing may be used. The joints should be thoroughly drenched.

INGREDIENT STATEMENT

ACTIVE INGREDIENTS:

Pentachlorophenol	35.	3%
Other chlorinated phenols	4.	1%
Petroleum solvent	59.	0%
INERT INGREDIENTS	1.	6%

*Equivalent to 41% pentachlorophenol, technical. as defined by Federal Spec. TT-W-570

WARNING

KEEP OUT OF REACH OF CHILDREN!

Harmful if swallowed or absorbed through skin! Causes skin irritation. Do not breathe vapor or spray mist. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling. Wear rubber gloves and protective clothing when handling freshly-treated lumber.

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

This product is toxic to fish and wildlife. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. DO NOT USE POUR SPILL OR STORE NEAR HEAT OR OPEN FLAME.

The solution obtained by diluting this concentrate with ten volumes of petroleum solution is a proven wood preservative and is especially recommended for the use of termite exterminators and others wishing to protect buildings from the ravages of these insects. Wood treated with ready-to-use solution is not paintable. If it is desired to paint treated wood. Penta WR should be used.


This concentrated pentachlorophenol solution complies with all requirements of Commercial Standard CS 19453, as developed by the trade under the procedure of the commodity Standards Division and issued by the U.S. Department of Commerce.

NON-WARRANTY

Neither the manufacturer nor the seller makes any representation or warranty, expressed or implied concerning this material except that it is of standard quality. Neither shall be held responsible in any manner for any personal injury, property damage or other type of loss resulting from the handling, storage or use of this material. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.

EPA Reg. No. 1022-120

MANUFACTURED BY CHAPMAN CHEMICAL COMPANY MEMPHIS, TENNESSEE



ACCEPTED MAY 0 8 1972 UNDER THE FEDERAL INSECTICIDE FUNGICIDE AND RODENTICIDE ACT FOR COMMIC POISON REGISTER-ED UNDER NOZOZOW REGISTER-TO ATTACHED COMMENTS: 10 7 *** *** 7 ***** 8 3 7 ***** A . 2 20 è ŝ ...

رلا A.

. .

. '

Ŵ