

300
17
147022
1

Chapman Chemical Company
P.O. Box 9150
Memphis, TN 38109

JUN 28 1985

Attention: David Linnavege

Gentlemen:

Subject: Amendment, Label Revision
TIMPRIS B
EPA Registration No. 1022-368
Your Application Dated February 21, 1985

The label amendment referred to above, submitted in connection with registration 1022-368 under FIFRA, is acceptable, provided that the following change is made:

- (1) Change your signal word to "DANGER." All pentachlorophenol products must bear the signal word "DANGER."

A stamped copy of the label is enclosed for your records.

Sincerely yours,

Henry H. Jacoby
Product Manager (21)
Fungicide-Herbicide Branch
Registration Division (TS-767)

Enclosure

BEST AVAILABLE COPY

RD/FHB:JOB 88651:Jacoby:RD:85/35:Kendricks&Co:898-1270:6/18/85:Del:6/28/85:ATB
REVISRD:RD/FHB:JOB 88651:Jacoby:RD:85/35:Kendricks&Co:898-1270:6/18/85:Del:6/28/85:lc

CONCURRENCES							
SYMBOL							
SURNAME							
DATE							

**POL-NU TYPE WOOD
PRESERVATIVE GREASE
GROUNDLINE TREATMENT**
CONTAINING SODIUM TETRABORATE (BOEAX)
CONTROLS DECAY AND AIDS IN THE
PROTECTION AGAINST TERMITES
EXTENDS SERVICE LIFE OF STANDING
POLES AND POSTS.

INGREDIENT STATEMENT

ACTIVE INGREDIENTS

Pentachlorophenol	8.95%*
Other chlorinated phenols	1.04%*
Sodium tetraborate, anhydrous	15.50%
Aromatic petroleum derivative solvent	67.74%

INERT INGREDIENTS	6.77%
TOTAL	100.00%

*Equivalent to 10.69% technical pentachlorophenol

**KEEP OUT OF REACH OF CHILDREN
WARNING**

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES Flush with plenty of water. Get medical attention.

IF SWALLOWED Drink promptly a large quantity of milk, egg whites, gelatin solution, or if these are not available, drink large quantities of water. Avoid alcohol. Consult physician.

IF ON SKIN Wash thoroughly with soap and water. Remove contaminated clothing and wash before reuse.

SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS

DIRECTIONS

It is a violation of Federal law to use this product in a manner inconsistent with the label.

APPLICATION

TEMPREG B can best be applied to the CHAPMAN BANDAGE coated kraft paper TEMPREG B by brush, paddle, trowel, pump. For application to timbers, fill caulking gun. Any grease equipment that grease will work with TEMPREG B.

Remove the soil away from the pole surface in areas of decay. Apply TEMPREG B to the pole surface to a depth of 1/2 inch or deeper. Remove any decay on the pole surface to a depth of 1/2 inch or deeper. Apply TEMPREG B to the pole surface to a depth of 1/2 inch or deeper. Apply TEMPREG B to the pole surface to a depth of 1/2 inch or deeper.

TEMPREG B will penetrate to leave excavated pole surface to weather to dry out.

Apply TEMPREG B in a 1/2" groundline treatment. No special conditions. CHAPMAN adjustable up to 3/8" of air prepared to cover ground 18 or 22 inches in height. Apply to cover the pole surface. Last evidence of decay on line.

More than one bandage may be used where the pole area to be treated is greater than 22 inches. Use THE CHAPMAN BANDAGE band of TEMPREG B. A term may be inserted to obtain

EP 1 1/2 IN

CHAPMAN CHEMICAL COMPANY

MEMPHIS, TENNESSEE 38109

A Kewanee Company