CHAPMAN®

SURE-MIX SYSTEM

NET CONTENTS 55 GALLONS

CHAPCO SSC CONCENTRATE

LIQUID FUNGICIDE CONCENTRATE FOR CONTROL OF SAPSTAIN AND MOLD
IN FRESH CUT LUMBER AND TIMBER DURING AIR SEASONING

6-8-1972
1022-466

INGREDIENTS

ACTIVE:	
Sodium Tetrachlorophenate	17.96
Sodium salts of other chlorinated phenols	4.86
Sodium metaborate, anhydrous	4.28
INERTS	72.90
Total	100.00

DIRECTIONS FOR USE

GENERAL: CHAPCO SSC is a [illegible] concentrated liquid pr[illegible] readily miscible with water. It may be mixed with water by [illegible] through the CHAPMAN SURE-MIX [illegible]

[illegible] CHAPCO SSC [illegible] primary [illegible] adjacent [illegible] water [illegible] CHAPCO SSC [illegible]

[illegible]

[illegible] CHAPCO SSC [illegible]

[illegible]

TREATMENT: For lumber [illegible] inches or less in thickness [illegible] solution of CHAPCO SSC with 60 gallons of water. For thicker lumber or timbers or handled lath or shook or under unusually severe or long periods or conditions favorable to sapstain and mold development, combine one gallon of CHAPCO SSC with 30 to 50 gallons of water. A dip of 15 seconds or more is sufficient.

DANGER

KEEP OUT OF THE REACH OF CHILDREN!

May be fatal if swallowed.
May produce delayed chemical burns.
Do not breathe spray mist.
[illegible]
May cause severe eye damage. Avoid contact [illegible] handling.
In case of contact wash skin with [illegible] and [illegible] flush with water for at least 15 minutes and [illegible] Carbon skin irritation.
Wash thoroughly after handling.
Wear protective [illegible]
[illegible]
Do not reuse empty drum. Return to drum reconditioner [illegible] reconditioning, washing and burning [illegible] supplies.

NOTICE

[illegible]

MANUFACTURED BY **CHAPMAN CHEMICAL COMPANY** MEMPHIS, TENNESSEE 38109