



ACCEPTED  
 JUL 7 1983  
 1022474

# NAPCLOR - G Bulk Pack

A Composition for Controlling Sapstain and Mold on S

### PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS & DOMESTIC ANIMALS

#### WARNING

May be fatal if swallowed, inhaled or absorbed through the skin.

Causes eye and skin irritation.

Do not get in eyes, on skin or on clothing. Do not breathe dust or spray mist. Wear goggles or face shield and rubber gloves when handling. Lumber wet with solution should be handled with rubber gloves. Avoid contamination of feed or feed stuff.

#### ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not apply when weather conditions favor drift from treated area.

#### DIRECTIONS FOR USE

Read and follow all directions on label. Use in accordance with Federal Law to use this product. Do not use in a manner inconsistent with its labeling.

#### STORAGE AND DISPOSAL

**PROHIBITIONS:** Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

**PESTICIDE DISPOSAL:** Pesticide, spray mixture or use water that cannot be used according to label instructions must be disposed of according to applicable Federal, State or local procedures.

**CONTAINER DISPOSAL:** Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Then dispose of liner in a sanitary landfill or by incineration if allowed by state and local authorities. If drum cannot be reused, dispose of in the same manner.

**GENERAL:** Consult Federal, State or local disposal authorities for approved alternative procedures.

### INGREDIENT STATEMENT

ACTIVE INGREDIENTS*:	90%
Sodium Pentachlorophenate	79%
Sodium Salts of other Chlorophenols	11%
INERT INGREDIENTS:	10%
	Total 100%

\*Calculated as sodium pentachlorophenate (molecular weight 288.3).

### KEEP OUT OF REACH OF CHILDREN WARNING STATEMENT OF PRACTICAL TREATMENT

**IF IN EYES:** Immediately flush with large quantity of water and get medical attention. **IF ON SKIN:** Wash with soap and plenty of water. Remove and wash contaminated clothing before reuse.

**IF SWALLOWED:** Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to unconscious persons. Get medical attention.

**NOTE TO PHYSICIAN:** This product is a non-flammable liquid. Causes irritation. Treat symptomatically.

SEE SIDE PANEL FOR ADDITIONAL  
 PRECAUTIONARY STATEMENTS

EPA Reg. No. 1022-474  
 EPA Est. No. 1022-TN-1

DECT

6/83

MANUFACTURED BY **CHAPMAN CHEMICAL COMPANY**

A KemaNobel Company

83  
Federal  
Insecticide Act,  
Fifteenth  
Amendment  
4/74

# NAPCLOR - G Bulk Pack

Net Wt. lbs.

100 2-474

## Controlling Sapstain and Mold on Softwood and Hardwood

### INGREDIENT STATEMENT

<b>ACTIVE INGREDIENTS*</b> .....	<b>90%</b>
Sodium Pentachlorophenate.....	79%
Sodium Salts of other Chlorophenols .....	11%
<b>INERT INGREDIENTS:</b> .....	<b>10%</b>
<b>Total 100%</b>	

\*Calculated as sodium pentachlorophenate (molecular weight 288.3).

To control blue stain and mold on softwoods and hardwoods, best results will be obtained if the lumber is treated with Napclor G within 24 hours of cutting; otherwise, interior stain may result. A dip of 15 seconds or more is sufficient. Spray systems may also be employed.

The treating solution should be carefully prepared in a separate mixing tank and then run into the dipping vat. After adding the dry chemical to the water, stir well for at least two minutes or until all is dissolved.

For dipping lumber 2 inches or less in thickness or for spraying Douglas fir, dissolve 6 lbs. in 80 to 100 U.S. gallons of water. For thicker lumber, or for bundled lath or shook, dissolve contents of 12 lbs. in 80 to 100 U.S. gallons of water. If pine lumber is sprayed in warm climates the higher rate should be used. During periods of slow drying, the lower gallonage of water should be used with 6 lb. or 12 lb. depending upon lumber dimension being treated.

### KEEP OUT OF REACH OF CHILDREN WARNING STATEMENT OF PRACTICAL TREATMENT

IF IN EYES, immediately flush with large quantity of water and get medical attention. IF ON SKIN, wash with soap and plenty of water. Remove and wash contaminated clothing before reuse.

IF SWALLOWED, Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. DO not induce vomiting or give anything by mouth to unconscious person. Get medical attention.

NOTE TO PHYSICIAN: This product is a metabolic stimulant. Causes hyperthermia. Treat symptomatically.

SEE SIDE PANEL FOR ADDITIONAL  
PRECAUTIONARY STATEMENTS

### NOTE

In order to insure best results, the dipping tank must be protected from rain. The treated lumber should not be allowed to remain unprotected in heavy rains, especially just after dipping. Lumber piles should be roofed, and adequate space should be left between chords and stacks. Stacks should be at least one foot above the ground and weeds and other hindrances to good air movement eliminated. Green lumber should not be used for stickers.

### WARRANTY STATEMENT

Neither Chapman Chemical Company, nor the seller makes any representation or warranty, expressed or implied, concerning this material, other than indicated on the label. Neither shall be held responsible in any manner for any personal injury, or property damage or other type of loss resulting from the improper handling, storage or use of this material. The buyer accepts and uses this material on these conditions.

EPA Reg. No. 1022-474  
EPA Est. No. 1022-TN-1

BEST DOCUMENT AVAILABLE

**CHAPMAN CHEMICAL COMPANY** MEMPHIS, TENNESSEE 38109  
A KemaNobel Company