



# RESTRICTED USE PESTICIDE

For sale to and use only by certified applicators or by persons under their supervision and only for those uses covered by the certified applicators' certification.

Batch Number \_\_\_\_\_  
Net Contents \_\_\_\_\_  
Date Packaged \_\_\_\_\_

## PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS **DANGER**

May be fatal if swallowed, inhaled or absorbed through skin. Causes skin and eye irritation. Causes delayed chemical burns. Do not get in eyes, on skin or on clothing. Do not breathe vapors, spray mist or dust. Use with adequate ventilation. Do not take internally. Wash thoroughly after skin contact, before eating, drinking, use of tobacco products, or using restrooms.

The U.S. EPA has determined that pentachlorophenol can produce defects in the offspring of laboratory animals. Exposure to pentachlorophenol during pregnancy should be avoided.

**FOR POWDER FORMULATIONS OF PENTACHLOROPHENATE:** Until August 31, 1987, a closed emptying and mixing system must be used or protective clothing including respirator, gloves, and long sleeved shirts and long pants or disposable overalls must be worn when emptying and filling powder formulations of pentachlorophenolate. After September 1, 1987, a closed system must be used when emptying and filling powder formulations of pentachlorophenolate. A closed system is defined as any containment which prevents the release of sufficient chemical into the surrounding normal environment, except the release of incidental amounts of chemical during equipment loading and periodic cleaning or maintenance operations, shall not be deemed a breach of containment.

**FOR THE SPRAY METHOD OF APPLICATION:** Spray apparatus must be operated so as to minimize overspray, and must be 1) clean and 2) be free of leaks in the system. Should there be a visible mist, spray, and vapors in the vicinity of the spray apparatus, the zone in which the mist is visible must wear a respirator and protective clothing, including overalls, jacket, gloves, boots, and head covering, impervious to the wood treatment formulation, and goggles.

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation.

Individuals who enter, clean, or repair vats, tanks or related equipment that is contaminated with the treatment solution must wear overalls, jackets, boots, head covering, impervious to the wood treatment formulation, and goggles.

Applicators must wear gloves, impervious to the wood treatment formulation in all situations where dermal contact is expected, for example, during the actual application process and when handling freshly treated wood.

Protective clothing must be changed when it shows signs of contamination. Applicators must leave protective clothing and workshoes or boots and equipment at the plant. Turn out protective clothing and workshoes or boots must be left at the treatment plant and disposed of in any general and/or in the trash or in any other manner applicable for pesticide disposal.

**RESPIRATOR:** As used on this use, the term "respirator" means properly fitting, air maintained, half mask canister or canister respirators which are NIOSH or OSHA approved for organic vapors. Examples of acceptable materials for protective clothing are: gloves, overalls, jackets, and boots, required during application and handling of pentachlorophenolate are polyvinyl acetate (PVA), polyvinyl chloride (PVC), neoprene, BR (Buna-N), and nitrile.

### ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water. Do not apply where runoff is likely to occur. Do not apply when weather conditions favor drift from areas treated. Do not contaminate water by cleaning of equipment.

### PHYSICAL AND CHEMICAL HAZARDS

Do not store near heat or open flame. Close container after each use.

## NAPCLOR-G

Bulk Pack

### A COMPOSITION FOR CONTROLLING SAPSTAIN AND MOLD ON SOFTWOOD AND HARDWOOD

### INGREDIENTS

ACTIVE INGREDIENTS	
Sorbin Pentachlorophenate .....	90.0%
INERT INGREDIENTS .....	10.0%
TOTAL .....	100.00%

Chapman Chemical Company has complied with all terms and conditions of the registration governing the composition of this product as approved by the United States Environmental Protection Agency under Section 3 of the Federal Insecticide, Fungicide and Rodenticide Act.

**Keep Out of Reach of Children**

## DANGER

### STATEMENT OF PRACTICAL TREATMENT

**IF SWALLOWED:** Call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.

**IF IN EYES:** Flush with plenty of water. Call a physician.

**IF ON SKIN:** Wash with plenty of soap and water. Get medical attention.

**IF INHALED:** Remove victim to fresh air. Get medical attention.

**NOTE TO PHYSICIAN:** This product is a metabolic stimulant. Treatment is supportive. Forced diuresis may be effective to reduce total body burden. Treat hyperthermia with physical measures. Do not administer aspirin, salicylates, or atropine since they may enhance toxicity.

**SEE SIDEPANEL FOR ADDITIONAL  
PRECAUTIONARY STATEMENTS**

DEC - 3 1987

1022-474

EPA Est No. 1022-TN-1022-474 EPA Reg No. 1022-474

MANUFACTURED BY  
**CHAPMAN CHEMICAL COMPANY**  
MEMPHIS, TENNESSEE 38109

## DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Use of this product for any purpose other than those stated on the label, including the use of this product in the manufacture and formulation of other pesticide products or in repackaging of this product, is prohibited.

To control bluestain and mold in softwoods and hardwoods best results will be obtained if the lumber is dipped within 24 hours of cutting. If lumber is not dipped within 24 hours interior stain may result. For lumber 2 inches or less in thickness or for spraying Douglas fir, dissolve 6 lbs. of NAPCLOR-G in 80 to 100 U.S. gallons of water. Warm water will hasten solution of NAPCLOR-G. For thicker lumber or bundled lath or shook, dissolve 12 lbs. of NAPCLOR-G in 100 U.S. gallons of water. If pine lumber is sprayed in warm climates, the high rate should be used. During periods of slow drying, the lower gallonage of water should be used with 6 or 12 lbs. of NAPCLOR-G depending on the lumber dimensions being treated. The treating solution should be carefully prepared in a separate mixing tank and then run into the dipping vat. After adding the dry chemical to the water the mixture should be stirred until it is dissolved. To avoid dust, bags should be immersed below water level and then opened. In order to insure best results, the dipping tank must be protected from rain. The treated lumber should not be allowed to remain unprotected in heavy rains, especially just after dipping. Lumber piles should be raked, and added pile space should be left between boards, and stacks. Green lumber should not be used for stickers. Stacks should be at least one foot above the ground and weeds and other hindrances to good air movement eliminated.

\*Farm and Home\* use of this product is prohibited.

## STORAGE AND DISPOSAL

**PROHIBITIONS:** Do not contaminate water, food or feed by storage or disposal.

**PESTICIDE DISPOSAL:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL:** Completely empty liner by shaking and tapping sides to loosen clinging particles. Empty residue into application equipment. Then dispose of liner in a sanitary landfill or by incineration, if allowed by state and local authorities. If drum cannot be reused, dispose of in the same manner.

## WARRANTY STATEMENT AND DISCLAIMER

Proper application is critical to the effectiveness of the product; however, when applied and used according to this label, NAPCLOR-G is capable of protecting wood for uses described. The actual life of the treatment will be affected by the condition of the wood when treated, the species of wood, the type of exposure, and previous and subsequent treatments.

**DANGER: READ THE LABEL THOROUGHLY BEFORE USE. COMPLY WITH ALL DIRECTIONS AND WARNINGS GIVEN, AND USE COMMON SENSE IN HANDLING.**

CHAPMAN MAKES NO WARRANTIES, EITHER EXPRESS OR IMPLIED, OTHER THAN AS SET FORTH ON THIS LABEL, AND CHAPMAN DISCLAIMS ANY IMPLIED WARRANTY OR MERCHANTABILITY NOT SPECIFICALLY SET FORTH ON THIS LABEL. CHAPMAN SHALL NOT BE RESPONSIBLE FOR ANY PERSONAL INJURY OR PROPERTY DAMAGE OR OTHER TYPE OF LOSS RESULTING FROM FAILURE TO FOLLOW THE DIRECTIONS FOR USE, WARNINGS AND PRECAUTIONARY LANGUAGE GIVEN ON THIS LABEL. CHAPMAN SHALL NOT BE RESPONSIBLE FOR DAMAGE TO PROPERTY BEYOND THE PURCHASE PRICE OF THIS PRODUCT, HOWEVER, SOME STATES DO NOT ALLOW THE INCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THIS LIMITATION MAY NOT APPLY TO YOU.