



BUCHANAN SPECIAL BLEND STAIN CONTROL

NET CONTENTS _____ POUNDS

3-5-74

FOR CONTROL OF BLUE STAIN AND MOLD IN SOFTWOODS AND HARDWOODS.

1022-475

DIRECTIONS

To control blue stain and mold in softwoods and hardwoods best results will be obtained if the lumber is dipped within 24 hours of cutting. If lumber is not dipped within 24 hours interior stain may result.

For lumber 2 inches or less in thickness, dissolve one 10-pound bag in 100 U.S. gallons of water. Warm water will hasten solution. For thicker lumber, or bundled lath or shook, or during periods of severe stain inducing weather, dissolve the contents of one 10-pound bag in 50 to 75 U.S. gallons of water. A dip of 15 seconds or more is sufficient. The treating solution should be carefully prepared in a separate mixing tank and then run into the dipping vat. After adding the dry chemical to the water the mixture should be stirred until it is all dissolved. To avoid dust, bags should be immersed below water level and then opened.

In order to insure best results, the dipping tank must be protected from rain. The treated lumber should not be allowed to remain unprotected in heavy rains, especially just after dipping. Lumber piles should be roofed, and adequate space should be left between boards and stacks. Green lumber should not be used for sticker.

INGREDIENT STATEMENT

ACTIVE INGREDIENTS:

Sodium pentachlorophenate	55.3%*	55.3%*
Sodium Salts of other Chlorophenols		7.7%*
Borax (Sodium tetraborate decahydrate)		30.0%

INERT INGREDIENTS:

	7.0%
	100.0%

*Equivalent to 70% by weight technical sodium pentachlorophenate

WARNING

KEEP OUT OF REACH OF CHILDREN!

Do not reuse empty Container. Destroy it by burying with waste or burning. Stay away from smoke or fumes.

Harmful dust. Avoid breathing dust. Use in mechanically operated equipment only. Lumber wet with solution should be handled with rubber hand protectors.

Causes skin irritation. Harmful if swallowed. Do not breathe dust or spray mist. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling.

In case of swallowing, induce vomiting by giving an emetic such as a tablespoon of mustard in water. Then give flour and water or raw egg white beaten and CALL A DOCTOR.

CAUTION

This product is toxic to fish and wildlife. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on the label.

NOTICE

Neither the manufacturer nor the seller makes any representation or warranty expressed or implied, concerning this material except that it is of standard quality. Neither shall be held responsible in any manner for any personal injury, property damage or other type of loss resulting from handling, storage or use of this material when such use and/or handling is contrary to label instructions.

EPA Reg. No. 1022-475

MANUFACTURED BY **CHAPMAN CHEMICAL COMPANY** MEMPHIS, TENNESSEE