



PERMATOX 181

NET CONTENTS _____ GALLONS

CONCENTRATE FUNGICIDE FOR CONTROL OF BLUE STAIN AND MOLD IN FRESH CUT LUMBER AND TIMBER

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS & DOMESTIC ANIMALS WARNING

Causes skin irritation and may produce delayed chemical burns. Harmful or fatal if swallowed or absorbed through the skin. May cause severe eye damage. Do not get in eyes, on skin or on clothing. Avoid breathing spray mists or vapors. Wear goggles or face shield and rubber gloves when handling Permatox 181 and rubber gloves and protective clothing when handling the freshly treated lumber. Avoid contamination of feed and foodstuffs.

Keep away from animals.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL AND CHEMICAL HAZARDS

Treated sawdust and other wood waste should not come in contact with domestic animals or be used so that they will come in contact with useful living plants.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

PROHIBITIONS Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL Pesticide spray mixture or rinsate that cannot be used or chemically reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies.

CONTAINER DISPOSAL Triple rinse (or equivalent) and offer for recycling, reconditioning or disposal in an approved landfill or bury in a safe place.

GENERAL Consult Federal, State or local disposal authorities for approved alternative procedures.

INGREDIENT STATEMENT

ACTIVE INGREDIENTS

Sodium Pentachlorophenate 21.36%
Sodium Salts of other
chlorinated phenols 2.48%

INERT INGREDIENTS 76.16%

TOTAL 100.00%

CONTAINS METHANOL

1022-481

READ THIS LABEL BEFORE USING PRODUCT

KEEP OUT OF REACH OF CHILDREN WARNING

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED, drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink several glasses of water and induce vomiting. Avoid alcohol and consult a doctor.

IF IN EYES, immediately flush with large quantity of water for at least 15 minutes and get medical attention. IF ON SKIN, flush with water. Remove and wash contaminated clothing before reuse.

SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS

EPA Est. 1022 TN - 1
EPA Reg. No. 1022-481

GENERAL: Permatox 181 is a concentrated liquid product readily miscible with water. It may be mixed with water by ordinary means or through the CHAPMAN SURE-MIX proportioning device or Dispenser.

When mixing a batch of Permatox 181 solution by ordinary means it is best to add part of the water to the mixing tank, then add the measured amount of Permatox 181 and follow with the balance of water, rinsing out the measuring container into the mixing tank at the same time.

It is recommended that plastic-coated synthetic rubber, liquid proof gloves be worn during preparation of the mixture or handling of the treated lumber while wet.

Delayed treatment may allow interior stain to develop, so lumber should be treated within 24 hours of cutting by a dip or spray application of Permatox 181. Freshly treated lumber should be protected from rain. Dipping tanks should also be protected from over-dilution by rainfall and sawdust should be raked out daily.

Approved stacking practices should be employed with adequate space between boards and stacks. Green lumber or infected wood should not be used for stickers. The bottoms of the stacks should be well above the ground with weeds and debris kept away from stacks.

TREATMENT: For lumber 2 inches or less in thickness, combine one gallon of Permatox 181 with 100 gallons of water. For thicker lumber or timbers or bundled, lath or shank, or under unusually severe or lengthy periods or conditions favorable to sapstain and mold development, combine one gallon of Permatox 181 with 30 to 50 gallons of water. A dip of 15 seconds or more is sufficient.

NOTICE

This company warrants that this material conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in accordance with directions under normal conditions of use, but neither this warranty nor any other warranty of merchantability or fitness for a particular purpose, expressed or implied, extends to the use of this product contrary to label instructions or under abnormal conditions, or under conditions not reasonably foreseeable to seller and buyer assumes the risk of any such use.