

PM 1000 1994  
340  
**IBC MANUFACTURING COMPANY**

April 21, 1994

(via DHI.)

Ms. Cynthia Giles-Parker (PM-22)  
Registration Division (H7505C)  
Office of Pesticide Programs  
U.S. Environmental Protection Agency  
Document Processing Desk  
Room 266A, Crystal Mall 2  
1921 Jefferson Davis Highway  
Arlington, VA 22202

Dear Ms. Giles-Parker:

**SUBJECT: NOTIFICATION** - Update Environmental Hazard Statement in  
Accordance to PR-Notice 93-3

Product Labels:	PQ-15 RTU	1022-491
	WOODGUARD	1022-514
	CUNAPSOL-1	1022-518
	CUNAPSOL-5	1022-522
	WEED FREE G	1022-271

Enclosed, please find a copy of the subject product labels for which IBC Manufacturing Co. has updated the Environmental Hazard Statement as per PR-Notice 93-3.

We have incorporated the exact wording as recommend in the PR-Notice, therefore, the submission is being submitted as a **NOTIFICATION**.

The distributors have been notified by IBC Manufacturing Co. to change the Environmental Hazard Statement on their label accordingly.

Thank you for your attention to this matter.

Sincerely,

**IBC MANUFACTURING COMPANY**

*S. Khattar*

Sangeeta V. Khattar  
Registrations Representative

svk/199  
Enclosures

2087

Net Contents:

Logo:

**PQ-15 R•T•U  
Above-Ground Clear Water Repellent**

**Paintable - Stops Rot  
An Ideal Underseal for Paint/Improves Adhesion  
Controls Warping & Swelling/Retards Insect Attack**

**Ingredient Statement**

**Active Ingredient:**

Copper 8-quinolinolate ..... 0.25%

**Inert Ingredients:** ..... 99.75%

**Total:** .....100.0%

This product contains Petroleum Distillates

EPA Reg. No. 1022-491

EPA Est. No. 1022-TN-1

**KEEP OUT OF REACH OF CHILDREN**

**CAUTION**

**See Precautionary Statements**

**IBC MANUFACTURING COMPANY  
416 East Brooks Road - P.O. Box 9158  
Memphis, TN 38109**

**CONTROLS WARPING AND SWELLING:** Under ordinary conditions of exposure, wood to which this preservative has been applied will not pick up noticeable amounts of moisture. Thus, wood so treated has dimensional stability and the possibility of warping, swelling, or shrinking in service is greatly reduced.

**PAINTABLE:** An excellent underseal to provide moisture barrier for paint protection. May be painted with all oil base paints and latex type paints.

---

### **DIRECTIONS FOR USE**

---

It is a violation of Federal law to use this product in a manner inconsistent with its label. Stir or shake well before use. All cutting should be completed before application. Wood must be clean, dry and free from previous finishes. Apply by spraying or brushing of multiple flowing coats. The most effective treatment is obtained with pressure treating or extended soaking where deep penetration and high absorption are obtained. A soaking period of five minutes per inch of thickness is recommended.

Pay particular attention to the treatment of joints and exposed end grain of the wood. It is here that moisture absorption is many times greater than the flat or edge grain surfaces.

**COVERAGE:** Varies by species and condition of wood. 150 to 200 square feet per gallon for spray or brush application. Five to ten gallons per thousand board feet for soaking.

**PAINTING:** Treated wood must be thoroughly dry (after solvent has completely evaporated) before application of paint. Usually 24 to 48 hours drying time is required.

**PLANT LIFE:** When applying, avoid contact with grass, shrubs or trees. When thoroughly dry, treated wood is harmless to plant life.

---

### **STORAGE AND DISPOSAL**

---

Do not reuse empty container. Rinse thoroughly before discarding in trash. Securely wrap original container in several layers of newspaper and discard in trash.

---

### **WARRANTY STATEMENT AND DISCLAIMER**

---

Proper application is critical to the effectiveness of the product; however, when applied and used according to this label, this product is capable of protecting wood under the conditions described above. The performance of the treatment will be affected by the condition of the wood when treated, the species of wood, the type of exposure, and previous and subsequent treatments.

**READ THE LABEL THOROUGHLY BEFORE USE, COMPLY WITH ALL DIRECTIONS, AND USE COMMON SENSE IN HANDLING.**

IBC MANUFACTURING CO. MAKES NO WARRANTIES EITHER EXPRESS OR IMPLIED OTHER THAN WHAT IS SET FORTH ON THE LABEL AND CHAPMAN DISCLAIMS ANY IMPLIED WARRANTY OR MERCHANTABILITY NOT SPECIFICALLY SET FORTH ON THIS LABEL. IBC MANUFACTURING CO. SHALL NOT BE RESPONSIBLE FOR DAMAGE TO PROPERTY BEYOND THE PURCHASE PRICE OF THIS PRODUCT: HOWEVER, SOME STATES DO NOT ALLOW THE INCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THIS LIMITATION MAY NOT APPLY TO YOU.

---

**PRECAUTIONARY STATEMENTS**

---

**Hazards to Humans and Domestic Animals****CAUTION**

Harmful if swallowed. Causes moderate eye irritation. Avoid contact with skin, eyes or clothing. Contains Petroleum Distillates and Copper-8-quinolinolate.

Do not take internally. Avoid breathing of vapors. Use only in a well ventilated area. Vapors may cause injury if adequate ventilation is not insured. Wash thoroughly with soap and water after handling. Close container after each use. Keep preservative and freshly treated wood away from flame, foodstuffs and plants. Do not use this product in any confined area where vapors may concentrate and cause injury to plant or animal life.

**FIRST AID**

**IF SWALLOWED:** Do not induce vomiting. Call your poison control center, hospital emergency room or physician immediately.

**IF IN EYES:** Flush with plenty of water. If irritation persists, get medical attention.

---

**ENVIRONMENTAL HAZARDS**

---

This product is toxic to fish. For terrestrial uses, do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment washwaters.

---

**PHYSICAL AND CHEMICAL HAZARDS**

---

Do not use or store near heat or open flame.

---

**RECOMMENDED USES**

---

This water-repellent wood preservative is a ready-to-use solution for unfinished wood and wood products...millwork, fences, siding, decks, shingles, outdoor furniture, structural lumber and many others. Apply by spraying, brushing, soaking, pressure treating or dipping. For below grade, use Cunapsol-1 for lasting protection.

**CONTROLS ROT-STAIN MOLD:** Contains copper 8 quinolinolate which controls rot-producing fungi. Use before painting on new wood to give penetrating protection to wood fibers not normally reached by surface coatings.

**INHIBITS ATTACKS BY TERMITES:** Termites can seriously damage wood used in building construction. This product provides penetrating protection through soaking, brush or flood spray application.

4