CHAPMAN

POL-NU 20-20

NET CONTENTS _____ POUNDS

PENTA PRESERVATIVE GREASE
ESPECIALLY RECOMMENDED
GROUNDLINE TREATMENT

FOR CONTROL OF DECAY AND AIDS IN THE PROTECTION AGAINST TERMITES.

Extends Service Life of Standing Poles and Posts.

INGREDIENTS

[illegible]

WARNING

KEEP OUT OF REACH OF CHILDREN

[illegible] or fatal if swallowed or [illegible] through skin. Causes skin irritation. Do not breathe vapor. Do [illegible] eyes, [illegible] skin, or on clothing [illegible] thoroughly after handling with [illegible] and warm water. [illegible] from foodstuffs, children, [illegible] livestock. In case of swallowing [illegible] vomiting by administering emetic. CALL A PHYSICIAN IMMEDIATELY. Inflammable - Keep away from fire and flame.

This product is toxic to fish and wildlife. Keep out of lakes, streams and ponds. DO NOT CONTAMINATE WATER BY CLEANING OF EQUIPMENT, OR DISPOSAL OF WASTES. APPLY THIS PRODUCT ONLY AS SPECIFIED ON THIS LABEL.

Do not reuse container. Destroy when empty.

MANUFACTURED BY **CHAPMAN CHEMICAL COMPANY** MEMPHIS, TENNESSEE

APPLICATION TO POLES

POL-NU 20-20 can best be applied to poles by using the CHAPMAN POL-NU BANDAGE MAKER and POL-NU paper. For application to deep checks in poles or timber, fill a caulking gun POL-NU [illegible] and apply. Any grease equipment that will handle No. [illegible] grease will work with POL-NU 20-20. Excavate the soil away from the poles to a depth of about 15 inches. Wire brush the pole surface to remove adhering soil. Scrape off any decay in the surface. It is also desirable to take increment borings directed toward the center of the pole. Holes should be plugged with wood plugs or treated wood plugs. If decay is present in the center of the pole, consideration should be given to its early replacement or stubbing.

POL-NU 20-20 will penetrate wet wood. It is not necessary to leave excavated poles exposed in order to dry out.

POL-NU 20-20 should be applied in a [illegible] inch thickness. More may be required for special conditions. CHAPMAN POL-NU BANDAGE MAKER is adjustable up to 3/8 of an inch. Bandages may be prepared to cover ground-line areas of poles in bands 18 to 22 inches in height. (The POL-NU BANDAGE MAKER produces a 22 inch band of grease. A template furnished separately may be inserted to obtain an 18 inch band.

POL-NU 20-20 should be applied to cover the pole surface 4 inches below the last evidence of decay and 3 inches above the ground-line. More than one bandage may be used in special cases where the pole area to be covered spans a height greater than 22 inches, such as on hillsides, etc. POL-NU can be used to advantage on sills, headers, joists and other members beneath subfloors in wood bridge maintenance, or on re-adzed railroad tie surfaces. It should be applied at points where condensation is likely to gather and at places where end grain wood butts against concrete or wood. No covering is needed as in the case of wood in ground contact. Since a reservoir of preservative is then at the wood surface it can work its way into the wood to give deep penetration. POL-NU can also be applied to the ground-line area of fence posts and pilings following the same general procedures outlined for treating poles.

NOTICE

Neither the manufacturer [illegible] [illegible]