

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
DANGER**

May be fatal if swallowed, inhaled, or absorbed through skin. Do not get in eyes, on skin, or on clothing. Causes delayed chemical burns. Do not take internally. Do not breathe vapors. Use with adequate ventilation. Wash thoroughly after skin contact, and before eating, drinking, use of tobacco products, or using restrooms.

The U.S. EPA has determined that pentachlorophenol can produce defects in the offspring of laboratory animals. Exposure to pentachlorophenol during pregnancy should be avoided. Applicators must wear gloves impervious to the wood treatment formulations (e.g., polyvinyl acetate (PVA), polyvinyl chloride (PVC), or neoprene). In all situations where dermal contact is expected (e.g., during the actual application process and when handling freshly treated wood).

Applicators must wear long sleeved shirts, long pants, and an impermeable apron during the application and mixing processes and all situations where dermal contact is expected.

Work clothing must be changed when it shows signs of contamination. Launder work clothing separately from other household clothing. Dispose of worn-out work clothing and workshoes or boots in any general landfill, in the trash, or in any other manner approved for pesticide disposal.

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation.

Wash thoroughly after skin contact, and before eating, drinking, use of tobacco products, or using restrooms.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL AND CHEMICAL HAZARDS

Do not use or store near heat or open flame. Close container after each use.

STORAGE AND DISPOSAL

PROHIBITIONS: Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

RESTRICTED USE

For sale to and use only by certified applicators or by persons under their supervision and only for those uses covered by the certified applicators' certification.

**POL-NU 20-20
PENTA PRESERVATIVE GREASE
WITH CREOSOTE ADDED
GROUNDLINE TREATMENT
FOR CONTROL OF DECAY AND AIDS IN THE PROTECTION
AGAINST TERMITES
Extends Service Life of Standing Poles and Posts**

INGREDIENTS

| | |
|--------------------------------|----------------|
| ACTIVE INGREDIENTS: | |
| Pentachlorophenol..... | 17.89%* |
| Other Chlorinated Phenols..... | 2.11%* |
| Creosote..... | 20.00% |
| Aromatic Petroleum Derivative | |
| Solvents..... | 50.95% |
| INERT INGREDIENTS..... | 9.05% |
| TOTAL..... | 100.00% |

**KEEP OUT OF REACH OF CHILDREN
DANGER**

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to and unconscious person.

IF IN EYES: Flush with plenty of water. Call a physician.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove victim to fresh air. Get medical attention.

NOTE TO PHYSICIAN: This product is a metabolic stimulant.

Causes hyperthermia. Treat symptomatically.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

**MANUFACTURED BY
CHAPMAN CHEMICAL COMPANY
MEMPHIS, TENNESSEE 38109**

EPA Reg. No. 1022-490

EPA Est. No. 1022-TN-1

NET CONTENTS _____ LBS.

ACCEPTED

MAR 14 1988

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
Registered under
EPA Reg. No. 1022-496

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

APPLICATION TO POLES

POL-NU 20-20 can best be applied to poles by using the CHAPMAN POL-NU BANDAGE MAKER and POL-NU paper. For application to deep checks in poles or timber, fill a caulking gun with POL-NU 20-20 and apply. Any grease equipment that will handle No 2 cup grease will work with POL-NU 20-20.

Excavate the soil away from the poles to a depth of about 18 inches. Wire brush the pole surface to remove adhering soil. Scrape off any decay on the surface. It is also desirable to take increment borings directed towards the center of the pole. Holes should be plugged with locust plugs or treated wood plugs. If decay is present in the center of the pole, consideration should be given to its early replacement or stubbing.

POL-NU 20-20 will penetrate wet wood. It is not necessary to leave excavated poles exposed in order to dry out.

POL-NU 20-20 should be applied in a 1/4 inch thickness. More may be required for special conditions. (CHAPMAN POL-NU BANDAGE MAKER is adjustable up to 3/8 inch. Bandages may be prepared to cover groundline areas of poles in bands 16 to 22 inches in height. The POL-NU BANDAGE MAKER produces a 22 inch band of POL-NU 20-20. A template furnished separately may be inserted to obtain an 18 inch band.) POL-NU 20-20 should be applied to cover the pole surface 4 inches below the last evidence of decay and 3 inches above the ground line. More than one bandage may be used in special cases where the pole area to be covered spans a height greater than 22 inches, such as on hillsides, etc.

OTHER USES

When structures are built with unpreserved woods that are susceptible to decay, carpenter ants, and powder post beetles, there exists a need for preservation of these parts. POL-NU 20-20 can also be applied to the ground line area of fence posts and pilings following the same general procedure outlined for treating poles.

NOTICE

Neither Chapman Chemical Company nor the seller makes any representation of warranty, express or implied, concerning the use of this material, other than indicated on the label. Neither shall be held responsible in any manner for any person's injury or property damage or other type of loss resulting from improper handling, storage or use of this material. The buyer accepts and uses this material on these conditions.