1022-504

Net Contents:

# PQ-56 RTU

Controls Fungus, Stain and Mold Protects Against Termites

#### **Ingredient Statement**

| Active Ingredient:<br>Copper 8-quinolinolate | 0.8%   |
|--|--------|
| Inert Ingredients:                           |        |
| Total:                                       | 100.0% |

EPA Reg. No. 1022-504

EPA Est. No. 1022-TN-1

# **KEEP OUT OF REACH OF CHILDREN**

## DANGER

ł

)

)

## See Precautionary Statements

PQ 56 RTU is a clear, water repellent, EPA registered, water-based wood preservative and insecticide treatment for wood above ground. It is suitable for interior and exterior use. When applied as directed, PQ 56 RTU provides protection against attack from termites and other wood eating insects, sapstain and decay fungi, including mildew, mold, rot and decay organisms. It also controls warping, swelling and end-checking caused by moisture absorption. This preservative has a "milky" look in the can that dries to a clear finish on wood. It has very little if any residual treatment odor after it has dried.

#### IBC MANUFACTURING COMPANY 416 East Brooks Road - P.O. Box 9158 Memphis, TN 38109

Į

| 06/14/2001 |  |  |
|------------|--|--|
|            | ACCEPTED   |  |
|            | JUN 1.4 2001   |  |
|            | Under the Federal Insecticide, Fungicide, and<br>Rodenticide Act as amended, for the |  |

EPA Reg. No.

### PRECAUTIONARY STATEMENTS

#### Hazards to Humans and Domestic Animals

#### DANGER

Corrosive. Causes irreversible eye damage. Do not get in eyes or on clothing. Wear protective eyewear (goggles, face shield or safety glasses). Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Remove and wash contaminated clothing before reuse.

#### **FIRST AID**

1

)

)

**IF SWALLOWED:** Call a Poison Control Center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a Poison Control Center or doctor. Do not give anything by mouth to an unconscious person.

**IF ON SKIN OR CLOTHING:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15 – 20 minutes. Call a Poison Control Center or doctor for treatment advice.

**IF IN EYES:** Hold eye open and rinse slowly and gently with water for 15 - 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a Poison Control Center or doctor for treatment advice.

**IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. Call a Poison Control Center or doctor for treatment advice.

1

Have the product container or label with you when calling a Poison Control Center or doctor, or going for treatment. For spills or emergencies, call Chemtrec at 1-800-424-9300.

PQ-56 RTU

Personal Protective Equipment (PPE):

Handlers must wear:

- Long sleeved shirt and long pants.
- Socks and shoes.
- Goggles or face shield.
- Chemical resistant gloves, (such as made out of barrier laminate, or any of the following types of gloves at ≥ 14 mils thickness; butyl rubber, nitrile rubber, neoprene rubber, polyvinyl chloride, and viton).

User Safety Requirements:

Follow manufacturer's instructions for cleaning / maintaining PPE. If no such instructions for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

User Safety Recommendations:

User must wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. Users must remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.

Users must remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.

#### **ENVIRONMENTAL HAZARDS**

)

For terrestrial uses, do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark.

Do not contaminate water by cleaning of equipment or disposal of wastes.

DO NOT discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. DO NOT discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the Environmental Protection Agency.

#### DIRECTIONS FOR USE

)

.1

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PQ 56 RTU requires no dilution before use. Use as received, following label directions. Wood treated with this preservative is suitable for incidental food contact, such as picnic tables and wooden baskets or crates holding raw agricultural produce.

**Recommended Uses:** Decks, Fences, furniture, greenhouse items, fruit and vegetable bins, playground equipment, windows, sills and frames, fascia boards, porches, siding, shakes, shingles, doors. Note: For portions of the wood in actual contact with soil or ground, we recommend using pressure treated lumber or lumber treated with Cunapsol TM brand wood preservative.

**Before you start**: Make sure wood is dry and free of dust, dirt and debris. Prior treatments or coatings should be removed before application for maximum penetration.

**Application Procedures**: For best results, apply when temperatures are between 50\* and 90\*F and (when treating exterior wood) when 24 hours of precipitation free weather is expected. Apply by dip treatment, brush roller or pump-up type sprayer. The best results will be obtained if wood to be treated is immersed for 3 minutes or longer. If dipping is not possible, apply liberally by brush, roller or spray. Coverage is about 200 sq. ft. per gallon for brush, roll or spray and 100 sq. ft. per gallon for dip application.

**Subsequent treatments**: If a stain or paint is desired after use, it is necessary to wait 72 hours in dry weather conditions after application of PQ 56 RTU. PQ 56 RTU must be thoroughly dry prior to top coating. Prime the surface with an oil-based primer before painting. Failure to allow for dry time can result in improper paint adhesion.

**Clean Up:** Clean tools and equipment after use with soap and water.

#### STORAGE AND DISPOSAL

**PROHIBITION:** Do not contaminate water, food, or feed by storage or disposal.

**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

### WARRANTY STATEMENT AND DISCLAIMER

Seller warrants to those persons lawfully acquiring title to this product that at the time of the first sale of this product by seller that this product conformed to its chemical description and was reasonably fit for the purposes stated on the label when used in accordance with Seller's directions under normal conditions of use and Buyers and users of this product assume the risk or any use contrary to such directions. SELLER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS OR OF MERCHANTABILITY, AND NO AGENT OF SELLER IS AUTHORIZED TO DO SO. In no event shall Seller's liability for any breach of warranty exceed the purchase price of the material as to which a claim is made.

Buyers and users of this product are responsible for all loss or damage from use or handling of this product which results from conditions beyond the control of Seller, including, but not limited to, incompatibility with other products unless otherwise expressly provided in the Directions for Use of this product, weather conditions, moisture conditions or other environmental conditions outside the ranges that are generally recognized as being conducive to good industrial and/or application practices.

ł

}