

COPPER NAPHTHENATE 1%



WOOD PRESERVATIVE

Ready-to-Use
ACCEPTED

NET CONTENTS _____ GAL.

SEP 23 1982

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 1022-507

PRECAUTIONARY STATEMENTS

WARNING

Hazards to Humans and Domestic Animals

Do not breathe fumes. Use outdoors with adequate ventilation.

Do not get in eyes. In case of skin contact wash with soap & water. Prolonged contact with skin may cause irritation. Remove contaminated clothing and wash skin with soap and water. Protective gloves normally not needed. Use chemical resistant gloves if you have contact with wet material. Eye protection normally not required.

ENVIRONMENTAL HAZARDS

Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wash water.

PHYSICAL AND CHEMICAL HAZARDS

Do not use or store near heat or open flame.

DIRECTIONS FOR USE

Read and follow all directions on Federal Label for use of this material in manner inconsistent with this labeling.

STORAGE AND DISPOSAL

PROHIBITIONS Do not contaminate water by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL Pesticide spray mixtures or residue water that cannot be used according to label instructions should be disposed of as follows:

1. Federal, State or local procedures.

CONTAINER DISPOSAL Triple rinse containers. Then offer for recycling or reconditioning, or to be used and disposed of as sanitary landfill, or by other approved State and local procedures.

GENERAL Consult Federal, State or local disposal authorities for approved alternative procedures.

INGREDIENTS

ACTIVE INGREDIENTS:

Copper naphthenate 7.5%*

INERT INGREDIENTS 92.5%

*Equivalent to 1% metallic copper

KEEP OUT OF REACH OF CHILDREN

WARNING

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES, immediately flush with large quantity of water and get medical attention.

IF ON SKIN, flush with water. Remove and wash contaminated clothing before reuse.

IF SWALLOWED, do not induce vomiting. Drink several glasses of water and consult a doctor.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

EPA Reg No. 1022-507
EPA Est No. 1022-TN-1

RECOMMENDED FOR

Windows, window frames, doors, stairs, porches, shingles, trellises, steps, subflooring, interior trim, wall paneling, furniture, fence pickets, fence rails, furring strips, arbors, flooring and beverage cases. Powder post beetles which invade furniture, flooring and structural lumber are killed by application of this preservative. These insects will not attack the treated wood.

In addition to preventing decay, blue stain, and insect attack on wood this preservative controls warping, swelling, shrinking, and end checking caused by changes in moisture content of lumber and plywood products.

Wood to be protected against subterranean termites should be treated before use in construction. Termites will not attack wood treated with Copper Naphthenate 1% Wood Preservative.

GENERAL DIRECTIONS

Copper Naphthenate 1% requires no dilution before use. Use as received, following label directions. It is intended for wood products that usually require painting or staining such as millwork and the like or in special situations to treat lumber for long storage in the open by simple to press air method.

The best results will be obtained if wood to be treated is immersed for 3 minutes or longer. If dipping is not possible, 2 liberal brush or spray applications should be applied. Allow at least 1 hour between applications. Make certain all areas are fully treated to get the maximum benefit. Allow 24 hours or longer after application of the preservative prior to painting.

WARRANTY STATEMENT

Neither Chapman Chemical Company nor the seller makes any representation or warranty, expressed or implied, concerning this material, other than indicated on the label. Neither shall be held responsible in any manner for any personal injury or property damage or other type of loss resulting from the improper handling, storage or use of this material. The buyer accepts and uses this material on these conditions.

9/82

MANUFACTURED BY **CHAPMAN CHEMICAL COMPANY** MEMPHIS, TENNESSEE 38109

A KemaNobel Company