

CHAPMAN

**RESTRICTED USE PESTICIDE**

For sale to and use only by certified applicators or persons under their supervision and only for those uses covered by the certified applicators' certification

Batch Number \_\_\_\_\_  
Net Contents \_\_\_\_\_  
Date Packaged \_\_\_\_\_**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND  
DOMESTIC ANIMALS  
DANGER**

May be fatal if swallowed inhaled or absorbed through skin. Causes delayed chemical burns. Do not take internally. Do not breathe vapors. Use with adequate ventilation. Wash thoroughly after skin contact before eating, drinking, use of tobacco products, or using restrooms.

The U.S. EPA has determined that pentachlorophenol can produce defects in the offspring of laboratory animals. Exposure to pentachlorophenol during pregnancy should be avoided.

**FOR POWDER FORMULATIONS OF PENTACHLOROPHENATE** Until August 31, 1987, a closed emptying and mixing system must be used or protective clothing (including respirator, gloves, and long-sleeved shirts and long pants or disposable overalls) must be worn when emptying and mixing powder formulations of pentachlorophenolate. After September 1, 1987, a closed system must be used when emptying and mixing powder formulations of pentachlorophenolate. A closed system is defined as any containment which prevents the release of subject chemicals into the surrounding external environment, except that release of incidental amounts of chemical during equipment loading and periodic clean-out or maintenance operations shall not be deemed a breach of containment.

**FOR THE SPRAY METHOD OF APPLICATION** Spray apparatus must (1) be operated so as to minimize overspray (i.e., no visible mist) and (2) be free of leaks in the system. Should there be a visible mist, spray applicators in the vicinity of the spray apparatus (the zone in which the mist is visible) must wear a respirator and protective clothing, (including overalls, jacket, gloves, boots, and head covering) impervious to the wood treatment formulation, and goggles.

Individuals who enter, clean or repair vats, tanks or other related equipment that is contaminated with the treatment solution must wear a respirator. In addition, where dermal contact is expected, these individuals must wear overalls, jackets, boots, head covering impervious to the wood treatment formulation, and goggles.

Applicators must wear gloves impervious to the wood treatment formulation in all situations where dermal contact is expected (e.g., during the actual application process and when handling freshly treated wood). Protective clothing must be changed when it shows signs of contamination. Applicators must leave all protective clothing, workshoes or boots, and equipment at the plant. *Worn out protective clothing, and workshoes or boots must be left at the plant and disposed of in any general landfill, in the trash, or in any other manner approved for pesticide disposal.*

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation.

**NOTE TO USER:** As used on this label, the term "respirators" means properly fitting, well-maintained, half-mask canister or cartridge respirators which are NIOSH/NIOSH approved for organic vapors. Examples of acceptable materials for protective clothing (e.g., gloves, overalls, jackets and boots) required during application and handling of pentachlorophenolate are polyvinyl acetate (PVA), polyvinyl chloride (PVC), neoprene, NBR (Buna-N), and nitrile.

**ENVIRONMENTAL HAZARDS**

This product is toxic to fish and wildlife. Do not apply directly to water. Do not apply where runoff is likely to occur. Do not apply when weather conditions favor drift from areas treated. Do not contaminate water by cleaning of equipment or disposal of wastes.

**PHYSICAL AND CHEMICAL HAZARDS**

Do not use or store near heat or open flame. Close container after each use.

**QUANCIDE-3**

FUNGICIDE CONCENTRATE

Controls Sapstain and Mold in

Fresh Cut Lumber and Other Wood Products

**INGREDIENTS****ACTIVE INGREDIENTS:**

Sodium Pentachlorophenate	36.9%
Sodium Tetraborate, Anhydrous	59.0%
INERT INGREDIENTS	4.1%
<b>TOTAL</b>	<b>100.00%</b>

Chapman Chemical Company has complied with all terms and conditions of the registration governing the composition of this product as approved by the United States Environmental Protection Agency under Section 3 of the Federal Insecticide, Fungicide, and Rodenticide Act.

Keep Out of Reach of Children

**DANGER****STATEMENT OF PRACTICAL TREATMENT**

**IF SWALLOWED:** Call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.

**IF IN EYES:** Flush with plenty of water. Call a physician.

**IF ON SKIN:** Wash with plenty of soap and water. Get medical attention.

**IF INHALED:** Remove victim to fresh air. Get medical attention.

**NOTE TO PHYSICIAN:** This product is a metabolic stimulant. Treatment is supportive. Forced diuresis may be effective to reduce total body burden. Treat hyperthermia with physical measures. Do not administer aspirin, phenothiazines, or atropine since they may enhance toxicity.

**SEE SIDE PANEL FOR ADDITIONAL  
PRECAUTIONARY STATEMENTS**

EPA Est. No. 1022-TN-1

EPA Reg. No. 1022-508

MANUFACTURED BY  
**CHAPMAN CHEMICAL COMPANY**  
MEMPHIS, TENNESSEE 38109

**BEST AVAILABLE COPY****DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Use of this product for any purpose other than those stated on the label, including the use of this product in the manufacture and formulation of other pesticide products or in repackaging of this product is prohibited.

To control bluestain and mold in softwoods and hardwoods best results will be obtained if the lumber is dipped within 24 hours of cutting. If the lumber is not dipped within 24 hours incense stain may result.

"Farm and Home" use of this product is prohibited.

Quancide-3 is packed in a water soluble bag placed inside a polyethylene bag to prevent deterioration of the inner bag by humidity. For lumber 2 inches or less in thickness, remove one 10 pound water soluble bag and place it in 100 U.S. gallons of water. Warm water will hasten solution of Quancide-3. For thicker lumber or bundled 2" or thicker, dissolve one 10 pound bag of Quancide-3 in 50 to 75 U.S. gallons of water. A dip of 15 seconds or more is sufficient. The dipping solution should be prepared in a separate mixing tank and then run into the dipping vat.

After adding a water soluble bag of the chemical to the water the mixture should be stirred or agitated until the chemical completely dissolves. Care must be taken to insure that the water soluble bag is removed from the polyethylene bag in order to insure best results. The dipping tank must be protected from rain. The treated lumber should not be allowed to remain unprotected in heavy rains, especially just after dipping. Lumber piles should be roofed, and adequate space should be left between boards and stacks. Green lumber should not be used for sticks.

**STORAGE AND DISPOSAL**

**PROHIBITIONS:** Do not contaminate water, food or feed by storage or disposal.

**PESTICIDE DISPOSAL:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL:** Completely empty liner by shaking and tapping sides to loosen clinging particles. Empty residue into application equipment. Then dispose of liner in a sanitary landfill or by incineration, if allowed by state and local authorities. If drum cannot be reused, dispose of in the same manner.

**WARRANTY STATEMENT  
AND DISCLAIMER**

Proper application is critical to the effectiveness of the product however, when applied and used according to this label, QUANCIDE-3 is capable of protecting wood under the conditions described above. The performance of the treatment will be affected by the condition of the wood when treated, the species of wood, the type of exposure and previous and subsequent treatments.

**DANGER: READ THE LABEL THOROUGHLY BEFORE USE, COMPLY WITH ALL DIRECTIONS AND WARNINGS GIVEN, AND USE COMMON SENSE IN HANDLING.**

NEITHER CHAPMAN CHEMICAL COMPANY NOR THE SELLER MAKES ANY REPRESENTATION OF WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE USE OF THIS MATERIAL, OTHER THAN AS SET FORTH ON THIS LABEL, AND CHAPMAN DISCLAIMS ANY IMPLIED WARRANTY OR MERCHANTABILITY NOT SPECIFICALLY SET FORTH ON THIS LABEL. CHAPMAN SHALL NOT BE RESPONSIBLE FOR ANY PERSONAL INJURY OR PROPERTY DAMAGE OR OTHER TYPE OF LOSS RESULTING FROM FAILURE TO FOLLOW THE DIRECTIONS FOR USE, WARNINGS AND PRECAUTIONARY LANGUAGE GIVEN ON THIS LABEL. CHAPMAN SHALL NOT BE RESPONSIBLE FOR DAMAGE TO PROPERTY BEYOND THE PURCHASE PRICE OF THIS PRODUCT; HOWEVER, SOME STATES DO NOT ALLOW THE INCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THIS LIMITATION MAY NOT APPLY TO YOU.