CHAPMAN AMBRODAN

NET CONTENTS _____ GALLONS

FOR CONTROL OF WOOD DESTROYING BEETLES IN _____ LUMBER

Not for storage or use in or around the home.

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS & DOMESTIC ANIMALS
WARNING

Hazardous if swallowed, inhaled, or absorbed through the skin! Do not get in eyes, on skin or on clothing. Do not breathe spray mist or vapor. When handling freshly treated lumber wear protective clothing and synthetic rubber gloves. When handling AMBRODAN wear clean synthetic rubber gloves, protective clothing and a pesticide respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR Part 11. Do not allow to drift to areas occupied by unprotected humans or beneficial animals. Treated sawdust and other wood waste should not come in contact with domestic animals or be used so that they come in contact with desirable plants or food crops."

ENVIRONMENTAL HAZARDS

This product is toxic to fish, birds, and other wildlife. Keep out of any body of water. Do not apply where runoff is likely to occur. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL CHEMICAL HAZARDS

Do not use or store near heat or open flame.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

PROHIBITIONS: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Do not store at temperature below 20°F.
PESTICIDE DISPOSAL: Pesticide, spray mixture, or rinse water that cannot be used according to label instructions must be disposed of according to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.
CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling, reconditioning, or puncture and dispose in a sanitary landfill or any other approved state and local procedures.
GENERAL: Consult Federal, State or local disposal authorities for approved alternative procedures.

The solution in this can is a concentrate and must be diluted as directed before use.

INGREDIENTS

Active Ingredients:
Endosulfan (Hexachlorohexahydromethano-2, 4, 3-benzodioxathiepin oxide) 24.0%
Xylene 68.0
Inert Ingredients: 8.0
100.0

KEEP OUT OF REACH OF CHILDREN
WARNING
STATEMENT OF PRACTICAL TREATMENT

If swallowed — Call a physician immediately. Gastric lavage is indicated if material was taken internally. DO NOT INDUCE vomiting unless other treatment is not available. Vomiting may cause aspiration pneumonia. If it is necessary to induce vomiting, give victim one or two glasses of water and insert finger in back of throat. Repeat until vomit fluid is clear. Do not induce vomiting or give anything by mouth to an unconscious person.

If inhaled — Remove victim to fresh air. Apply respiration if indicated.

If on skin — Wash immediately with soap and water. Wash contaminated clothing before reuse.

If in eyes — Flush eyes for at least 15 minutes with water. Call a physician immediately.

Antidote

Note to Physicians: Thiodan is a central nervous system stimulant and may cause convulsions. There is no specific antidote. Barbituric acid derivatives may be used in treatment.

See side panel for additional precautions.

EPA Reg No. 1022-512
EPA Est. No. 1022-TN-1

FOR SPRAYING _____ LUMBER

Add one gallon Ambrodan to 50 gallons of water and stir thoroughly to form an emulsion.

Emulsions should be agitated frequently when in mixing tank or sprayer tank. Make sure that the mixture is free of sediment, debris or anything else which might clog the spray nozzle. Strain the solution if necessary, when pouring into the sprayer tank.

FOR DIPPING LUMBER

Ambrosia Beetle Control—Add 2 quarts of Ambrodan to each 100 gallons of solution in the dip tank. Ambrodan may be added after the Dowicide G or Permatox 10-S solutions are prepared. Add directly to the mixing tank or dip tank and agitate to form emulsion.

Lyctus Beetle Control—Add 2 gallons of Ambrodan to each 100 gallons of antistain solution as described above.

Dipping solution to which Ambrodan has been added should be stirred or agitated after it has been allowed to stand overnight or for several hours undisturbed before using.

NOTICE

This company warrants that this material conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in accordance with directions under normal conditions of use, but neither this warranty nor any other warranty of merchantability or fitness for a particular purpose, expressed or implied, extends to the use of this product contrary to label instructions or under abnormal conditions, or under conditions not reasonably foreseeable to seller and buyer assumes the risk of any such use.

1/82

MANUFACTURED BY CHAPMAN CHEMICAL COMPANY MEMPHIS, TENNESSEE 38109