



PERMATOX SN-8EC

NET CONTENTS _____ GALLONS

WOOD PRESERVATIVE - WATER REPELLENT

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS & DOMESTIC ANIMALS

DANGER

Corrosive, causes eye damage and skin irritation.

Harmful or fatal if swallowed or absorbed through the skin. Do not get in eyes, on skin or on clothing. Avoid breathing spray mists or vapors. Wear goggles or face shield and rubber gloves when handling this product and rubber gloves and protective clothing when handling the freshly treated lumber. This product is toxic to domestic animals.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to lakes, streams or ponds.

Do not use indoors or in any confined area where spray mist and vapors may concentrate and cause injury to plants or animals.

Do not contaminate water by cleaning of equipment or disposal of wastes.

Treated sawdust and other wood waste should not be used so that they come in contact with useful living plants.

PHYSICAL & CHEMICAL HAZARDS

Do not use or store near heat or open flame.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

PROHIBITIONS: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide spray mixture or residue that cannot be used according to label instructions must be disposed of according to Federal, State or local procedures under the Resource Conservation and Recovery Act.

CONTAINER DISPOSAL: Triple rinse (or equivalent) and offer for recycling or reconditioning, or dispose of in a sanitary landfill, or by other approved State and local procedures.

GENERAL: Consult Federal, State or local disposal authorities for approved alternative procedures.

WATER REPELLENT—CLEAR—PAINTABLE
STOPS ROT
CONTROLS WARPING—SWELLING

ACTIVE INGREDIENT:

Bis(tributyltin) oxide	8.3%
INERT INGREDIENTS:	91.7%
TOTAL	100.0%

Exceeds NWMA and Fed. MIL
Spec TT-W-572 Swellograph
water repellency requirement.

KEEP OUT OF REACH OF CHILDREN
DANGER

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Immediately flush with large quantity of water for at least 15 minutes and get medical attention. **IF ON SKIN:** flush with water. Remove and wash contaminated clothing before reuse.

IF SWALLOWED: Induce vomiting.
CALL A DOCTOR IMMEDIATELY

**SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS**

EPA Reg No 1022-517
EPA Est No 1022-TN-1

Permatox SN-8EC must be diluted with water before use. Dilute 1 part Permatox SN-8EC with 10 parts water which has been warmed to 100°F. Vigorous agitation is necessary during the dilution.

Permatox SN-8EC emulsions tend to separate if retained for long periods without agitation. Therefore mixing before using is always the best policy.

The diluted concentrate must be protected from freezing.

The best results will be obtained if wood to be treated is immersed for 3 minutes or longer. If dipping is not possible, 2 1/2 inch brush or spray applications should be applied. Allow at least 1 hour between applications. Make certain all areas are fully treated to get the maximum benefits. Allow 24 hours or longer after application of the preservative prior to painting. Less paint is needed over wood treated with this water repellent wood preservative.

Avoid contamination of feed and feedstuffs.

RECOMMENDED USES

Windows, window frames, doors, stairs, porches, shingles, trellises, steps, subflooring, interior trim, wall paneling, furniture, fence pickets, fence rails, furring strips, arbors, flooring and beverage cases.

In addition to preventing decay and blue stain on wood this preservative inhibits warping, swelling, shrinking and end checking caused by changes in moisture content of lumber and plywood products.

WARRANTY STATEMENT

Neither Chapman Chemical Company nor the seller makes any representation or warranty, expressed or implied, concerning use of this material other than indicated on the label. Neither shall be held responsible in any manner for any personal injury or property damage or other type of loss resulting from the improper handling, storage or use of this material. The buyer accepts and assumes all responsibility under the conditions.

ACCEPTED

JUN 30 1981

561

MANUFACTURED BY CHAPMAN CHEMICAL COMPANY

A KemaNobel Company

MEMPHIS, TENNESSEE 38109

21