



Permatox 102

Net Contents _____ gallons

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

May be fatal if swallowed, inhaled or absorbed through the skin.

Causes eye and skin irritation. May produce delayed chemical burns.

Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Lumber wet with solution should be handled with rubber gloves. Avoid contamination of feed or foodstuff.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL AND CHEMICAL HAZARDS

Do not use or store near heat or open flame.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

- **PROHIBITIONS:** Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.
- **PESTICIDE DISPOSAL:** Pesticide spray mixture or rinsate that cannot be used according to label instructions must be disposed of according to Federal, State or local procedures under the Resource Conservation and Recovery Act.
- **CONTAINER DISPOSAL:** Triple rinse (or equivalent) and offer for recycling or reconditioning, or dispose of in a sanitary landfill, or by other approved State and local procedures.
- **GENERAL:** Consult Federal, State or local disposal authorities for approved alternative procedures.

GENERAL

Permatox 102 is a concentrated liquid product readily miscible with water. It may be mixed with water manually or through the CHAPMAN Sure MIX proportioning device.

481

LIQUID FUNGICIDE CONCENTRATE FOR CONTROL OF BROWN MOLE (Cephalosporium fragrans) IN FRESH CUT LUMBER AND TIMBER DURING AIR SEASONING

FOR INDUSTRIAL USE ONLY

ACTIVE INGREDIENTS

Sodium tetrachlorophenate	8.93%
Sodium pentachlorophenate	10.27%
Sodium salts of other chlorinated phenols	3.58%
Sodium metaborate anhydrous	2.71%
Phenylmercuryl acetate	0.37%
NET INGREDIENT	74.14%
TOTAL	100.00%

CONTAINS METHANOL

KEEP OUT OF REACH OF CHILDREN

DANGER  **POISON**

Methanol may cause blindness, harmful or fatal if swallowed, vapor harmful. Avoid breathing spray mist or vapors. Avoid contact with skin.

STATEMENT OF PRACTICAL TREATMENT

If swallowed, drink promptly a large quantity of milk, egg white, gelatin solution if these are not available. Drink tepid glasses of water and induce vomiting. Avoid alcohol and fatty foods.

If inhaled, immediately flush with a large quantity of water for at least 15 minutes and seek medical attention. If in contact with water, remove and wash contaminated clothing before reuse.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

MANUFACTURED BY
CHAPMAN CHEMICAL COMPANY
MEMPHIS, TENNESSEE
38109

A KemaNobel Company

When manually mixing a batch of PERMATOX 102 solution, it is best to add part of the water to the mixing tank, then add the measured quantity of PERMATOX 102 and follow with the balance of the water, rinsing out the measuring container into the mixing tank at the same time. Delayed treatment may allow mold to develop, so lumber should be treated within 24 hours of cutting by a dip or spray application of PERMATOX 102. Freshly treated lumber should be protected from rain. Dipping tanks should also be protected from over dilution by rain and sawdust should be raked out daily.

Approved stacking practices should be employed with adequate space between boards and stacks. Green lumber or infected wood should not be used for stickers. The bottom of the stacks should be well above the ground with weeds and debris kept away from stacks.

TREATMENT

Use 1 gallon of PERMATOX 102 per 100 gallons of water as a 15 second dip for lumber 2 inches or less in thickness.

Use 2 gallons of PERMATOX 102 per 100 gallons of water for thicker stock under severe conditions or when applying as a spray.

Use 3 gallons of PERMATOX 102 per 100 gallons of water as a dip when lumber is to be bulk piled.

WARRANTY STATEMENT

Neither Chapman Chemical Company nor the seller makes any representation or warranty, expressed or implied, concerning this material other than indicated on the label. Neither shall be held responsible in any manner for any personal injury, property damage or other type of loss resulting from the improper handling, storage or use of this material. The buyer accepts and uses the material at his own risk.

EPA Est. No. 1022-TN-1
EPA Reg. No. 1022-521

