

POL-NU CuRAP 20

WOOD PRESERVATIVE PASTE EFFECTIVE GROUNDLINE TREATMENT FOR CONTROL OF DECAY AND INSECTS FOR COMMERCIAL APPLICATOR USE ONLY For Sale Only In 50 Pound Or Greater Containers

INGREDIENTS:

ACTIVE INGREDIENTS

Copper naphthenate 18.16%*

Borax
(sodium tetraborate decahydrate) . . . 40.00%

INERT INGREDIENTS 41.84%

TOTAL 100.00%

*Equivalent to 2% metallic copper.

Keep Out of Reach of Children

DANGER

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Hold eyelids open and flush with a steady, gentle stream of water for 15 minutes.

IF ON SKIN: Wash thoroughly with plenty of soap and water. Get medical attention.

IF SWALLOWED: Call a physician or poison control center. Drink promptly a large quantity of milk, egg white, gelatin solution, or if these are not available, large quantities of water. Avoid alcohol.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate use of gastric lavage.

See right panel for additional precautions.

EPA Reg. No. 1022-536

EPA Est. No. 1022-TN-1

Printed in U.S.A.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its label.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE: Keep away from food or feed in a secure, well-ventilated area protected from extreme temperatures. Do not allow to freeze. Do not transfer to unmarked containers. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or mixtures is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

POL-NU CuRAP 20 is intended for use as a remedial treatment for standing wood utility poles and as a primary or remedial treatment for wooden structures susceptible to attack by decay and soft rot fungi, termites, carpenter ants, or wood boring beetles.

Pol-Nu CuRap 20 may be applied to form a layer 1/16-inch to 3/8-inch thick by brush or trowel or by application to Pol-Nu Paper via the CHAPMAN POL-NU BANDAGE MAKER. Use a trowel to apply Pol-Nu CuRap 20 to deep checks in wood or fill a caulking gun with the preservative and apply liberally.

For utility poles, piling, posts and other wooden structures standing in the ground, excavate the soil away from the structure to a depth of about 18 inches. Wire brush the surface to remove adhering soil and remove any damaged wood. The structure should be inspected for internal decay and insect attack by taking increment borings. If internal damage is found, early replacement or shoring is recommended. Plug bore holes with locust plugs or treated wood plugs.

Bandages may be prepared to cover groundline areas of structures in bands typically 18 to 22 inches in height. Pol-Nu CuRap 20 should be applied to at least cover the wood surface 4 inches below the last evidence of decay and 3 inches above the groundline. More than one bandage may be used in special cases where the structure spans a height greater than 22 inches, such as on hillsides.

Other wooden structures such as sills, headers, joists and other subfloor members, boats, bridge members, and re-aded railroad tie surfaces may be treated with Pol-Nu CuRap 20. Apply by brush, trowel, caulk gun or bandage. Heavier application at points where condensation is likely to occur, where moisture may collect, and where end grain is exposed or butts against concrete or other wood members is recommended.

For control of internal decay in utility poles, drill 3/4 inch holes in each quarter of the pole near the areas of the pole where internal decay protection is required. Do not drill holes nearer than two feet of each other in the vertical direction. These holes should be at a 45 degree angle downward and to a depth equal to or slightly greater than the radius of the pole.

Pack the Pol-Nu CuRap 20 into the holes leaving enough room to insert treated wood plugs into the holes as a cap.

BEST AVAILABLE COPY

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

Corrosive. Causes irreversible eye damage and skin burns. May be fatal if swallowed or absorbed through the skin. Do not get in eyes, on skin, or on clothing. Wash thoroughly with soap and water after skin contact and before eating, drinking, use of tobacco products, or using restrooms.

Applicators must wear gloves impervious to the wood treatment formulation (e.g., polyvinyl chloride (PVC) or neoprene) in all situations where dermal contact is expected (e.g., during the actual application process and when handling freshly treated wood).

Applicators should wear long sleeved shirts, long pants, and an impermeable apron during the application process and all situations where dermal contact is expected. Remove contaminated clothing and wash before reuse. Launder work clothing separately from other household clothing. Dispose of worn-out work clothing and work shoes or boots in any general landfill, in the trash, or in any other manner approved for pesticide disposal.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply directly to water or wetlands. Do not contaminate water when disposing of equipment washwaters.

PHYSICAL AND CHEMICAL HAZARDS

Do not use or store near heat or open flame.

WARRANTY STATEMENT AND DISCLAIMER

Proper application is critical to the effectiveness of this product; however, when applied and used according to this label, Pol-Nu CuRap 20 is capable of protecting structural wood products. The actual life of the treatment will be affected by the condition of the wood when treated, the species of wood, the type of exposure, and the previous and subsequent treatments.

DANGER: READ THE LABEL THOROUGHLY AND COMPLY WITH ALL DIRECTIONS AND WARNINGS GIVEN, AND USE COMMON SENSE IN HANDLING.

CHAPMAN MAKES NO WARRANTIES, EITHER EXPRESS OR IMPLIED, OTHER THAN AS SET FORTH ON THIS LABEL, AND CHAPMAN DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY NOT SPECIFICALLY SET FORTH ON THIS LABEL. CHAPMAN SHALL NOT BE RESPONSIBLE FOR ANY PERSONAL INJURY OR PROPERTY DAMAGE OR OTHER TYPE OF LOSS RESULTING FROM FAILURE TO FOLLOW DIRECTIONS FOR USE, WARNINGS AND PRECAUTIONARY LANGUAGE GIVEN ON THIS LABEL. CHAPMAN SHALL NOT BE RESPONSIBLE FOR DAMAGE TO PROPERTY BEYOND THE PURCHASE PRICE OF THIS PRODUCT; HOWEVER, SOME STATES DO NOT ALLOW THE INCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THIS LIMITATION MAY NOT APPLY TO YOU.

MANUFACTURED BY
CHAPMAN CHEMICAL COMPANY
MEMPHIS, TENNESSEE 38109

1022-536

PM 21