Please read instructions of	nn	<u>rverse before comple</u>	ting form,			Form Apr	OFOVO	. OMB No.	2070-006	O. Approvel expires 2-28-9
o EDA			Inited States					Registra	ation	OPP Identifier Number
SEPA Environmental Protecti								Amend	ment	
Washington, DC 20460			460	²⁰ X Other			Other			
			Applicati	on for F	estici	de - Sec	tion	1		
1. Company/Product Number			2. EPA Product Manager			3. Proposed Classification				
1022-562	·							 	[None Restricted
4. Company/Product (Name)			PM#				ــــــ <i>-</i> - د			
Chap Fume	Ann	licent (loclude 7/P Co			6 F	aditad Bay				FIEDA Caralas 2(a)(0)
5. Name and Address of Applicant (Include ZIP Code) IBC Manufacturing Company			6. Expedited Reveiw. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling							
416 East Broo					to:					
Memphis, TN	3	3109			EPA F	Reg. No				
Check if t	his	is a new address		Product Name						
				Sect	tion - I	li e				
Amendment - Expl	ain	below.			[]			ls in repsons	e to	INTIFICATION
Resubmission in re	apo	onse to Agency letter	dated		_		letter dated o" Application.			
X Notification - Expla	sin t	selow.			Other - Explain below.					MAI 2 0-1777
Explanation: Use addit	· · · ·	el page(s) if pagessar	- /Enc seesie	n I and Sa						
			-			عدال المعادمات	#			ed Ototowant
NOTIFICATION	•	Updated Warr Per PR Notic	-	remenc	∝ up	uateu Ei	IVIL	Officerica.	L nazai	.d Statement
		101 111 110010	33 10							
				Sect	ion - I	1				
1. Material This Product V	Vill	Be Packaged In:								
Child-Resistant Packaging Unit Packaging			Water Soluble Packaging			•	2. Type of Container			
Yes			Yes			Metal				
No No		No			No				Plastic Glass	
Certification must		If "Yes" Unit Packaging wat.	No. per	if "Yes"		No. per		1 [Paper (S	· maaili d
ae submitted		Onit Fackaging Wgt.	contemer	Packag	e wgt	CONTRING		[j Other (S	pectry)
3. Location of Net Content	ts I	nformation	4. Size(s) Re	tail Contain	187	T	5. Lo	cation of Lat	el Directio	ns .
Label	Co	ntainer					<u>. E</u>			
6. Manner in Which Label	is /	iffixed to Product	Lithor	graph glued		Other				
			Stenc	iled						<u> </u>
		· · · · · · · · · · · · · · · · · · ·			on - i\					
1. Contact Point (Comple	te i	ems directly below for	or identification	on of individ	fuel to be	contected, i	f nec	essery, to pr		
Name			Title							
Gail Early					tratio	ons Repr	ese	ntative	901/3	344_5315
l a seifer shae sha ata	***	ents I have made on	Certifica		nanta tha	veto ere telle	9001	vete end oor	nniete	6. Date Application Received
	any	knowlingly false or r								(Stamped)
A 6:				3. Title						•
Milos	1	arly			بالمسموط	ma Dan		n4		
Au.	_				rrac10	ons Repr	ese	ntative		•
4. Typed Name			}	5. Date						
Gail Early			Ì	5-20	-99				,	1 •

NOTIFICATION

Net Contents:

MAY 2 8 1999

CHAP FUME

A FUMIGANT FOR CONTROLLING DECAY AND INSECTS IN WOOD POLES AND WOOD CHIPS

INGREDIENT STATEMENT

ACTIVE INGREDIENT: Sedium Methyldithiocarbamate (AINERT INGREDIENTS:	Anhydrous)	33.0%* 67.0%
TOTAL:		100.0%

^{*}Contains 3.18 lbs. active ingredient per gallon

UN 3006

(Contains Sodium Methyl Dithiocarbamate)

(IMO: Dithiocarbamate Pesticides, Liquid, Toxic, N.O.S., UN 3006)

This product is sold only for uses stated on its label. No expressed or implied license is granted to use or sell this product under any patent in any country except as specified: Country, United States.

EPA Reg. No. 1022-562

EPA Est. No. 1022-TN-1

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT

IF ON SKIN: Immediately flush skin with large amounts of running water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately.

IF IN EYES: immediately flush eyes with large amounts of running water for at least 15 minutes. Hold eyelids apart to ensure rinsing of the entire surface of the eye and lids with water. Get medical attention immediately.

IF INHALED: Remove to fresh air. If not breathing, clear the victim's airway; and start mouth-to-mouth artificial respiration. If breathing is difficult, give oxygen, preferably with a physician's advice. Get medical attention immediately.

IF SWALLOWED: Immediately give several glasses of water, but do not induce vomiting. If vomiting does occur, give flags again. Have a physician determine if condition of patient will permit induction of vomiting or evacuation of stomagn. Do not give anything by mouth to an unconscious or convulsing person.

See Back Panel for Additional Precautionary Statements

IBC Manufacturing Company 416 East Brooks Road P.O. Box 9158 Memphis, TN 38109-0158

PRODUCT INFORMATION

CHAP FUME is a fumigant solution. When used as directed, it will arrest internal decay and control insects present in Douglas Fir, Western Red Cedar and Southern Pine. During the sterilization of the treated area, a fungitoxic residue is deposited in the cells of the wood. This residue is effective for an indefinite period. Poles known to have internal decay should be scheduled for treatment before they have decayed to the point where replacement is necessary.

USE PRECAUTIONS

READ ALL LABEL DIRECTIONS BEFORE USING. Apply this product only as specified on this label. Keep children and pets out of treated area. Keep off desirable lawns and plants. Wash contaminated hands, skin, eyes or clothing immediately upon exposure to chemical and always before eating or smoking. Use respirators, waterproof protective gloves and footwear when appropriate and required. Keep container tightly closed when not in use. Do not store near feed or food.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

Corrosive, causes skin damage. Do not get in eyes, on skin, or on clothing. May be fatal if swallowed or absorbed through skin. Prolonged contact may cause severe skin irritation. Do not breathe vapor or spray mist. Use waterproof gloves, safety goggles or face shield, and protective clothing when handling. Wash hands, arms and face thoroughly with soap after handling and before eating or smoking. Wash clothing and shoes before reuse. Do not apply to food or forage. Do not apply this product in such a manner as to directly or through drift expose workers or other persons. The area being treated must be vacated by unprotected persons. When applying in enclosed areas, wear a mask or respirator of a type passed by the U.S. Bureau of Mines for Metam-Sodium protection.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and other wildlife. For terrestrial uses, do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not apply when weather conditions favor drift from areas treated. Do not contaminate water by cleaning of equipment or disposal of equipment washwaters. Apply this product only as specified on this label. In case of emergency--immediately call Chemtrec at 1-800-424-9300.

DO NOT discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. DO NOT discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the Environmental Protection Agency.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

POLES

Groundline Treatment: When a pole is detected with rot or insect damage, dig the soil away from the base of the pole to a depth of 12 inches. Drill 3/4 to 7/8 inch diameter holes in each quarter of the pole at groundline and one 3/4 to 7/8 inch hole two feet above the groundline, preferably above the decay pocket. These holes should be drilled at a 45 to 65 degree downward angle. Use the Rate Table to determine the number and length of holes to hold the prescribed amount of CHAP FUME. Avoid drilling across seasoning checks and knots that will cause leakage.

Plug all holes with treated wood plugs that are 1/16 inch larger in diameter than the hole. Wear impermeable waterproof protective gloves and safety goggles or face shield to avoid splashing any of the liquid CHAP FUME on the skin or into the eyes.

When the CHAP FUME treatment is for the control of insects, the pole should be wrapped over the treated area with 48 inch laminated kraft paper. Staple and seal the seam and top edge with 1-inch masking tape. NO WRAPPING IS NECESSARY WHEN CONTROLLING DECAY IN POLES. Backfill and tamp the excavated area to form a seal against the kraft paper.

Above Groundline Treatment to Control Decay: Drill 3/4 to 7/8 inch holes in a spiral pattern up the pole starting at groundline. Avoid drilling across seasoning checks and knots that will cause leakage. The holes should be drilled at a 45 to 65 degree downward angle. Space holes at least 6 inch to 1 foot vertically from each other. Use the Rate Table to determine the number and length of holes to hold the prescribed amount of CHAP FUME. If rot pocket is intersected by drilling, attempt to drill holes in sound wood above and below the pocket.

In areas of the pole above the groundline that are susceptible to internal decay, drill two 3/4 to 7/8 inch diameter holes 90 degrees apart and avoid seasoning checks. Holes should be one foot apart vertically.

Before applying CHAP FUME assure that no one is below you. Pour CHAP FUME into the holes slowly, watching for leakage. If leakage occurs, stop pouring chemical, plug the hole and drill a replacement hole observing the one foot vertical spacing between holes. Plug all holes with treated wood plugs 1/16 inch larger in diameter than the hole.

	POLE APPLICATION	RATE TABLE	
Approximate	Diameter	Length	Number
Pints Per Pole	of Hole	of Hole	of
CHAP FUME	(inches)	(inches)*	Holes**
	3/4"	10"	6
3/4 Pint	"	12"	5
(poles with less	7/8"	8"	6
than 30" circumference)	"	9"	5
		11"	4
1.0 Pint	3/4"	13"	6
(poles 30" to 45"	7/8"	10"	6
in Circumference)	"	12"	5
2.0 Pints			
(poles greater than	7/8"	18"	6
45" in circumference)	1		

*Effective length is 2.0 inches less than shown to allow for sealing plug.

**CHAP FUME should be evenly divided among the holes drilled in the pole.

Note: Care should be taken not to drill through the circumference of the pole.

WOOD CHIPS

CHAP FUME reduces wood fiber degradation and helps retain brightness in softwood and hardwood chips by controlling cellulose degrading bacteria and fungi. Tall oil and turpentine losses are greatly reduced because temperatures in the wood chip storage piles are held to near ambient levels for up to 30 days. CHAP FUME is a water soluble liquid. Use promptly after mixing with recommended amount of water. Do not allow solution to stand. Flush all equipment with water after use. Disassemble valves and clean carefully. Allow at least 4 weeks between treatment and processing of chips.

Soaking Method - Soak chips in 0.3% to 0.8% CHAP FUME/water solution for 15 seconds in sufficient quantity to completely cover the chips. Approximately 72 gallons of solution will be needed for each ton of oven dry wood chips. Runoff should be recycled to soaking tank after filtering. Replenish CHAP FUME solution as needed using original dilution rate.

Spraying Method - Soak chips in 0.3% to 0.8% **CHAP FUME**/water solution uniformly on each ton of oven dry wood in fresh chips using a minimum of 40 gallons of solution per ton. Use sufficient number of nozzles for adequate coverage. Recycle runoff after filtering.

Amount of CHA	P FUME Needed for	Desired Solution*
Gallons of Water	0.3%	0.8%
40	0.48 qt. (15.4 fl. oz.)	1.28 qt. (41.0 fl. oz.)
72	0.86 qt. (27. 6 fl. oz.)	2.30 qt. (73.7 fl. oz.)

*Use the higher concentration if chips are dirty or to be stored for more than three months.

STORAGE AND DISPOSAL

PROHIBITIONS: Do not contaminate water, food, or feed by storage or disposal.

STORAGE: DO NOT STORE BELOW 0 degrees F. Product crystallizes at lower temperature. Warm or store at higher temperatures and mix to redissolve crystals and assure uniformity before use.

PESTICIDES DISPOSAL: Rinsate from the containers may be applied around the bottom of the pole. Care should be taken to prevent contamination of water and desirable vegetation. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the ;nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by incineration, or if allowed by state and local authorities by burning. If burned, stay out of smoke.

WARRANTY AND LIMITATION OF DAMAGES

Seller warrants to those persons lawfully acquiring title to this product that at the time of the first sale of this product by seller that this product conformed to its chemical description and was reasonably fit for the purposes stated on the label when used in accordance with Seller's directions under normal conditions of use and Buyers and users of this product assume the risk or any use contrary to such directions. SELLER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS OR OF MERCHANTABILITY, AND NO AGENT OF SELLER IS AUTHORIZED TO DO SO. In no event shall Seller's liability for any breach of warranty exceed the purchase price of the material as to which a claim is made.

Buyers and users of this product are responsible for all loss or damage from use or handling of this product which results from conditions beyond the control of Seller, including, but not limited to, incompatibility with other products unless otherwise expressly provided in the Directions for Use of this product, weather conditions, moisture conditions or other environmental conditions outside the ranges that are generally recognized as being conducive to good industrial and/or application practices.