



Reg # 1022-571 PM-22

BEST AVAILABLE COPY

181

AC...  
11 2 1991  
CHAPCO  
FUNGICIDE 1022-571

DIRECTIONS FOR USE (Continued)

Ground contact: Seasoned or green wood may be treated. Make certain the wood is free of bark, then immerse in Chapco Cu-Map 400 for 12 to 48 hours or until the sapwood is completely penetrated.

Water repellents may be admixed with Chapco Cu-Map 400 to improve dimensional stability of the treated wood. Colorants may be admixed for aesthetics and additional u v protection. This product is compatible and may be colored by the universal machine colorants employed to color oil or water based paints. Note that colorants weather differently, and that color develops it varies with species, grain and wood texture.

Net Contents: 35 gallon 5 gallon

PRECAUTIONARY STATEMENTS  
Hazards to Humans & Domestic Animals  
WARNING  
Harmful if swallowed, inhaled, or absorbed through the skin. Avoid contact with skin, eyes, or clothing. Avoid breathing vapor or spray mist. Wash thoroughly with soap and water after handling. Contaminated clothing should be removed and washed thoroughly before reusing. Use in a well-ventilated area.  
PHYSICAL & CHEMICAL HAZARDS  
Harmful if swallowed. Keep out of reach of children. Do not use, pour, spill, or store near heat or open flame.  
ENVIRONMENTAL HAZARDS  
Do not contaminate water by cleaning of equipment or disposal of waste

CHAPCO CU-NAP 400

END USE PRODUCT

INGREDIENT STATEMENT:

Active Ingredient: Copper Naphthenate 40%  
Inert Ingredients: 60%  
Total 100%

\*Equivalent to 4% metallic copper.

RECOMMENDED FOR

Porches, siding, shingles, trellises, steps, sub-flooring, furniture, fence pickets, and rails, furring strips, arbors, and flooring. Powder post beetles which invade furniture, flooring and structural lumber are killed by application of this preservative. These insects will not attack the treated wood. Wood rot protection of interior use wood is only needed on wood which is subject to frequent or prolonged wetting (e.g., condensation, rain seepage).

Chapco Cu-Map 400 may also be used on fence posts, poles, foundation sills, decks, boats and all wood exposed to moisture or weather.

Due to its very low phytotoxicity, Chapco Cu-Map 400 can be used to treat wood for greenhouses, nursery flats, etc.

In addition to preventing decay, blue stain, and insect attack on wood, Chapco Cu-Map 400 controls warping, swelling, shrinking and end checking caused by changes in moisture content of lumber and plywood products.

Wood to be protected against subterranean termites should be treated before use in construction. Termites will not attack wood treated with Chapco Cu-Map 400 wood preservative.

Chapco Cu-Map 400 may be used where livestock and dairy animals may come in contact with the treated wood. Wood treated with Chapco Cu-Map 400 should not be used where it may come in contact with food, feed or potable water.

KEEP OUT OF REACH OF CHILDREN  
WARNING  
STATEMENT OF PRACTICAL TREATMENT  
IF IN EYES: Immediately flush with large quantity of water and get medical attention.  
IF ON SKIN: Flush with water. Remove and wash contaminated clothing before re-use.  
IF SWALLOWED: Do not induce vomiting. CALL A DOCTOR.  
SEE RIGHT PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Chapco Cu-Map 400 is a concentrate and requires dilution with water or oil before use. To treat wood for use in moderate decay hazard locations, dilute one volume of Chapco Cu-Map 400 with three volumes of water. To treat wood for use in high decay hazard locations, such as ground contact, dilute one volume of Chapco Cu-Map 400 with one volume of water.

To treat wood to meet ANPA requirements, mix one volume Chapco Cu-Map 400 with from two to six volumes of fuel oil. Adjust the copper content of the treating solution by adding Chapco Cu-Map 400 or fuel oil in order to achieve the desired copper retention.

Above ground contact: The best results will be obtained if wood to be treated is immersed for three minutes or longer. If dipping is not possible, two liberal brush or spray applications should be applied. Allow at least one hour between applications. Make certain all areas are fully treated to get the maximum benefits.

STORAGE & DISPOSAL  
PROHIBITIONS:  
Do not contaminate water, food or feed by storage or disposal. Even dumping is prohibited.  
PESTICIDE DISPOSAL:  
Pesticide, spray mixture or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State, or local authorities.  
CONTAINER DISPOSAL:  
Triple rinse (or equivalent). Then offer for recycling and reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by State and local authorities.  
GENERAL:  
Consult Federal, State, or local disposal authorities for approved alternative procedures.

WARRANTY STATEMENT AND DISCLAIMER

Proper application is critical to the effectiveness of the product; however, when applied and used according to this label, this product is capable of protecting wood for uses described. The actual life of the treatment will be affected by the condition of the wood when treated, the species of wood, the type of exposure, and the previous and subsequent treatments.

READ THE LABEL THOROUGHLY AND COMPLY WITH ALL DIRECTIONS AND WARNINGS GIVEN, AND USE COMMON SENSE IN HANDLING.

CHAPMAN MAKES NO WARRANTIES, EITHER EXPRESS OR IMPLIED, OTHER THAN AS SET FORTH ON THIS LABEL, AND CHAPMAN DISCLAIMS ANY IMPLIED WARRANTY OR MERCHANTABILITY NOT SPECIFICALLY SET FORTH ON THIS LABEL. CHAPMAN SHALL NOT BE RESPONSIBLE FOR ANY PERSONAL INJURY OR PROPERTY DAMAGE OR OTHER TYPE OF LOSS RESULTING FROM FAILURE TO FOLLOW DIRECTIONS FOR USE, WARNINGS AND PRECAUTIONARY LANGUAGE GIVEN ON THIS LABEL. CHAPMAN SHALL NOT BE RESPONSIBLE FOR DAMAGE TO PROPERTY BEYOND THE PURCHASE PRICE OF THIS PRODUCT; HOWEVER, SOME STATES DO NOT ALLOW THE INCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THIS LIMITATION MAY NOT APPLY TO YOU.

MANUFACTURED BY  
CHAPMAN CHEMICAL COMPANY  
MEMPHIS, TENNESSEE 38109