

U.S. I 'IRONMENTAL PROTECTION **AGENCY**

Office of Pesticide Programs Antimicrobials Division (7510P)

1200 Pennsylvania Avenue NW Washington, D.C. 20460

NOTICE OF PESTICIDE:

x Registration

__ Reregistration

A Reg. Number:

Date of Issuance:

2008

1022-590

December 29,

Term of Issuance:

Unconditional

Name of Pesticide Product:

WOODGUARD® NC

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

IBC Manufacturing Company 416 Brooks Road Memphis, TN 38109

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product [OPP Decision Number: D-392159] is unconditionally registered in accordance with FIFRA sec 3(c)(5) provided that you:

- 1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for re-registration of your product under FIFRA section 4.
- 2. Make the following labeling changes listed below before you release the product for Shipment:
 - a. Revise the "EPA Registration Number to read, "1022-590".

Signature of Approving Official:

Date:

Adam Heyward

Product Manager 34

Regulatory Management Branch II

Antimicrobials Division (7510P)

December 29, 2008

EPA Form 8570-6

b. Revise the precautionary statement to read as follows:

"Causes moderate eye irritation. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Remove and wash contaminated clothing before reuse."

c. Revise the first Aid statement to read as follows:

IF IN EYES:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing.
- Call a poison control center or doctor for treatment advice.

IF ON SKIN OR CLOTHING:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call poison control center or doctor for treatment advice.

IF SWALLOWED:

- Immediately call a poison control center or doctor.
- Do not give any liquid to the person.
- Do not give anything by mouth to an unconscious person.

<u>Note to Physicians</u>: Contains petroleum distillate. Vomiting may cause aspiration pneumonia.

Have the product container or label with you when calling a poison control center or doctor or going for treatment. For emergency information, call the National Pesticides Information Center at 1-800-858-7378, 6:30 AM to 4:30 PM Pacific time (PT), seven days a week. During other times, call the poison control center 1-800-222-1222.

d. Revise the environmental hazards statement to read as follows:

This pesticide is toxic to fish. DO NOT discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. DO NOT discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the Environmental Protection Agency.

e. Add the following PPE languages to the label:

Personal Protective Equipment (PPE):

Applicators and other handlers must wear: Long sleeved shirt and long pants a Shoes plus socks For Cleaning Equipment: Chemical—resistant apron

3/

User Safety Requirements:

Follow manufacturer's instructions for cleaning / maintaining PPE. If no such instructions exist for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

User Safety Recommendations:

- -Users should wash hands before eating, drinking, chewing gum, using tobacco or using the toilet.
- -Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.
- -User should remove personal protective equipment immediately after handling this product. Wash outside of gloves before removing. As soon as possible, wash thoroughly.
- f. Add the following statement immediately below the Storage and Disposal statement heading: "Do not contaminate water, food or feed by storage or disposal."
- 3. Submit three (3) copies of your final printed labeling before distributing or selling the product bearing the revised labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records. Note that the Agency is moving away from review of paper submitted registration applications to electronic review of applications. Therefore, we need your help to make this an efficient and convenient process for both you and the Antimicrobials Division. Accordingly, we are asking you to submit future labeling amendments for this product via the electronic labeling process. Refer to the following website for guidance on electronic submissions, including label:

http://www.epa.gov/oppfead1/eds/esr_guidance.htm#overallsub. If you have questions concerning electronic labeling, a list of contacts is available at the following site: http://www.epa.gov/oppfead1/eds/edsgoals.htm#contacts.

Sincerely,

Adam Heyward

Product Manager 34

Regulatory Management Branch II Antimicrobials Division (7510P)

Enclosure: (Stamped Label)

WOODGUARD® NC

EXTERIOR WOOD PRESERVATIVE AND FINISH OIL BASED WOOD PRESERVATIVE

CONTROLS SURFACE MOLD, DECAY & MILDEW

with COMMENTS EPA Letter Dated:

DEC 29 2008

MEETS VOC STANDARDS

LOG HOMES . SHINGLES AND SHAKES . SIDING . FENCES Function and Rodenticide Act as

EXCEPTIONAL WATER REPELLENCY

Under the Federal Insecticide, anended, for the pesticide, registered under EPA Reg. No.

THE SUPERIOR DEEP PENETRATING TREATMENT

IDEALLY SUITED FOR LOG HOMES, ROOFS, SIDING, AND FENCES ESPECIALLY ROUGH SAWN LUMBER OLD WEATHERED WOOD NEW POROUS WOODS

Test before using on smooth dense wood. Do not use on painted surfaces. WOODGUARD® NC must penetrate to be effective Wood must be dry before application (less than 18% moisture)

This product exceeds NWWDA and Fed. Spec. TT-W-572 Water Repellency requirements by 400%.

INGREDIENTS:

Active Ingredients:

3-lodo-2-Propynyl Butyl Carbamate 0.450%

Propiconazole:1-[[2-(2,4-dichlorophenyl)-4-propyl-1,

3-dioxolan-2-yl]-methyl]-1H-1,2,4-triazole 0.125% Other Ingredients 99.425%

TOTAL 100.000%

This product contains Petroleum Distillates

EPA Reg. No. 1022-EPA Est. No. 1022-TN-001

KEEP OUT OF REACH OF CHILDREN

CAUTION

See side panel for additional precautionary statements



HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION

Causes moderate eye irritation. Avoid contact with eyes, skin and clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet.

	FIRST AID
IF IN EYES:	 Hold eye open and rinse slowly and gently with water for 15 – 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advice.
IF ON SKIN OR CLOTHING:	
In case of emergency, call Chemtrec toll free at 800-424-9300. Have the product container or label with you when calling a poison control center or doctor or going for treatment.	

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to water. Do not contaminate water when disposing of equipment washwaters or rinsate.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

Pesticide Storage

Store in a secure, well-ventilated area protected from extreme temperatures. Do not transfer to unmarked containers. Keep container closed when not in use.

Pesticide Disposal and Container Handling

Nonrefillable container. Do not reuse or refill this container.

If Empty: Place in trash or offer for recycling if available.

If Partially Filled: Call your local solid waste agency or 1-800-CLEANUP for disposal instructions. Never place unused product down any indoor or outdoor drain.

WOODGUARD NC is an oil-based, transparent preservative designed for log homes, wood shingle roofs, siding, and fences. WOODGUARD NC's oil formula provides long-term protection by penetrating deeply into the wood. It achieves maximum performance on rough sawn lumber, old weathered wood and new porous wood where maximum penetration results in exceptional water repellency on sloping roofs and vertical surfaces; horizontal surfaces are normally subjected to more severe weathering and will usually require earlier retreatment. In harsh exposures involving standing water, retreatment may be required annually to maintain water repellency.

Surfaces previously treated with a semi-transparent stain (non-film forming) may be satisfactorily recoated with WOODGUARD NC when a superior, water repellent wood preservative is desired. If WOODGUARD NC is applied to non-porous or film-covered surfaces which prevent or significantly retard penetration, reduced performance or even complete failure can result. Test first if in doubt.

See the WOODGUARD NC Preparation and Application Guide for guidelines on preparation of the wood surface for WOODGUARD NC application.
WOODGUARD NC combines mold and decay control with unique and EXCEPTIONAL WATER REPELLENCY THAT WITHSTANDS OUTDOOR VERTICAL WEATHERING, ESPECIALLY ON OLD, CRACKED WEATHERED WOOD. WOODGUARD NC IS TOXIC TO TERMITES AND ANOBIID POWDERPOST BEETLES.

WOODGUARD NC cannot chip, crack or peel. When applied as directed, it leaves a uniform, streak-free appearance.

WOODGUARD NC CONTAINS NO COPPER-CONTAINING INGREDIENTS.

WOODGUARD NC protects and extends service life by inhibiting mold and decay, as well as cupping and warping. A single coat application is recommended every 2 to 4 years on vertical surfaces. Always apply to the point of refusal. Double coat applications are not needed or recommended. WOODGUARD NC cleans up with water and detergent at time of application — provided it has not soaked into the surface. Cured WOODGUARD NC will clean up with paint thinner or mineral spirits.

WOODGUARD NC (clear) temporarily darkens wood color which later greys after weathering. Use pigmented WOODGUARD NC to help hide this greyed effect.

DIRECTIONS FOR USE

It is a violation of Federal Law to use WOODGUARD NC in a manner inconsistent with its labeling.

10/08

Apply liberally to log buildings, roof, wood siding, or fence by simply wetting down the surface as follows:

Spray – Do not use airless spray equipment. Use a garden-type, pump-up sprayer with adjustable nozzle. Set nozzle to deliver a low pressure, coarse spray and backbrush as necessary.

Brush – A regular paint brush is fine for most surfaces. For uneven shingle or rough surfaces, use a stiff bristle brush. Apply evenly, brushing out sags, etc. as necessary.

Roller - Use a long nap for rough surfaces.

ONE COAT IS SUFFICIENT. Surface must be clean and free of all loose debris. Apply to dry wood for maximum penetration and fastest drying. Wood must be dry before application (less than 18% moisture).

Avoid contact with plants, shrubs and trees. NOTE:

- 1. Stir or shake well before use.
- 2. WOODGUARD NC goes on "dark" but lightens considerably during the curing period.
- 3. Cure time will range from 3 days to 2 weeks, depending on temperature and wood porosity.
- 4. Coverage: 150 to 300 sq. ft. per gallon, depending on surface condition and wood porosity. Always apply to the point of refusal.

- 8/9
- 5. Application temperature: Do not apply if the overnight low temperature is below 50 °F/10 °C or the daytime high temperature is above 95 °F/35 °C. At 50-55 °F, dilute with mineral spirits or turpentine one pint to one gallon of WOODGUARD NC. The hotter the weather, the faster the drying. Below 65 °F, WOODGUARD NC may become too viscous to spray, but easily spreads by brush down to 50 °F.
- WOODGUARD NC softens asphalt (including asphalt shingles) avoid contact.
- 7. Do not apply if rain is expected within 36 hours.
- 8. WOODGUARD NC provides an immediate water repellent barrier; however, its ability to bead water develops as it cures. Re-treat when the surface exhibits signs of losing capability to inhibit water penetration.
- Avoid open flame during application and until WOODGUARD NC has soaked in completely.
- 10. Subsequent painting WOODGUARD NC provides such strong properties of water repellency that subsequent applications of paint will not adhere as long as the WOODGUARD NC barrier remains intact. If in doubt, test first. If a gloss or semi-gloss finish is desired, apply WOODGUARD TC™. Contact www.WOODGUARD.com or your WOODGUARD NC dealer for details.
- 11. WOODGUARD NC protection will not withstand repeated contact with chlorine or chlorinated water. Avoid using on wood in contact with this chemical, or retreat as necessary.
- 12. Until WOODGUARD NC has thoroughly cured, treated surface may be slippery. WOODGUARD NC in its clear, untinted form is effective on many wood products greenhouse items, fruit and vegetable boxes, and other farm uses, especially wood surfaces in close proximity with animals, feedstuffs and the like:

TINTING INSTRUCTIONS

WOODGUARD NC is compatible with and may be colored by the addition of small quantities of the Universal Machine Colorants employed to color oil or water based paints. It is important to note that different colorants weather differently, and that color development varies with wood species, wood grain and wood undertone.

Consult your dealer for assistance in tinting WOODGUARD NC. WOODGUARD NC is a transparent preservative oil finish that can be tinted to a light stain; do not attempt to obtain a heavy or solid color stain by overloading with pigment.

Approved formulas are available from your dealer or at www.WOODGUARD NC.com.

Stir tinted WOODGUARD NC frequently when applying to keep pigments evenly dispersed and uniform. Coat surfaces evenly. Smooth sags or runs by feathering with a brush or cloth in order to achieve a uniform appearance.

WARRANTY AND LIMITATION OF DAMAGES

Seller warrants to those persons lawfully acquiring title to this product that at the time of the first sale of this product by seller this product conformed to its chemical description and that it was reasonably fit for the purposes stated on the product label when used both in accordance with the Direction for Use appearing on the product label and under normal conditions of use. Buyers and users of this product assume the risk of all loss or damage from use or handling of this product that results from their failure to read and comply with the Directions for Use of this product which appear on the product label. SELLER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING ANY OTHER **EXPRESS** OR **IMPLIED** WARRANTY OF **FITNESS** OR MERCHANTABILITY, AND NO AGENT OF SELLER IS AUTHORIZED TO DO SO. Unless expressly prohibited by state law, the liability of seller for any breach of warranty shall not exceed the purchase price of the product as to which a claim is made.

Manufactured by:

IBC Manufacturing Company 416 East Brooks Road Memphis, TN 38109

[®]WOODGUARD is a registered trademark of IBC Manufacturing Company.

TMWOODGUARD TC is a trademark of IBC Manufacturing Company.