WTM 30

cifth CC. ANTE

MAR U 1003

100 - 2014 Paris 140 160 1239 - 46

ACTIVE II	NGREDIENT:
-----------	------------

50.0 %

INERT INGREDIENT

50.0_%

This product contains 4.68 lb. of active ingredient per gallon and weighs 9.35 lb. per gallon.

KEEP OUT OF REACH OF CHILDREN

CAUTION

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

FIRST AID: If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

ENVIRONMENTAL HAZARDS: This pessicide is toxic to fish. Keep out of lakes, streams, or ponds. Permits may be required for discharges containing this pesticide into lakes, streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Agency.

GENERAL CLASSIFICATION

It is a violation of Federal law consistent with its labeling.	to use this product in a manner is
trest 30	is used to control along thactor

and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of1.1 to2.7 fluid ounces of WTM_30	WTM 30	is used to control algae, bacteria
in the system, is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 0.25 to 2.71 fluid ounces of WTM 30 per 1000 gallons of water (2.4 to 24 parts per million of WTM 30 lshould be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers. WTM 30 is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 4.1 to 6.83 fluid ounces of WTM 30 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 2.77 to 6.83 fluid ounces of WTM 30 per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water	and fungi in recirculating commercial its use, systems must be cleaned to and other deposits. An initial slug at	l and industrial water cooling towers. Prior to remove algal growth, microbiological slime difficult of 1.1 to 2.7 fluid ounces
Subsequent slug additions of 0.25 to 2.71 fluid ounces of WTM 30 per 1000 gallons of water (2.4 to 24 parts per million of WTM 30 should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers. WTM 30 is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 4.1 to 6.83 fluid ounces of WTM 30 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 2.77 to 6.83 fluid ounces of WTM 30 per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water		
be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers. WTM 30 is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 4.1 to 6.83 fluid ounces of WTM 30 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 2.77 to 6.83 fluid ounces of WTM 30 per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water	Subsequent slug additions of	0.25 to 2.71 fluid ounces of
be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers. WTM 30 is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 4.1 to 6.83 fluid ounces of WTM 30 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 2.77 to 6.83 fluid ounces of WTM 30 per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water	to 24 parts per million of	WTM 30) should
lem. Slug additions should be made in the sump of water cooling towers. WTM 30 is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 4.1 to 6.83 fluid ounces of WTM 30 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 2.77 to 6.83 fluid ounces of WTM 30 per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water	be employed every 2 to 5 days, or as	needed. The frequency of addition depends
wth 30 is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 4.1 to 6.83 fluid ounces of wth 30 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 2.77 to 6.83 fluid ounces of wth 30 per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water		
air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 4.1 to 6.83 fluid ounces of WTM 30 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 2.77 to 6.83 fluid ounces of WTM 30 per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water		
mended. Repeat initial dosage until control is evident. Subsequent slug additions of 2.77 to 6.83 fluid ounces of WTM 30 per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water	air-washing systems that maintain e to its use, systems should be cle deposits. An initial slug dose of	effective mist eliminating components. Prior aned to remove bacterial slime and other 4.1 to 6.83 fluid ounces of
per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water	mended, Repeat initial dosage until d	control is evident. Subsequent slug additions
	per 1000 gallons of water should be e frequency of addition depends upon of the bacterial problem. Slug addition	employed each 1 to 5 days, or as needed. The the relative amount of bleedoff and severity ons may be made to the sump or to the water

STORAGE & DISPOSAL: Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal or cleaning of equipment. Rinsate that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open dumping is prohibited.

U	METAL CONTAINERS: Triple
	rinse and offer for recycling,
	reconditioning, or disposal in an
	approved landfill or bury in a safe
	place.

\Box	PLASTIC CONTAINERS: Do not
	reuse empty container. Triple rinse
	and incinerate or dispose of in an
	approved landfill or bury in safe
	place.

	Manufactured by: Industrial Chemical Labs, Inc.
	1015 North 14 Street
	Omaha, NE 68102
EPA REG. NO.	EPA EST. NO
	NET CONTENTS

U.S. ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (HH-567) WASHINGTON, D.C. 20460	EPA REGISTRATION NO.	WAL O 1983		
	TERM OF ISSUANCE	1 111/11/11/11/11		
NOTICE OF PESTICIDE: PRESISTRATION	NAME OF PESTICIDE PRODUCT			
(Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)				
NAME AND ADDRESS OF REGISTRANT (Include ZIP code)	.1			
_				
	-7			
t t				
L	J			
NOTE: Changes in labeling formula differing in substance from submitted to and accepted by the Registration Division prior product always refer to the above U.S. EPA registration numbers.	to use of the label in commerce.			
On the basis of information furnished by the registrant, the a the Federal Insecticide, Fungicide, and Rodenticide Act.	bove named pesticide is hereby	Registered/Reregistered under		
A copy of the labeling accepted in connection with this Reg	istration/Reregistration is return	ed herewith.		
Registration is in no way to be construed as an indorsement	or approval of this product by th	is Agency. In order to protect		
health and the environment, the Administrator, on his motion	, may at any time suspend or car	icel the registration of a pest-		
icide in accordance with the Act. The acceptance of any nar Act is not to be construed as giving the registrant a right to	_	•		
by others.				
Pide process of a middle soliter of the state of the soliter of th	control of the second control of	· • · / // / @*C •		
The state of the state of the state of	and the property of the second	,		
af it was to make and the first of 100 to 100 to		* * *		
gradus entre som to the first of the state of the south				
o, the combinate type present the	and the second second	Company that man		
and the second of the second o		- N. G		
the State transfer (the project of the second		_		
i de la jaro de la composició de la construcció de la composició de la com				
A Company of the control of the cont				
contrades to annually of the in the appropriation of the first many field. They are the				
atomic of the many that appropriate and the second of the parties of the second				
to compare of the light to ending of Tentrolle will be and a.				
	a .			
for all				
See True	nx (120)			
in the state of th				
promotion in the residence of the 1957				
Phase Services				
Alternative Charles				
ATTACHMENT IS APPLICABLE				

EFA Form \$570-6 (Rev. 5-76)

SIGNATURE OF APPROVING OFFICIAL

PREVIOUS EDITION MAY BE USED UNTIL SUPPLY IS EXHAUSYED.

DATE