SUPPLEMENTAL LABELING


OLIN HTH (R) DRY CHLORINATOR TABLETS

Active Ingredients:

1

EPA Reg. No. 1258-969





DIRECTIONS FOR SPA AND HOT TUB USE: It is a violation of federal law to use the product in a manner inconsistent with its labeling. Two tablets (½ oz.) of product will provide approximately 5 ppm available chlorine in 500 gallons of water.

Using an appropriate test kit and adjust the water to the following values: pH 7.2 - 7.8; total alkalinity 60 - 125 ppm; calcium hardness 200 - 1,000 ppm. Maintain these conditions for proper spa and hot tub operation by frequent testing with the test kit. The spa or hot tub can be stabilized by adding enough cyanuric acid to give a level of 20 - 60 ppm. It is recommended that the water be drained every 30 - 90 days, more often under heavy use. Consult manufacturers' recommendations concerning the compatibility of chlorine sanitizers with their equipment. Some oils, lotions, fragrances, cleaners, etc., may cause foaming or cloudy water and may react with chlorine sanitizers to reduce their efficiency.

START-UP (FRESHLY FILLED): (1) Turn on the circulation system and ensure that it is operating properly. (2) Place tablets in a skimmer, dissolving basket, or other appropriate continuous feeder or dissolving device. Check the free available chlorine (FAC). Spa or hot tub should not be entered until FAC reaches 4 - 5 ppm.

REGULAR USE: (1) Test for FAC to assure 4-5 ppm. (2) After each use, shock treat with 3 tablespoons (1.5 ozs.) SOCK-IT^(R) per 500 gallons to control odor and algae. Repeat as needed. Spa or hot tub should not be entered until FAC reaches 4-5 ppm.

EXTENDED NON-USE PERIOD: During extended periods when the spa or hot tub is not being used, maintain 1 - 3 ppm FAC.

KEEP OUT OF REACH OF CHILDREN

DANGER!

SEE PRINCIPAL LABEL FOR COMPLETE PRECAUTIONARY INFORMATION AND STORAGE AND HANDLING INSTRUCTIONS

All applicable directions, restrictions, and precautions on the EPA principle registered label are to be followed.

OLIN CHEMICALS

Consumer Products · OLIN Corporation 120 Long Ridge Road Stamford, CT 06904