DIRECTIONS FOR POOL USE: Olin Granular Dry Chlorine is a concentrated chlorine agent in dry, free-flowing, non-dusting form.

Olin Granular Dry Chlorine controls growth of algae and effectively kills many bacteria which may be the cause of infections.

INITIAL CHLORINATION: For initial chlorination of any pool water, add 1 oz. (approx. 2 level tbs.) of Olin Granular Dry Chlorine for each 1,000 gallons. Test the chlorine residual with a pool test kit and if below 0.6-1.0 ppm repeat this dos age until 0.6-1.0 ppm is obtained.

subsequently add 3.4 ounces (6.8 level tbs.) per 5,000 gallons daily or as often as needed to maintain 0.6-1.0 ppm whether the pool is in use or not. To help you in maintaining the proper available chlorine residual, it is possible to add approximately 1.0 ppm available chlorine by adding 1 ounce (2 level tbs.) of Olin Granular Dry Chlorine for each 5,000 gallons of water. Use an orthotolidine test kit for residual chlorine determinations. For best results, add Granular as a solution (1 oz. in 2 qts. of water) to the pool water or scatter the granular material directly over the pool surface.

MAINTENANCE OF PH: PH should be maintained in the 7.2-7.6 range. Maintaining 0.6-1.0 ppm (parts per million) chlorine residual and a 7.2-7.6 pH range will result in clean, sparkling water.

STABILIZED POOLS: For pools stabilized or conditioned (Olin Pool Stabilizer) with cyanuric acid at concentrations up to 50 ppm, always maintain the chlorine residual at 1.0-1.5 ppm as determined by a test kit.

SHOCK TREATMENT: If algae develop, shock treat the pool water by adding 1 oz. (approx. 2 level tbs.) of Olin Granular Dry Chlorine for each 500 gallons of water. Repeat if necessary. Before entering the pool, check the chlorine residual and if above 2.0 ppm allow the pool to stand until the residual drops to 2.0 ppm.

WINTERIZING POOL TO CONTROL ALGAE: To control algae during the winter when the pool is not in use add approx. 6 ozs. of Olin Granular Dry Chlorine per 1,000 gallons of clean, clear pool water. Then cover pool with a plastic cover for the winter. When the pool cover is removed in the spring add 1 oz. of Olin Granular Dry Chlorine per 1,000 gallons of water; check the chlorine residual with a pool test kit and if above 2.0 ppm allow the pool to stand until the residual drops to 2.0 ppm.

DANGER! HARMFUL OR FATAL IF SWALLOWED. MAY PRODUCE SEVERE CHEMICAL BURNS. DO NOT ALLOW CONTACT WITH EYES, SKIN, MUCOUS MEMBRANES, OR CLOTHING. STRONG OXIDIZER, CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE OR EXPLOSION. Keep from contact with clothing and other combustible materials. Do not store near combustible materials. Remove and wash contaminated clothing promptly. While Olin Granular Dry Chlorine by itself is not a combustible material, it must not be mixed or contaminated with any foreign material such as household products, soap products, paint products, solvents, acids, pool chemicals, garbage, vinegar, beverages, oils, pine oil, dicty rags, etc. Contamination or mixing with these types of chemicals and products may result in fire and the fire can be of great intensity. Prevent any burning material such as a lighted cigarette from falling into product. Drench fires with water. Flush spilled product with water. Dispose of spilled product by flushing with large amounts of water. Keep in a cool, dry place in original container. Rinse empty container thoroughly with water and discard it.

ANTIDOTE: External flood skin or eyes with plenty of water for 15 minutes. If irritation to skin persists, get medical attention. For eyes - call a physician immediately. Internal - drink large quantities of water or milk. Follow with milk of magnesia, vegetable oil, or beaten eggs. Call physician immediately.

Olin Granular Dry Chlorine is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, or ponds.

Olin CHEMICALS

HYPOCHLORITE PRODUCTS + OLIN CORPORATION 120 Long Ridge Rd Stamford Conn 06904

OGDC 1272



DANGER: KEEP OUT OF REACH OF CHILDREN STRONG OXIDIZER

See antidote statement and other required danger statement on the back panel. Mix only with water. May cause fire if contaminated.

ACCEPTED

5 LBS. NET