DIRECTIONS FOR USE IN SWIMMING POOLS (8,000 gals. or more capacity.

- 1. At the start of the pool season or in newly filled pools add Olin Pace Dry Chlorine Tablets at the rate of 1 tablet per 8,000 gallons of pool water to meet chlorine demand, reduce bacterial numbers, and control algae. Check pool in 48 hours and if below 1.0-1.5 ppm, repeat this dosage until 1.0-1.5 ppm chlorine residual, as shown by your test kit is obtained. When adding Olin Pace Dry Chlorine Tablets to pool, use a dissolving basket, a floating container, or add the Tablets to a plastic leaf strainer in the surface skimmer. Do not permit tablets to contact steel or plastic pool linings.
- 2. Thereafter, add Olin Pace at the rate of 1 tablet per 10,000 gallons of pool water every third day or as often as needed to maintain a 1.0 to 1.5 ppm chlorine residual.
- 3. pH should be maintained in the 7.2-7.6 range. Use a pool test kit for pH and available chlorine residual.
- 4. During the pool season superchlorinate with 1 tablet of Olin Pace Dry Chlorine Tablets per 8,000 gallons of pool water every two weeks when the pool water temperature is below 80°F, and every week when the average pool water temperature is above 80°F, in order to minimize odors and control algae. Before entering pool, check the chlorine residual and if above 2.0 ppm, allow the pool to stand until the chlorine residual drops to 2.0 ppm.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public water.

DANGER! STRONG OXIDIZER. CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE. AVOID INHALATION OF DUST. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. Keep from contact with clothing and other combustible materials. Do not store near combustible materials. Store in tightly closed container. Remove and wash contaminated clothing promptly. While Olin Pace Dry Chlorine Tablets by itself is not a combustible material, it must not be mixed or contaminated with any foreign material such as household products, soap products, paint products, solvents, acids, pool chemicals, vinegar, beverages, oils, pine oil, dirty rags, etc. Contamination or mixing with these types of chemicals and products may result in fire and the fire can be of great intensity. Prevent any burning materials, such as a lighted cigarette from falling into product. Drench fires with water. Flush spilled product with water. Keep in a cool dry place in original container. Always replace container lid. Do not reuse empty container.

ANTIDOTE: External - flood skin or eyes with plenty of water for 15 minutes. If irritation to skin persists, get medical attention. For eyescall a physician immediately. Internal - drink large quantities of mil?. Follow with milk of magnesia, vegetable oil, or beaten eggs. Call physician immediately.

## Olin CHEMICALS

HYPOCHLORITE PRODUCTS OLIN CORPORATION 120 Long Ridge Rd , Stamford, Connecticut 06904



To Control Algae and Bacteria

DESIGNED TO DISSOLVE SLOWLY AND COMPLETELY STABILIZED FOR EXTENDED CHLORINE LIFE

## DANGER! KEEP OUT OF REACH OF CHILDREN

May Be Fatal if Swallowed. May cause eye damage. May cause burns on wet skin, nose and throat. Doest May be Harmful if inhaled. Mix only with water. Strong Oxidizer. Lo not mix with any pool chemicals. May Cause Fire if contaminated. See Antidote Statement and other precautionary statements on back panel.

NET WT. 5 LBS.