

**DIRECTIONS FOR SWIMMING POOLS USE:** Olin HTH Granular Dry Chlorine is a concentrated chlorine agent in dry free flowing, non-dusting form. Olin HTH Granular Dry Chlorine when used as directed controls growth of algae and effectively kills many bacteria which may be the cause of infections. Use cap to measure HTH Granular.

**INITIAL CHLORINATION:** For initial chlorination of any pool water, add 1 ounce of Olin HTH Granular Dry Chlorine for each 1,000 gallons. Allow five minutes for the dry chlorine granular to disperse and then test the chlorine residual with a pool test kit and if below 0.6-1.0 ppm repeat dosage until 0.6-1.0 ppm is obtained. If above 2.0 ppm, allow the pool to stand until the residual drops to 2.0 ppm.

**ROUTINE CHLORINATION DOSAGE:** Subsequently add 3-4 oz. of HTH Granular per 5,000 gallons daily or as often as needed to maintain 0.6-1.0 ppm whether the pool is in use or not. Use a test kit to determine chlorine residual. To help you in maintaining the proper chlorine residual it is possible to apply approximately 1.0 ppm available chlorine by adding 1 oz. of HTH Granular per 5,000 gallons of water. For best results, add HTH Granular as a solution (1 oz. in 2 qts. of water) to the pool water or scatter the granular material directly over the pool surface. pH should be maintained in the 7.2-7.6 range.

**STABILIZED POOLS:** For pools conditioned with cyanuric acid at concentrations up to 50 ppm, always maintain the chlorine residual at 1.0-1.5 ppm as determined by a test kit. Add 3 oz. of HTH Granular per 10,000 gallons every other day or as often as needed to maintain this 1.0-1.5 ppm chlorine residual.

**SHOCK TREATMENT FOR ALGAE:** If algae develops with resulting slimy feel and greenish color on bottom and sides of the pool, shock treatment is necessary. Add 1 oz. of HTH Granular for each 500 gallons of water. Repeat if necessary. Before entering the pool, check the chlorine residual and if above 2.0 ppm allow the pool to stand until the residual drops to 2.0 ppm.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Apply this product only as specified on the label.

**DANGER! HARMFUL OR FATAL IF SWALLOWED. MAY PRODUCE SEVERE CHEMICAL BURNS. DO NOT ALLOW CONTACT WITH EYES, SKIN, MUCOUS MEMBRANES, OR CLOTHING. STRONG OXIDIZER, CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE OR EXPLOSION.**

Keep from contact with clothing and other combustible materials. Do not store near combustible materials. Remove and wash contaminated clothing promptly. While Olin HTH Granular Dry Chlorine by itself is not a combustible material, it must not be mined or contaminated with any foreign material such as household products, soap products, paint products, solvents, acids, pool, chemicals, garbage, vinegar, beverages, oils, pine oil, dirty rags, etc. Contamination or mixing with these types of chemicals and products may result in fire or explosion and the fire can be of great intensity. Prevent any burning material such as a lighted cigarette from falling into product. Drench fires with water. Flush spilled product with water. Dispose of spilled product by flushing with large amounts of water. Keep in a cool, dry place in original container. Rinse empty container thoroughly with water and discard it.

**FIRST AID:** External-flood skin or eyes with plenty of water for 15 minutes. If irritation to skin persists, get medical attention. For eyes-call a physician immediately. Internal-Drink milk, gelatin solution, or egg whites. Follow with milk of magnesia, vegetable oil or beaten eggs. Call physician immediately.

HTH-62-973

**Olin CHEMICALS**

CONSUMER PRODUCTS OLIN CORPORATION  
120 Long Ridge Road, Stamford, Connecticut 06904

**OLIN HTH<sup>®</sup> GRANULAR DRY CHLORINE**

**FOR SWIMMING POOLS - 62**

Active Ingredient: Calcium Hypochlorite\* ..... 62%  
Inert Ingredients: ..... 38%  
\*Available Chlorine: ..... 62%

**5 LBS. NET**

**DANGER KEEP OUT OF REACH OF CHILDREN**

STRONG OXIDIZER Mix only with water. Mixing or contaminating with other materials may result in fire. Read precautionary and first aid information on back panel.

EPA Reg. 1258-978