

pacee

pool chlorinating Type E cartridge
for use in E-Z Chlor, CPC,
and SUN Feeders

- Protects against bacteria and algae
- Stabilized (Sun Protected) for extended chlorine life
- Slow dissolving
- Totally soluble
- The PACE Tablets in this cartridge will provide an effective chlorine residual of 1.0 - 1.5 parts per million (ppm) in 10,000 gallons of water for about 9 weeks under normal conditions

DIRECTIONS FOR POOL USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Use with E-Z Chlor, CPC and Sun Feeders

START UP

1. Bring chlorine residual to 1.0-1.5 ppm. Follow instructions for your specific testing kit for this purpose.
2. The day after your chlorine residual reaches 1.0-1.5 ppm, use a sample with a PACE Tablet & C multimeter to determine your pool. Follow label directions.
3. Adjust pH to the ideal range of 7.2-7.4.

INSTRUCTIONS FOR USE IN E-Z CHLOR AND SUN FEEDERS

1. Remove and use these instructions for future reference.
2. Select the dipole to affect immediately according to the table below.

Approx. Pool Size (sq ft)	Starting Dipole No.*
15,000	1
15,000	1
20,000	5
30,000	7

* For 24 hours per day, week-long operation

1. Using two calculators at a time, divide your pool's size by two to determine the proper dipole number to use. Insert (e.g. for 2 calculators in 30,000 gallons use the dipole specified for 15,000 gallons).
 2. Find the dipole on the side panel of this cartridge corresponding to your dipole number and punch out the dipole and punch out a 1/2 inch hole in the dipole. Also punch out the unnumbered dipole on the bottom of both sides of the cartridge.
 3. Remove the top seal from the bottom of the cartridge.
 4. Place the cartridge in your feeder.
 5. Make the chlorine residual between 1.0 and 1.5 ppm. Test your water frequently using a suitable test kit.
- If the chlorine residual is below 1.0, punch out the next higher numbered dipole. If chlorine residual is above 1.5, punch out the next lower numbered dipole and cover the original hole with black electrical tape.
- Periodically remove cartridge and dipole to determine approximate tablet level. Insert new cartridge when old one is empty.

INSTRUCTIONS FOR USE IN CPC FEEDER

1. Remove and save bottom flange for future reference.
 2. Punch a 1/2 inch hole anywhere in the side of the handle at the top of the cartridge. Also punch 1/2 inch holes in the unnumbered dipoles on the bottom of both sides of the cartridge.
 3. Remove the top seal from the bottom of the cartridge.
 4. Place the cartridge in your feeder.
 5. Make the calibration tube until the water level is about the level corresponding to the number of gallons in your pool per the feeder instruction book.
 6. Maintain your chlorine residual between 1.0 and 1.5 ppm. Test frequently using a suitable test kit.
- If the chlorine residual is below 1.0, raise the calibration tube. If the chlorine residual is above 1.5, lower the calibration tube.
- Periodically remove the cartridge and shake it to determine the approximate tablet level. Insert a new cartridge when the old one is empty.



pacee
BEST DOCUMENT AVAILABLE

pool chlorinating
Type E
cartridge
for feeders

ACCEPTED
1258-997
JAN 9 1993
FOR ECONOMIC POISON REGISTRATION UNDER NO. 1258-997

Active Ingredient:
Trichloro-s-Triazinotriene 89%
Inert Ingredients 1%
Available Chlorine 89%

**KEEP OUT OF REACH OF CHILDREN
DANGER!**

See Usage Instructions and Precautions on Back Panel

For use in E-Z Chlor, CPC and
SUN Feeders

EPA Reg. No. 1258-997

EPA Est. No. 1258-LA 1

NET WT. 4 LBS. (1.8 kg)

Precautionary Statements

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Highly corrosive. Causes skin and eye irritation. May be fatal if swallowed. May get in eyes, on skin or on clothing. Do not handle with bare hands. Wear goggles or face shield and use rubber gloves or only use specially chosen dry cloths when handling. Irritating to nose and throat. Avoid breathing dust and fumes. Remove and wash contaminated clothing before reuse.

FIRST AID (Practical Treatment)

- If Swallowed:** First large amounts of milk or tea water and then vomiting. Call a physician immediately.
- If On Skin:** Wash off excess chemical and flush skin with cool water for at least 15 minutes. If irritation persists get medical attention.
- If In Eyes:** Flush with cool water for at least 15 minutes. Get immediate medical attention.
- If Inhaled:** Remove person to fresh air. Get immediate medical attention.

CHEMICAL HAZARDS

DANGER: Strong oxidizing agent. May cause fire, explosion. May cause severe eye irritation with moisture, skin, mucous membranes or other tissues. The liquid portion (and crystals) or any other liquid matter may cause a chemical reaction with acid solution of heat. Generation of hazardous gases and possible generation of fire and explosion. May cause severe eye irritation or burning material, such as nylon, leather, etc. Do not use this cartridge in any chlorinating system which has been used with an inorganic or compound chlorinating concentrate (e.g. calcium hypochlorite). Such use may cause fire or explosion. Do not empty this cartridge or the metal of compound tanks or metal plates, pool feeders or metal of pipe to the street. Throw this cartridge directly into the pool.

ENVIRONMENTAL HAZARDS

This product in this cartridge is toxic to fish. Do not discharge into lakes, streams, ponds or public water courses in accordance with an NPDES Permit. Use guidelines issued by the regional office of EPA.

STORAGE AND DISPOSAL:

Keep product dry in unopened package until use. Do not use in a hot, dry, well-ventilated area away from heat and open flame. Do not store empty cartridge. When cartridge becomes empty, with water to dissolve all material before discarding. Place empty cartridge in disposal of in appropriate local area or try to a collection. **EMERGENCY HANDLING:** In case of contamination or decomposition of product, do not use as fertilizer. If possible, isolate cartridge in open and well-ventilated area. Flush with large volumes of water. Do not use as fertilizer in an enclosed (soil) area or try to a safe place.

ADDITIONAL POOL CARE RECOMMENDATIONS

pH: Maintaining pH in the ideal range of 7.2-7.4 is extremely important to the efficacy of your chlorine and oxidizing systems. Test the pH often with a suitable test kit. Adjust pH as necessary, using products such as PAC-3 pH Minus™ or PAC-3 pH Plus™.

Superchlorination: Superchlorination with a chlorine hypochlorite product such as PAC-3 Super Chlorinator & Shock Treatment™ is recommended to treat out the organic material your filter can't handle and keep your water sparkling clear. Use as directed on the label, especially during excessive heat when bathing loads are high, when water becomes dull looking or hazy, when there is a "chlorine" like smell or orange eye irritation or other heavy rains.

Shock Treatment: If algae appear, shock treat your pool with a chlorine hypochlorite product such as PAC-3 Super Chlorinator & Shock Treatment™. Follow label directions. An alternative method is to add 20 PAC-3 Tablets (approx. 14 oz.) in the chlorine for each 10,000 gallons of water. Run pump and filter until totally dead-end (approx. 12 hours). Thoroughly clean pool by scrubbing surface of glass, vinyl, vacuum and scrub through filter. Pool should not be used until chlorine residual is lower than 1.0-1.5 ppm.

HOW TO DETERMINE POOL CAPACITY:

Rectangular Pools: Multiply length x width x average depth x 7.5 = pool capacity (10% gallon of Round Pools, multiply radius (1/2 diameter) x radius x average depth x 2.5 = pool capacity (10% gallon)

CLIN CHEMICALS
CONSUMER PRODUCTS - CLIN CORPORATION
120 Long Ridge Road, Stamford, Conn. 06904

STOCK AVAILABLE
27

4 E PC 1175



pool chlorinating Type E cartridge
for use in E-Z Chlor, CPC,
and SUN Feeders

- Protects against bacteria and algae
- Stabilized (Sun Protected) for extended chlorine life
- Slow dissolving
- Totally soluble
- The PACE Tablets in this cartridge will provide an effective chlorine residual of 1.0-1.5 parts per million (ppm) in 10,000 gallons of water for about 4 weeks under normal conditions.

DIRECTIONS FOR POOL USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
Use with E-Z Chlor, CPC and Sun Feeders.

START UP

1. Using chlorine residual in 1.0-1.5 ppm. Follow instructions for your specific testing kit for chlorine testing.
2. The day after your chlorine residual reaches 1.0-1.5 ppm, use a weak acid (e.g., PACI Stabilizer & Conditioner) to stabilize your pool. Follow label directions.
3. Adjust pH to the ideal range of 7.2-7.6.

INSTRUCTIONS FOR USE IN E-Z CHLOR AND SUN FEEDERS

1. Read and save these instructions for future reference.
2. Select the dipole identified numerically according to the table below.

Approx. Pool Size (gal)	Starting Dipole No.*
5,000	1
15,000	3
25,000	5
35,000	7

* For 24 hour two day replacement operation

3. If using two cartridges at a time, divide your pool's size by two to determine the proper dipole number to use instead (e.g. for 2 cartridges in 30,000 gallons use the dipole specified for 15,000 gallons).
4. Find the dipole on the side panel of the cartridge corresponding to your dipole number specified above and punch out a 1/2" hole in the dipole. Also punch out the unnumbered dipoles on the bottom of both sides of the cartridge.
5. Remove the tape seal from the bottom of the cartridge.
6. Place the cartridge in your feeder.
7. Maintain your chlorine residual between 1.0 and 1.5 ppm. Test your water frequently using a suitable test kit.
If the chlorine residual is below 1.0, punch out the next higher numbered dipole. If chlorine residual is above 1.5, punch out the next lower numbered dipole and cover the original hole with black electrical tape.
Periodically remove cartridge and dipole to determine approximate tablet level, insert new cartridge when old one is empty.

INSTRUCTIONS FOR USE IN CPC FEEDER

1. Read and save instructions for future reference.
2. Punch a 1/2" hole anywhere in the side of the handle at the top of the cartridge. Also punch 1/2" holes in the unnumbered dipoles on the bottom of both sides of the cartridge.
3. Remove the tape seal from the bottom of the cartridge.
4. Place the cartridge in your feeder.
5. Place the calibration tube until the water level reaches the level corresponding to the number of gallons in your pool per the feeder instructions.
6. Maintain your chlorine residual between 1.0 and 1.5 ppm. Test frequently using a suitable test kit.
If the chlorine residual is below 1.0, raise the calibration tube. If the chlorine residual is above 1.5, lower the calibration tube.
Periodically remove the cartridge and shake it to determine the approximate tablet level. Insert a new cartridge when the old one is empty.



pool chlorinating
Type E
cartridge
for feeders

ACCEPTED
1258
JAN 9
UNDER THE FEDERAL
FUNGICIDE AND R
FOR ECONOMIC P
ED UNDER NO. 1/5

Active Ingredient:
Trichloro-s-Triazinetrione 89%
Inert Ingredients 1%
Available Chlorine 89%

**KEEP OUT OF REACH OF CHILDREN
DANGER!**

See Usage Instructions and Precautions on Back Panel

For use in E-Z Chlor, CPC and
SUN Feeders

EPA Reg. No. 1258-997

EPA Est. No. 1258-LA-1

NET WT. 4 LBS. (1.8kg)

30

pool chlorinating Type E cartridge
 for use in E-Z Chlor, CPC,
 and SUN Feeders

Use the chlorine
 cartridge as follows:

1. Remove cartridge with

instructions for easy specific handling

2. Open the cartridge and place in the feeder as shown.

FEEDERS

1. Check the label for the

2. Check the

3. Check the

4. Check the

5. Check the

6. Check the

7. Check the

8. Check the

9. Check the

10. Check the

11. Check the

12. Check the

13. Check the

14. Check the

15. Check the

16. Check the

17. Check the

18. Check the

19. Check the

20. Check the

21. Check the

22. Check the

23. Check the

24. Check the

25. Check the



pace
 BEST DOCUMENT LABEL

pool chlorinating
 Type E
 cartridge
 for feeders

ACCEPTED
 1258-997
 JAN 9 1980
 UNDER THE FEDERAL INSECTICIDE
 FUNGICIDE AND ROBERTICIDE ACT
 FOR ECONOMIC POISON REGISTRATION
 UNDER NO. 1258-997

Active Ingredient:
 Trichloro-s-Triazinetrione 99%
 Inert Ingredients 1%
 Available Chlorine 89%

**KEEP OUT OF REACH OF CHILDREN
 DANGER!**
 See Usage Instructions and Precautions on Back Panel

For use in E-Z Chlor, CPC and
 SUN Feeders

EPA Reg. No. 1258-997

EPA Est. No. 12684A-1

NET WT. 4 LBS. (1.8kg) 30

Precautionary Statements

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Irritant. Causes skin and eye irritation. May be fatal if swallowed. Run out of eyes, on skin or on clothing. Do not breathe dust. Wash hands or face with water. Wash clothing. Avoid breathing dust. Avoid contact with eyes. Avoid contact with skin. Avoid contact with clothing. Avoid contact with food. Avoid contact with feed. Avoid contact with water. Avoid contact with swimming pool water. Avoid contact with drinking water. Avoid contact with food and feed. Avoid contact with water. Avoid contact with swimming pool water. Avoid contact with drinking water. Avoid contact with food and feed.

FIRST AID (Practical Treatment)

If Swallowed: Feed large amounts of milk and or water and induce vomiting. Call a physician immediately.
 If On Skin: Wash off excess chemical and flush skin with cold water for at least 15 minutes. If irritation persists, get medical attention.
 If In Eyes: Flush with cold water for at least 15 minutes. Get immediate medical attention.
 If Inhaled: Remove person to fresh air. Get immediate medical attention.

CHEMICAL HAZARDS:

DANGER: Strong oxidizing agent. Use only clean, dry vessels. Mix only into water. Can combine with moisture, dirt, organic matter or other chemicals (including other pool chemicals) or any other foreign matter may start a chemical reaction with generation of heat, formation of hazardous gases, and possible generation of the gas explosion. Avoid any contact with flammable or burning material, such as paper, cloth, etc. Do not use this cartridge in any chlorinating device which has been used with an inorganic or unbuffered chlorinating compound (e.g. calcium hypochlorite). Such use may cause fire or explosion. Do not permit this cartridge or the material contained herein to contact plastic pool linings or metal objects. Do not throw the cartridge directly into the pool.

ENVIRONMENTAL HAZARDS:

This product in this cartridge is toxic to fish. Do not discharge into lakes, streams, ponds, or public waters unless in accordance with an NPDES Permit. For additional contact the regional office of EPA.

STORAGE AND DISPOSAL:

Keep product dry in unopened cartridge when not in use. Store in a cool, dry, well-ventilated area away from heat and open flame. Do not store empty cartridge. Empty cartridge thoroughly with water to dissolve all material before discarding. Place empty cartridge or mixture of in approved landfill area or bury in a safe place. **EMERGENCY HANDLING:** In case of contamination or decomposition of product, discard cartridge. If possible, isolate cartridge in open and well ventilated area. Flush with large volumes of water. Effluent of contained material in an authorized landfill area or bury in a safe place.

ADDITIONAL POOL CARE RECOMMENDATIONS:

pH - Maintaining pH in the level range of 7.2 - 7.6 is extremely important to the efficacy of your chlorine and swimming comfort. Test the pH often with a suitable test kit. Adjust pH as necessary, using products such as "PACE pH Minus" or "PACE pH Plus".
Superchlorination - Superchlorination with a calcium hypochlorite product such as "PACE Super Chlorinate & Shock Treatment" is recommended to kill out the organic material your filter can't handle and keep your water sparkling clean. Use as directed on the label, especially during excessive heat, when bathing loads are high, when water becomes dull looking or hazy, when there is a "chlorine" smell or decrease eye irritation, or after heavy rains.
Shock Treatment - If after another check your pool with a calcium hypochlorite product such as "PACE Super Chlorinate & Shock Treatment", follow label directions. An alternative method is to add 28 PACE Tablets (approx. 14 oz.) in the skimmer for each 10,000 gallons of water. Run pump and filter until totally distributed (approx. 24 hours). Thoroughly clean pool by scrubbing surface of steps, bench, vacuum, and circle through floor. Pool should not be used until chlorine residual is from 9.0 - 3.0 ppm.

TO DETERMINE POOL CAPACITY:

Rectangular Pools: Multiply length x width x average depth x 2.5 = pool capacity (U.S. gallons)
 Round Pools: Multiply radius (1/2 diameter) x radius x average depth x 2.5 = pool capacity (U.S. gallons)

Olin CHEMICALS
 CONSUMER PRODUCTS - OLIN CORPORATION
 120 Long Ridge Road, Stamford, Conn. 06908
 8-E-FC-1179