

pace pool chlorinating Type G cartridge
for use in GUARDEX and ANTHONY
FEEDERS and PACE® and
GUARDEX FLOATERS

- Protects against bacteria and algae
- Stabilized (Sun Protected) for extended chlorine life
- Slow dissolving
- Totally soluble
- The PACE Tablets in this cartridge will provide an effective chlorine residual of 1.0-1.5 parts per million (ppm) in 10,000 gallons of water for about 9 weeks under normal conditions.

DIRECTIONS FOR POOL USE

It is a violation of Federal law to use this product in a manner inconsistent with the labeling.

Use with Guards and Anthony Feeders and Pace® and Guardex Floaters

START UP

1. Bring chlorine residual to 1.0-1.5 ppm. Follow instructions for your specific feeding device shown below.
2. The day after your chlorine residual reaches 1.0-1.5 ppm, use cyanuric acid (e.g. PACY Stabilizer & Conditioner) to stabilize your pool. Follow label directions.
3. Adjust pH to the ideal range of 7.2-7.8.

INSTRUCTIONS FOR USE IN GUARDEX AND ANTHONY FEEDERS

1. NOTE: A small amount of powdered sanitizer may fall from inside cartridge during preparation for use.
 2. Remove and save these instructions for future reference.
 3. Punch "X" hole in designated spot in handle of cartridge. Punch "Y" hole in one set of three vertical dividers near bottom of cartridge.
 4. Remove top seal from bottom of the cartridge.
 5. Select initial height setting according to the size of your pool as follows:
- | Pool Size (Gallons) | 10,000 | 15,000 | 20,000 | 25,000 | 30,000 | 35,000 |
|---------------------|--------|--------|--------|--------|--------|--------|
| Height Setting | 1 | 2 | 3 | 4 | 5 | 6 |
6. If using two cartridges at a time, divide your pool size by two to determine the proper height setting (e.g. for 2 cartridges in 30,000, use the height setting for 15,000 gallons).
 7. Insert the cartridge(s) into the feeder until the selected height setting is even with the top of the feeder cover and rotate cartridge clockwise about one quarter turn until it stops.
 8. Maintain chlorine residual between 1.0 and 1.5 ppm. Test your water frequently using a suitable test kit. If chlorine residual is below 1.0, adjust height setting to next higher number (e.g. 3 to 4). If chlorine residual is above 1.5, adjust height setting to next lower number (e.g. 3 to 2).

INSTRUCTIONS FOR USE IN PACE® FLOATER

1. Follow instructions 1-5 for Guards and Anthony Feeders.
2. Center the three rows of ridges on the cartridge between the triangular guides on the floater.
3. Holding the floater by handle and having the opposite edge supported, insert and wedge the cartridge in the selected height setting (number) to be first above triangular guide of floater.
4. To lock, rotate cartridge in clockwise direction about one quarter turn until it stops. It may be necessary to raise or lower the cartridge slightly (see ridges line up with ridges in floater roller).
5. Maintain chlorine residual between 1.0 and 1.5 ppm. Test your water frequently using a suitable test kit. If chlorine residual is below 1.0, adjust height setting to next higher number (e.g. 3 to 4). If chlorine residual is above 1.5, adjust height setting to next lower number (e.g. 3 to 2).

INSTRUCTIONS FOR USE IN GUARDEX FLOATERS

1. Follow instructions 1-4 for Guards and Anthony Feeders.
 2. Select initial height setting according to the size of your pool as follows:
- | Pool Size (Gallons) | 10,000 | 15,000 | 20,000 | 25,000 | 30,000 | 35,000 |
|---------------------|--------|--------|--------|--------|--------|--------|
| Height Setting | Off | 0 | 1 | 2 | 3 | 4 |
3. Holding the floater with one hand and having the opposite edge supported, insert and wedge the cartridge into the floater until the selected height setting is even with the top of the floater and lock in place by rotating cartridge clockwise about one quarter turn until it stops. It may be necessary to raise or lower the cartridge slightly (see ridges line up with ridges in floater roller).
 4. Maintain chlorine residual between 1.0 and 1.5 ppm. Test your water frequently using a suitable test kit. If chlorine residual is below 1.0, adjust height setting to next higher number (e.g. 3 to 4). If chlorine residual is above 1.5, adjust height setting to next lower number (e.g. 3 to 2).



pace

pool chlorinating
Type G
cartridge
for feeders and floaters

Active Ingredient:
Trichloro-s-Triazinetrione 99%
Inert Ingredients 1%
Available Chlorine 89%

**KEEP OUT OF REACH OF CHILDREN
DANGER**
See Usage Instructions and Precautions on Back Panel

For use in GUARDEX and ANTHONY FEEDERS and
PACE® and GUARDEX FLOATERS

EPA Reg. No. 1258-998 EPA Est. No. 1258-LA-1

NET WT. 4 LBS. (1.8kg)

BEST DOCUMENT AVAILABLE

2

Precautions & Statements

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Highly corrosive. Causes skin and eye damage. May be fatal if swallowed. Do not get in eyes, on skin or on clothing. Do not handle with bare hands. Wear goggles or face shield and use under a hood or only thoroughly clean dry utensils when handling. Striking to nose and throat. Avoid breathing dust and fumes. Remove and wash contaminated clothing before reuse.

FIRST AID (Practical Treatment)

- H Swallowed:** Feed large amounts of water and induce vomiting. Call a physician immediately.
- H On Skin:** Brush off excess chemical and flush skin with cold water for at least 15 min. Use if irritation persists, get medical attention.
- H In Eyes:** Flush with cold water for at least 15 minutes. Get immediate medical attention.
- H Inhaled:** Remove person to fresh air. Get immediate medical attention.

CHEMICAL HAZARDS

DANGER: Strong oxidizing agent. Use only clean, dry utensils. Mix only into water. Combination with moisture, dirt, organic matter or other chemicals (including other pool chemicals) or any other foreign matter may start a chemical reaction with generation of heat, liberation of flammable gases, and possible generation of fire and explosion. Avoid any contact with flammable or burning material, such as lighter, cigarette. Do not use this cartridge in any chlorinating device which has been used with an inorganic or unstabilized chlorinating compound (e.g. calcium hypochlorite). Such use may cause fire or explosion. Do not permit this cartridge or the material contained herein to contact plastic pool linings or metal objects. Do not allow the cartridge directly into the pool.

ENVIRONMENTAL HAZARDS

This product in this cartridge is toxic to fish. Do not discharge into lakes, streams, ponds, or public waters unless in accordance with an NPDES Permit. For guidance contact the regional office of EPA.

STORAGE AND DISPOSAL

Keep product dry in unopened cartridge when not in use. Store in a cool, dry, well-ventilated area away from heat and open flame. Do not reuse empty cartridge. Rinse cartridge thoroughly with water to dissolve all material before discarding. Place empty cartridge or dispose of in approved landfill area or bury in a safe place. **EMERGENCY HANDLING:** In case of contamination or decomposition of product, do not reuse cartridge. If possible, before cartridge is seen and ventilated area. Flood with large volumes of water. Observe of contaminated cartridge in an approved landfill area or bury in a safe place.

ADDITIONAL POOL CARE RECOMMENDATIONS:

- pH:** Maintaining pH in the ideal range of 7.2-7.8 is extremely important to the efficacy of your chlorine and ensuring comfort. Test the pH often with a suitable test kit. Adjust pH as necessary using products such as "PACE pH Minus™" or "PACE pH Plus™".
- Superchlorination:** Superchlorination with a calcium hypochlorite product such as "PACE Super Chlorinator & Shock Treatment" is recommended to burn out the organic material which filter can't handle and keep your water sparkling clear. Use as directed on the label, especially during excessive heat, when bathing loads are high, when water becomes dull looking or hazy, when there is a "chlorine" smell or excessive eye irritation, or after heavy rains.
- Shock Treatment:** If algae appear, shock treat your pool with a calcium hypochlorite product such as "PACE Super Chlorinator & Shock Treatment". Follow label directions. An alternative method is to add 28 PACE Tablets (approx. 14 oz.) in the skimmer for each 10,000 gallons of water. Run pump and filter until totally exhausted (approx. 1 1/2 days). Thoroughly clean pool by scrubbing surface of algae growth, vacuum, and cycle through filter. Pool should not be used until chlorine residual is from 1.0-3.0 ppm.

TO DETERMINE POOL CAPACITY:

Rectangular Pools: Multiply length x width x average depth x 7.5 = pool capacity (U.S. gallons)
Round Pools: Multiply radius (1/2 diameter) x radius x average depth x 23.5 = pool capacity (U.S. gallons)

Olin CHEMICALS
CONSUMER PRODUCTS—OLIN CORPORATION
120 Long Ridge Road, Stamford, Conn. 06904

4 G-PC-1278

ACCEPTED
1258-998

34

pace

pool chlorinating Type G cartridge
for use in GUARDEX and ANTHONY
FEEDERS and PACE® and
GUARDEX FLOATERS

- Protects against bacteria and algae
- Sun Protected (Sun Protected™) for extended chlorine life
- Stable chlorine
- Totally soluble

• The PACE Tablets in this cartridge will provide an effective chlorine residual of 1.0-1.5 parts per million (ppm) in 10,000 gallons of water for about 9 weeks under normal conditions.

DIRECTIONS FOR POOL USE

It is a violation of Federal law to use this product in a manner inconsistent with the labeling.

Use with Guardex and Anthony Feeders and Pace® and Guardex Floaters.

START UP

1. Bring chlorine residual to 1.0-1.5 ppm. Follow instructions for your specific feeding device shown below.
2. The day after your chlorine residual reaches 1.0-1.5 ppm, use cyanoic acid (i.e., PACE Stabilizer & Conditioner) to stabilize your pool. Follow label directions.
3. Adjust pH to the ideal range of 7.2-7.6.

INSTRUCTIONS FOR USE IN GUARDEX AND ANTHONY FEEDERS

1. NOTE: A small amount of powdered chlorine may fall from inside cartridge during preparation for use.
 2. Remove and save these instructions for future reference.
 3. Punch 1/2" hole in designated spot in bands of cartridge. Punch 1/2" hole in one set of three vertical dividers near bottom of cartridge.
 4. Remove tape seal from bottom of the cartridge.
 5. Select initial height setting according to the size of your pool as follows:
- | Pool Size (Gallons) | 10,000 | 15,000 | 20,000 | 25,000 | 30,000 | 35,000 |
|---------------------|--------|--------|--------|--------|--------|--------|
| Height Setting | 1 | 2 | 3 | 4 | 5 | 6 |
6. If using two cartridges at a time, divide your pool size by two to determine the proper height setting (e.g., for 2 cartridges in 30,000, use the height setting for 15,000 gallons).
 7. Insert the cartridge(s) into the feeder until the selected height setting is even with the top of the feeder cover and rotate cartridge clockwise about one quarter turn until it stops.
 8. Maintain chlorine residual between 1.0 and 1.5 ppm. Test your water frequently using a suitable test kit. If chlorine residual is below 1.0, adjust height setting to next higher number (e.g., 3 to 4). If chlorine residual is above 1.5, adjust height setting to next lower number (e.g., 3 to 2).

INSTRUCTIONS FOR USE IN PACE® FLOATER

1. Follow instructions 1-5 for Guardex and Anthony Feeders.
2. Center the three rows of ridges on the cartridge between the triangular guides on the floater.
3. Holding the floater by handle and having the opposite edge supported, insert and wedge the cartridge in the selected height setting (must be just above triangular guide at floater).
4. To lock, rotate cartridge in clockwise direction about one quarter turn until it stops. It may be necessary to raise or lower the cartridge slightly (so ridges line up with ridges in floater collar).
5. Maintain chlorine residual between 1.0 and 1.5 ppm. Test your water frequently using a suitable test kit. If chlorine residual is below 1.0, adjust height setting to next higher number (e.g., 3 to 4). If chlorine residual is above 1.5, adjust height setting to next lower number (e.g., 3 to 2).

INSTRUCTIONS FOR USE IN GUARDEX FLOATERS

1. Follow instructions 1-5 for Guardex and Anthony Feeders.
 2. Select initial height setting according to the size of your pool as follows:
- | Pool Size (Gallons) | 10,000 | 15,000 | 20,000 | 25,000 | 30,000 | 35,000 |
|---------------------|--------|--------|--------|--------|--------|--------|
| Height Setting | Off | 0 | 1 | 2 | 3 | 4 |
3. Holding the floater with one hand and having the opposite edge supported, insert and wedge the cartridge into the floater until the selected height setting is even with the top of the floater and lock in place by rotating cartridge clockwise about one quarter turn until it stops. It may be necessary to raise or lower the cartridge slightly (so ridges line up with ridges in floater collar).
 4. Maintain chlorine residual between 1.0 and 1.5 ppm. Test your water frequently using a suitable test kit. If chlorine residual is below 1.0, adjust height setting to next higher number (e.g., 3 to 4). If chlorine residual is above 1.5, adjust height setting to next lower number (e.g., 3 to 2).



pace

pool chlorinating Type G cartridge for feeders and floaters

Active Ingredient:
Trichloro-s-Triazinetrione 99%
Inert Ingredients 1%
Available Chlorine 89%

**KEEP OUT OF REACH OF CHILDREN
DANGER**

See Usage Instructions and Precautions on Back Panel

For use in GUARDEX and ANTHONY FEEDERS and
PACE® and GUARDEX FLOATERS

EPA Reg. No. 1258-998 EPA Est. No. 12684A-1

NET WT. 4 LBS. (1.8kg)

ACCEPTED
1258-998
JAN 17 1980

U.S. DEPARTMENT OF AGRICULTURE
OFFICE OF PESTICIDE REGULATION
WASHINGTON, D.C. 20250

BEST DOCUMENT AVAILABLE

37

Precautionary Statements

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Highly corrosive. Causes skin and eye damage. May be fatal if swallowed. Do not get in eyes, on skin or on clothing. Do not handle with bare hands. Wear goggles or face shield and use rubber gloves or only thoroughly clean, dry work clothes when handling. Irritating to nose and throat. Avoid breathing dust and fumes. Remove and wash contaminated clothing before reuse.

FIRST AID (Practical Treatment)

- If Swallowed: Flush large amounts of milk and/or water and induce vomiting. Call a physician immediately.
- If On Skin: Brush off excess chemical and flush skin with cold water for at least 15 minutes. If irritation persists, get medical attention.
- If In Eyes: Flush with cold water for at least 15 minutes. Get immediate medical attention.
- If Inhaled: If you have returned to fresh air. Get immediate medical attention.

CHEMICAL HAZARDS:

Strong oxidizing agent. Use only clean, dry vessels. Mix only into water. Can react with organic matter, dirt, organic matter or other chemicals (including other pool chemicals) or any other foreign matter may start a chemical reaction with generation of heat, liberation of hazardous gases, or a possible generation of fire and explosion. Avoid any contact with flammable or burning material, such as liquid chlorine. Do not use this cartridge in any chlorinating device which has been used with an inorganic or unsuitable chlorinating compound (e.g., calcium hypochlorite). Such use may cause fire or explosion. Do not permit this cartridge or the material contained herein to contact plastic pool linings or metal objects. Do not throw the cartridge directly into the pool.

ENVIRONMENTAL HAZARDS:

This product in this cartridge is toxic to fish. Do not discharge into lakes, streams, ponds, or public waters unless in accordance with an NPDES Permit. For guidance contact the regional office of EPA.

STORAGE AND DISPOSAL:

Keep product dry in unopened cartridge when not in use. Store in a cool, dry, well-ventilated area away from heat and open flame. Do not store empty cartridge. Rinse cartridge thoroughly with water to dissolve all material before discarding. Place empty cartridge or discard in an approved landfill area or bury in a safe place. **EMERGENCY HANDLING:** In case of contamination or decomposition of product, do not reuse cartridge. If possible, recast cartridge in open and well-ventilated area. Flood with large volumes of water. Dispose of contaminated cartridge in an approved landfill area or bury in a safe place.

ADDITIONAL POOL CARE RECOMMENDATIONS:

pH: Maintaining pH in the ideal range of 7.2-7.6 is extremely important to the efficacy of your chlorine and swimming comfort. Test the pH often with a suitable test kit. Adjust pH as necessary, using products such as PACE pH Increaser™ or PACE pH Plus™.

Superchlorination: Superchlorination with a calcium hypochlorite product such as PACE Super Chlorinator & Shock Treatment™ is recommended to burn out the organic material your filter can't handle and keep your water sparkling clear. This is directed at the filter, especially during dry-weather heat, when bather loads are high, when water becomes still (locking or heavy), when there is a "chlorine" film on the pool or excessive eye irritation, or after heavy rains.

Shock Treatment: If algae appear, shock treat your pool with a calcium hypochlorite product such as PACE Super Chlorinator & Shock Treatment™. Follow label directions. An alternative method is to add 25 PACE Tablets (approx. 16 oz.) in the skimmer for each 10,000 gallons of water. Then pump and filter until results improved (approx. 5-7 days). Thoroughly clean pool by scrubbing surface of algae growth, vacuum, and cycle through filter. Pool should not be used until chlorine residual is from 1.5-2.0 ppm.

TO DETERMINE POOL CAPACITY:

Rectangular Pools: Multiply length x width x average depth x 7.5 = pool capacity (U.S. gallons)
Round Pools: Multiply radius (½ diameter) x radius x average depth x 22.5 = pool capacity (U.S. gallons)

Olin CHEMICALS
CONSUMER PRODUCTS - Olin CORPORATION
120 Long Ridge Road, Stamford, Conn. 06904

4-G-PC-1270