## UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460

JUN 10 2008



## United States Environmental Profession Office of Pesticide Programs Agency

Arch Chemical, Inc. 1955 Lake Park Drive, Suite 100 Smyrna, GA 30080

Attention: Garrett Schifilliti

Senior Regulatory Manager

Subject: Sodium Omadine 10% Aqueous Solution Industrial

Bactericide and Fungicide

EPA Registration No. 1258-1213

Your Amendment Dated February 4, 2008

The amendment, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, to add use in Leather Treatment, Surface and Floor Cleaners and In Dry Wall and Gypsum, Pearlite, Plaster-Like, Mineral Based, or Cellulose Derived Building Materials Used in the Manufacture of Ceilings, Ceiling Tile, Walls and Partitions" to the label, is acceptable, provided that you:

- 1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3©(5) and sec. 4 when the Agency requires all registrants of similar products to submit such data.
- 2. Submit two (2) copies of final printed labeling before you release the product for shipment.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

Page 2 EPA Registration No. 1258-1213

A stamped copy of the "accepted" product labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely

Marshall Swindell

Product Manager (33)

Regulatory Management Branch 1 Antimerobials Division (7510C)

**Enclosure** 

#### PRECAUTIONARY STATEMENTS: HAZARDS TO HUMANS AND DOMESTIC

**ANIMALS.** May cause eye and skin irritation. Harmful if swallowed, inhaled, or absorbed through the skin. Do not get in eyes, on skin, or on clothing.

#### PERSONAL PROTECTIVE EQUIPMENT(

**PPE):** Applicators and other handlers must wear: goggles or face shield, long sleeved shirt and long pants, socks and shoes, chemical- resistant gloves (such as rubber or waterproof gloves).

USER SAFETY REQUIREMENTS: Follow manufacturer's instructions for cleaning/ maintaining PPE. If no such instructions exist for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

USER SAFETY RECOMMENDATIONS: Users should wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Remove PPE immediately after handling this product. Wash the outside of gloves before removing.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, ponds, streams, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact our State Water Board or Regional Office of the EPA. CHEMICAL HAZARDS: Do not store or mix with strong oxidizing agents.

### SODIUM OMADINE® 10% AQUEOUS SOLUTION INDUSTRIAL FUNGICIDE & BACTERICIDE

Active Ingredient:
Sodium 2- pyridinethiol- 1- oxide 10.0%
Inert Ingredients 90.0%
Total 100%

#### KEEP OUT OF REACH OF CHILDREN

#### **CAUTION**

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONS

FIRST AID: IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advice.

IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

IF ON SKIN: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth- to- mouth, if

possible. Call a poison control center or doctor for further treatment advice.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. In case of emergency, for additional information call 1-800-654-6911. Have the product container or label with you when calling a poison control center or doctor or going for treatment.

STORAGE AND DISPOSAL: Do not contaminate water, food, or feed by storage and disposal. PESTICIDE STORAGE: Do not store above 130 degrees F. (55 deg. C.). Keep container tightly closed when not in use. Do not store with strong oxidizing agents.

PESTICIDE DISPOSAL: Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

CONTAINER DISPOSAL: Triple rinse container. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

ARCH CHEMICALS, INC. 501 MERRITT 7 NORWALK, CT 06856

EPA Reg. No. 1258- 1213 EPA Est. No. 1258- NY- 3

Omadine Gistal Marin trademark of Arch Chemicals, Inc. With CONIMENTS Wt. 25 Lbs.

EPA Letter Dated:

10 2006

Under the Federal Insecticide, Fungicide, and Redenticide Act as amended, for the pesticide, registered under EPA Reg. No. 1258–1213

DIRECTIONS FOR USE: It is a violation of federal law to use this product in a manner inconsistent with its labeling. Do not apply this product in a way that will contact workers or other persons. Do not use for applications involving direct or indirect food/drinking water contact.

IN AQUEOUS BASED FLUIDS SUCH AS METALWORKING, CUTTING, COOLING AND LUBRICATING FLUIDS: To inhibit bacterial and fungal growth add an initial dose of up to 5000 ppm of this product (5 lbs. of this product to 1,000 lbs. Of solution) to the solution by pouring from the container and subsequent maintenance doses of up to 5000 ppm (5 lbs. of the product per 1,000 lbs. of solution) every 7- 10 days or as needed. This product can be used at fluid to water ratios of 1: 10 to 1: 100. This product may be added to the fluid at the time it is prepared (diluted) or to the reservoir (sump) containing the fluid after it is put into use. If it is added to the reservoir, the fluid should be circulated after addition to ensure mixing. Contaminated fluid systems should be cleaned prior to the initial addition of this product. Drain the system, clean with a cleaner designed for this purpose, rinse with water and refill with fresh fluid containing this product (up to 5000 ppm). Frequent checks (at least once a week) of the bacterial and fungal population in the system should be made using standard microbiological plate count procedures or any of the commercial "dip-stick" type devices. When the pacterial count reaches 10<sup>7</sup> and/ or the fungal count-reaches 10<sup>3</sup> organisms per ml, add additional product-according to the above directions. If this does not reduce the bacterial and/or fungal count below the above value in 12-24 hours, the fluid should be discarded and replaced after

cleaning the system. Add this product to the fresh fluid according to the above directions. When adding fresh, diluted fluid to compensate for dragout or other losses, add this product to make- up fluid according to the above directions.

#### TO INHIBIT THE GROWTH OF BACTERIA AND FUNGI IN METALWORKING, CUTTING, COOLING AND LUBRICATING FLUID

CONCENTRATES: Add an amount that will give up to a 5000 ppm solution. The amount required in the concentrate will depend on the end use dilution. For example: If the desired level of this product is 1000 ppm and the end use dilution of the fluid is 5%, then a 2.0% concentration of this product is required in the concentrate (1000 ppm/ 0. 05= 20,000 ppm or 2.0%).

FOR THE IN- CAN PRESERVATION OF LATEX EMULSIONS USED IN ADHESIVES, CAULKS, PATCHING COMPOUNDS, SEALANTS, PASTES AND GROUTS: To inhibit bacterial growth in latex emulsions for a period of up to 1 year, a dosage of p to 4000 ppm of this product (4 lb. of this product per 1,000 lbs. of emulsion) is recommended. Product may be added at any time during the formulation procedure by pouring from the container.

IN AQUEOUS SYNTHETIC FIBER LUBRICANTS (SPIN FINISHES): To inhibit the growth of bacteria and the formation of bacterial slime in synthetic fiber lubricants (spin finishes) for periods of 2-4 weeks during use, add 5000 ppm (5 lbs. per 1,000 lbs. of lubricant) of this product to the diluted lubricant. This product may be used in

lubricant solutions containing 5-10% lubricant concentrate (water to lubricant ratios of 20-1 to 10-1). This product should be added by pouring from the container to the diluted lubricant in the dilution tank.

IN AQUEOUS BASED INKS: To inhibit the growth of bacteria and fungi in inks such as aqueous based inks, printing solutions, pigment slurries or press cake, add up to 4000 ppm of this product. While the inks are in use, a concentration of 4% w/ w of this product is necessary. The amount of this product to be added at the time of manufacture of the ink to obtain the above concentrations, at the time of use, will vary with the shelf- life of the ink. The table below shows the

relationship.

Shelf- Life Ink (months) %Sodium Omadine 10%

36	4.00
24	2.60
18	1.9
12	1.25
8	1.00

To inhibit the growth of bacteria in neutral or slightly acidic aqueous based jet-printer inks for periods of up to 4 weeks while the inks are in use, add 3% w/ w of this product to the ink at the time of manufacture. To avoid decomposition of this product during shelf-life of the ink, airtight packaging must be used. In all cases, this product may be added to the ink at any point in the manufacturing process by pouring from the container.



FOR THE DRY FILM PRESERVATION OF NATURAL AND SYNTHETIC ADHESIVES, LATEXES, URETHANE FOAMS, CAULKS, PATCHING COMPOUNDS, SEALANTS, ARCHITECTURAL PAINTS, INDUSTRIAL PAINTS AND COATINGS (Including wood coatings), PASTES AND GROUTS: Addition of up to 20,000 ppm (20 lbs. of this product per 1000 lbs. of formulation) of the active ingredient can inhibit microbial growth (bacteria and fungi) in the dry film of these products. This product can be added at any time during the formulation procedure. For example, sheet vinyl adhesives used in the installation of vinyl flooring can be preserved by the addition of 8400 ppm of this product (8.4 lbs. per 1000 lbs. of adhesive).

FOR THE IN- CAN PRESERVATION OF LAUNDRY RINSE ADDITIVES, LAUNDRY DETERGENTS, CARPET CLEANERS, SURFACE CLEANERS, FLOOR CLEANERS:

To inhibit the growth of bacteria and fungi in laundry rinse additives for periods of up to one year, add 0.64% w/ w (6400 ppm or 6.4 lbs. of this product per 1000 lbs. of formulation). This product can be added at any time during the formulation procedure.

FOR THE IN- CAN PRESERVATION OF WATER BASED CHEMICAL OR MINERAL ADD MIXTURES THAT ARE USED IN CONCRETE: Addition of up to 4000 ppm of this product can inhibit microbial growth (bacteria and fungi) in add mixtures. Add mixtures can be preserved by addition of 4000 ppm of this product (4.0 lb. of this product per 1000 lbs. of add mixture.)

# FOR THE PRESERVATION OF AQUEOUS ANALYTICAL AND DIAGNOSTIC REAGENTS USED IN CHEMICAL AND CLINICAL

ANALYSIS: Addition of up to 5000 ppm of this product can inhibit the growth of bacteria and fungi in aqueous analytical and diagnostic reagents (5 lbs. of this product per 1000 lbs. of reagent).

TO INHIBIT THE GROWTH OF FUNGI IN

Gypsum Wallboard: Addition of up to 38,400 ppm of this product (38.4 lbs of product per 1000 lbs of the formulation, i.e., wet slurry) will inhibit the growth of fungi. It can be added at any time during the formulation procedure. For example, to control the growth of fungi in Gypsum & Dry Wall add a minimum of 4000 ppm of this product (4.0 lb. of product per 1000 lbs of formulation).

To Control The Growth Of Fungi In Carrageenan Based Gels Used To Produce Solid Air Fresheners. Add 0.12 - 0.4% of this product (0.12 - 0.4 lb./100 lbs. of formulation). Add this product into the gel formulation prior to cooling.

To Inhibit the Growth of Bacteria and Fungi In Dry Wall and Gypsum, Pearlite, Plaster-Like, Mineral Based, or Cellulose Derived Building Materials Used In the Manufacture of Ceilings, Ceiling Tile, Walls and Partitions: Addition of up to 38400 ppm of this product (38.4 lbs. of product per 1000 lbs. of the formulation, i.e., wet slurry) will inhibit the growth of bacterial and fungi. It can be added at any time during the formulation procedure. Alternatively the product may be added to latex or other types of coating systems routinely applied to the surfaces of walls, ceiling tiles, partitions, etc. at the same dosage as above.

**LEATHER:** Sodium Omadine is used at treatment rates of 0.08% to 4.0%, based on the weight of the leather stock, to prevent the bacterial or fungal degradation of hides and skins. Application level is dependent on the type of hide or leather to be protected, the length of protection desired and the presence of other constituents in the processing formula. The optimum addition should be determined by trial for each individual application. For soaking raw hides this product should be added to the water to be used for soaking. For treating hides cured with dry salt, this product should be applied to the hides or should be mixed with the salt before it is applied to the hides. This product can be used for the protection of wet leather stock such as pickled, chrome, chrome alternative, metal free, and vegetable tanned leathers from mold and mildew during in-tannery wet processing and for the protection of wet-blue during long storage and transportation times. Treatment rates should be calculated based on the wet white weight or wet blue weight, and compatibility with chrome solutions or other treatment chemicals should be confirmed prior to trial.



## SODIUM OMADINE® PRODUCT LICENSING & PATENT NOTICE

The SODIUM OMADINE® product may be used in paints with zinc oxide in accordance with the label and composition and method claimed in U.S. Patent 5,518,774 and European Patent 0807152, and their other corresponding foreign patents. Purchase of this product from Arch Chemicals, Inc. gives the purchaser a nonexclusive license to use this product in the composition and method claimed in the above-mentioned patents, and the royalty for this license is incorporated into the purchase price of the product.

ACCEPTED with COMMENTS EPA Letter Dated:

Under the Federal Insecticide, Fungicide, and Rodenticide Act as registered under EPA Reg. No.