



DIRECTIONS

Remove cap. Point valve opening away from face. Push or press valve button.

FOR TREATING DUSTMOP:

Thoroughly spray the top of the dustmop. Do not spray near the ends. Allow to stand until dry. After dustmop has been used, shake mop vigorously out of doors or onto a sheet of newspaper to release the small accumulated black balls. If fine dust comes out of mop, it is an indication that the mop should be treated again. When mop becomes too soiled, it may be rinsed under a stream of warm water and allowed to dry.

Use sparingly, do not saturate the mop. Ends of mop should not be wet. Follow directions carefully.

FOR DUST CLOTHS: Spray onto cloth from a distance of about 6 inches by moving the aerosol rapidly across the cloth. Fold into several sections and allow to dry. Do not use dust cloth while it is still wet. Dust cloths treated this way may be used to dust furniture, walls, woodwork, table pieces, etc.

When cloths become excessively dirty they may be rinsed out and retreated.

DE WITT®

WITT-O-LITE

BACTERIOSTATIC TREATMENT

For Treating Dus'mops Dust Cloths Air Conditioning Filters

ACTIVE INGREDIENTS: 0.15%

N-alkyl (50% C., 30% C., 17% C., 3% C.)
dimethyl ethylbenzyl ammonium chlorides—0.06%
N-alkyl (60% C., 30% C., 5% C., 5% C.)
dimethyl benzyl ammonium chlorides—0.06%
Isopropanol—0.03%

INERT INGREDIENTS: 99.85%

CAUTION - Flammable KEEP OUT OF REACH OF CHILDREN

Contents Under Pressure
See Side Panel For Additional Precautions

NET CONTENTS. . . 1 Lb. 1 Oz. Av.

MANUFACTURERS OF INDUSTRIAL
MAINTENANCE PRODUCTS

DIRECTIONS

FILTER CLEANING AND COATING: Tap filter gently to remove loose dirt. Wash with stream of water, preferably hot, applied to dirty side of filter. Flush out dirt and old filter spray. Shake off excess water. Allow to dry.

Direct WITT-O-LITE spray to inlet side of cleaned filter. Coat liberally, but avoid excess which causes run or drip. For best odor removal, coat both sides of filter. Be sure filters are thoroughly dry before applying WITT-O-LITE.

CAUTION

Harmful or fatal if swallowed
Flammable.
Contains Petroleum Distillate
Contents under pressure. Store below 120°F. Do not puncture can. Do not throw into fire or incinerator. Do not use near open flame.

U.S.D.A. Reg. No. 1269-72

Atlanta
Georgia 30301

DE WITT
CHEMICAL COMPANY

St. Louis
Missouri 63043

