



**ZEP X-4974
ALGAECIDE FOR COOLING TOWERS**

ACTIVE INGREDIENTS: 10.0%

Poly[oxyethylene(dimethyliminio)ethylene(dimethyl-
iminio)ethylene dichloride].....10.0%

INERT INGREDIENTS:.....90.0%

Weight per gallon.....8.49 Pounds

Weight of active ingredient per gallon.....0.85 Pounds

DIRECTIONS:

This product is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algae growth, microbiological slime and other deposits. An initial slug addition of 6.2 to 15.4 fluid ounces of product per 1,000 gallons of water to provide a concentration of 48 to 120 parts per million of product based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 1.6 to 15.4 fluid ounces of product per 1,000 gallons of water (12 to 120 parts per million of product) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CAUTION

KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Do not get in eyes. Avoid contact with skin. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food.

This product is toxic to fish. Do not discharge treated effluent where it will drain into lakes, streams, or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Use only as directed on label.

Do not re-use empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

E.P.A. REG. NO. 1270-173

E.P.A. EST. NO. 1270-GA-1

ZEP MANUFACTURING COMPANY

Division of National Service Industries, Inc.

ATLANTA, GEORGIA 30301

PRINCIPAL CITIES, USA AND THROUGHOUT THE WORLD