PENTAchlorophenol

PENETRATING, NON-PAINTABLE PRESERVATIVE FOR WOOD AND TREATMENT FOR SOIL

CONCENTRATE - CLEAR

BEFORE USING DILUTE BY ADDING 10 PARTS FUEL OIL OR DIESEL OIL TO 1 PART CONCENTRATE

WARNING! COMBUSTIBLE! KEEP OUT OF REACH OF CHILDREN. KEEP AWAY FROM HEAT OR OPEN FLAME. HARMFUL OR FATAL IF SWALLOWED OR

ABSORBED THROUGH SKIN.
Contains Petroleum Distillate. Keep contents and freshly treated articles away from flame, food and living plants. Do not use, pour, spill or store near heat or open flame. Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place away from water supplies.

Causes skin irritation. Do not breathe vapor or spray mist. Do not get in eyes or on skin or clothing. Use only in well ventilated area.

Wear rubber gloves and protective clothing when handling the freshly treated lumber. Not for use or storage in or around the home.

This product is toxic to fish and wildlife. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this product only as specified on this label.

FIRST AID: External — Wash with soap and water. Internal — Call a physician immediately. Force vomiting by drinking warm water mixed with a table-spoon of salt, milk or egg white. Lie down and keep

ACTIVE INGREDIENTS: Pentachlorophenol Other Chlorophenols Petroleum Distillates

34.4°.. 4.0″. 60.0

INERT INGREDIENTS

warm.

1.6%

*Equivalent to 40.0% technical grade pentachlorophenol in accordance with Fed. Spec. TT-W-570.

NOTICE: SELLER MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, IN LAW OR IN FACT, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR USE, except that specifically set forth on this label. Buyer assumes all risks of use, handling or storage of this product when such use, handling or storage is not in strict accordance with the provisions of this label.

Manufactured by

Roberts Consolidated Industries

Subsidiary of Champion International CITY OF INDUSTRY, CA. 91749

EPA Est. No. 1409 MI-1 EPA Reg. No. 1409-7 Made in U.S.A./Printed in U.S.A.

Net Contents: 55 Gallons U.S. Measure (208.2 Liters)

DO NOT REUSE CONTAINER — DESTROY WHEN EMPTY

SEP 2 6 1975

Undon the Federal Insecticide,
Puncticide, and Rodenticide Act,
Puncticide, and Rodenticide Act,
as amanded, for the pessicide
registered under
PA Req. No.

DIRECTIONS (After Dilution)

DESCRIPTION: 10-1 concentrate wood preservative. For any wood not to be painted, varnished or finished. Protects against decay, termites, carpenter ants, mold, powder post beetles and mildew.

APPLICATION: Use only at 40°F. (4.4°C) surrounding temperatures, or above. Non-commercial users can apply by soak, dip, brush or low pressure flooding spray. Commercial users can use hot-cold soaking, pressure and vacuum processes. Treat after cutting and machining whenever possible. Re-treat newly cut surfaces with several liberal brush applications. For fenceposts and wood to be in contact with soil, wood should be dry and free from outer and inner bark and soaked 24-48 hours vertically with buttlends down. Oil drums welded together make excellent treating tanks.

TERMITE CONTROL: For new construction, treat all new wood with Penta. Immerse lumber less than 1 inch thick for 3 minutes and at least 5 minutes for each additional inch of thickness. Treat soil (see below). For old construction, replace badly eaten wood with Penta-treated wood. Apply Penta by brush or flooding spray to all exposed wood surfaces. All cutting, boring, etc., should be done before treating. Treat soil (see below).

SOIL TREATMENT: For hollow block foundations, dig a trench 30 inches deep, but not below the top of the footing, if it is shallower. Apply Penta at the rate of 5 gal./10 linear feet of trench in trenches up to 15 inches deep, at the rate of 10 gal./10 linear feet in deeper trenches. Grass, trees and shrubs within 3 feet of the trench should be removed or protected with tar paper.

For wood to be painted: Use WOODLIFE paintable water repellent wood preservative.

CLEAN-UP: Use mineral spirits to clean immersion tanks, spray equipment and surrounding area.