

MARINE WOODLIFE®

Contains Copper Naphthenate

WATER REPELLENT PRESERVATIVE FOR WOOD

ACCEPTED

NOV 25 1975

Approved by the Federal Insecticide,
Fungicide, and Rodenticide Act.
Registered under
EPA Reg. No. 1409-13

CONCENTRATE - MARINE

BEFORE USING DILUTE BY ADDING
2 PARTS MINERAL SPIRITS TO
1 PART CONCENTRATE

CAUTION!

COMBUSTIBLE!

KEEP OUT OF REACH OF CHILDREN.
KEEP AWAY FROM HEAT OR OPEN FLAME.
HARMFUL OR FATAL IF SWALLOWED OR
ABSORBED THROUGH SKIN.

Contains Petroleum Distillate. Keep contents and freshly
treated articles away from flame, food and living plants.
Do not use, pour, spill or store near heat or open flame.
Do not reuse empty drum. Return to drum reconditioner
or destroy by perforating or crushing and burying in a
safe place away from water supplies.

Causes skin irritation. Do not breathe vapor or spray
mist. Do not get in eyes or on skin or clothing. Use
only in well ventilated area. Not for use or storage in
or around the home.

This product is toxic to fish. Keep out of lakes,
streams or ponds. Do not contaminate water by
cleaning of equipment or disposal of waste. Apply
this product only as specified on this label.

FIRST AID:

External — Wash with soap and
water. Internal — Call a physician immediately. Force
vomiting by drinking warm water mixed with a table-
spoon of salt, milk or egg white. Lie down and keep
warm.

ACTIVE INGREDIENTS:

Copper Naphthenate 34.6%
(Equiv. to 2.6% metallic copper)

INERT INGREDIENTS 65.4%

TOTAL 100.0%

MEETS FED. SPEC. TT-W-572B, COMPOSITION B

NOTICE: SELLER MAKES NO WARRANTIES, EXPRESSED
OR IMPLIED, IN LAW OR IN FACT, INCLUDING THE WAR-
RANTIES OF MERCHANTABILITY AND FITNESS FOR PAR-
TICULAR USE, except that specifically set forth on this
label. Buyer assumes all risks of use, handling or storage
of this product when such use, handling or storage is not
in strict accordance with the provisions of this label.

Manufactured by



Roberts Consolidated Industries

Subsidiary of Champion International

CITY OF INDUSTRY, CA. 91749

Net Contents: 55 Gallons
U.S. Measure
(208.2 Liters)

DO NOT REUSE CONTAINER — DESTROY WHEN EMPTY

EPA Est. No. 1409-MI-1
EPA Reg. No. 1409-13
Made in U.S.A./Printed in U.S.A.

DIRECTIONS

DESCRIPTION: MARINE WOODLIFE is a penetrating,
non-swelling, paintable, water repellent preservative
for wood. Protects against wood destroying fungi,
staining fungi and dimensional change.

PRODUCT USES: Boats, docks, piers, structural lum-
ber, all lumber and wood products in a marine en-
vironment.

RETENTION: 3 minute immersion — 5-10 gallons
per MBM. 30 minute immersion — 10-15 gallons per
MBM. 24 hour immersion — 15-25 gallons per MBM.
Brush application — 150 sq. ft. per gallon, but varies
by species and condition of wood.

PREPARATION: Machine, cut, glue and sand wood,
as desired, before treating. Do not use over previ-
ously finished or stained wood without stripping off
old finish. Wood must be clean and dry. Do not use
steel wool. Keep solution and freshly treated wood
away from plastics and asphalt products. Fence
posts, foundation timbers and heavy wood members
should be free of bark, dry and well-seasoned.

APPLICATION: Use only at 40°F. (4.4°C) surround-
ing temperature or above. Apply by immersion, roller
coater, flood spray or brush.

IMMERSION: Items to be painted or finished, im-
merse for 3 minutes. Plywood for 30 seconds. Wood
to be in contact with soil, immerse 24 hours, posts
48 hours.

FINISHING: Before finishing, treatment should be
completely dry and odor free. Allow at least 48 hours
under average temperature and humidity conditions.
Can be heat-dried for plant production. Use a sealer
such as shellac before using lacquers. Green color
may bleed through first coat of white paint, but finish
coats will cover.

CLEAN-UP: Use mineral spirits to clean immersion
tanks and surrounding area. Lacquer thinner may be
required to remove dried MARINE WOODLIFE from
floors and equipment.

BEST AVAILABLE COPY

PM 21
1409-13
181