

Precautionary Statements: Hazards to Humans and Domestic Animals

Danger: May be fatal if swallowed, inhaled, or absorbed through skin. Do not get in eyes, on skin or on clothing. Causes delayed chemical burns. Do not taste internally. Avoid breathing vapors, spray mist, or dust. Use with adequate ventilation. Wash thoroughly after skin contact and before eating, drinking, use of tobacco products, or using restrooms.

The U.S. EPA has determined that pentachlorophenol can produce defects in the offspring of laboratory animals. Exposure to pentachlorophenol during pregnancy should be avoided.

Avoid breathing vapors. If inhalation of vapors cannot be avoided, applicators must wear a properly fitting, well-maintained half-mask canister or cartridge respirator which is NIOSH/NIOSH-approved for polynuclear aromatic and organic vapors.

Applicators must wear gloves impervious to the wood treatment formulation in all situations where dermal contact is expected (for example, during the actual application process and when handling freshly treated wood).

Spray applicators must wear protective clothing (including overalls, jacket, gloves, boots, and head covering) impervious to the wood treatment formulation, and a respirator and goggles when spraying.

Applicators who apply pentachlorophenol by other application processes (e.g., brush and wash) must wear long sleeved shirts, long pants and an impervious apron. Launder work clothing separately from other household laundry.

Protective clothing must be changed when it shows signs of contamination. Launder non-disposable protective clothing separately from other household clothing. Dispose of worn-out protective clothing and soles of boots in any general landfill. In the trash, or in any other manner approved for pesticide disposal.

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation.

Do not apply where there may be direct contact with domestic animals or livestock, and where there may be contamination of food, feed, or drinking and irrigation water.

Do not apply pentachlorophenol to wood intended for farrowing or brooding facilities.

Do not apply pentachlorophenol to wood intended to be used in the interiors of farm buildings where there may be direct contact with domestic animals or livestock which may drink from or lick the wood. Pentachlorophenol may be used to treat wood intended to be used in the exterior of farm buildings where domestic animals or livestock are unlikely to lick or lick the wood. If the coats of an appropriate sealer will be applied. Sealers may be applied at the installation site.

Do not apply to wood intended to be used in a manner in which the preservative may become a component of food or animal feed. Examples of such sites would be structures or containers for storing silage or food.

Do not use this product to treat wood intended to be used for cutting boards or counter tops.

Do not use this product to treat wood intended for construction of those sections of beehives which may come into contact with the honey.

Do not use this product to treat wood intended for use where it may come into direct or indirect contact with drinking water for the public and domestic animals or livestock except for those uses involving incidental contact such as docks and bridges.


Wood to be treated with this product should be cut to size before treatment. If it is necessary to saw or machine wood after treatment, wear goggles to protect the eyes from flying particles and a dust mask to avoid breathing dust from the treated wood. If oily preservatives or sealers accumulate on clothes, launder before re-use. Wash work clothes separately from other household laundry.

Contact with treated surfaces should be avoided even after the preservative has dried. When handling treated wood wear long-sleeved shirts, long pants and impervious gloves (e.g., vinyl coated). Wash exposed skin thoroughly after contact with treated wood and before eating, drinking or using tobacco products.

This product should not be used to treat wood which will be in frequent contact with skin, unless the wood will be treated with an effective sealer.

NOTE TO USER: As used on this label, the term "respirators" means properly fitting, well-maintained, half-mask canister or cartridge respirators which are NIOSH/NIOSH-approved for polynuclear aromatic and organic vapors. Examples of acceptable materials for protective clothing (e.g., gloves, overalls, jackets, and boots) required during application and handling of wood are polyvinyl acetate (PVA), polyurethane, neoprene, and MB (butyl). Hexane, latex, epoxy enamel, urethane, and urea are acceptable sealers for all pentachlorophenol-treated wood.

4247A



RESTRICTED USE PESTICIDE.
For sale to and use only by certified applicators or by persons under their direct supervision and only for those uses covered by the certified applicators' certification.

Weldwood®
WOODLIFE®
WOOD PRESERVATIVE
WATER REPELLENT PRESERVATIVE FOR WOOD
READY TO USE — CLEAR

KEEP OUT OF REACH OF CHILDREN.
DANGER!
KEEP AWAY FROM HEAT OR OPEN FLAME.
Contains PETROLEUM SPIRITS. Keep contents and freshly treated articles away from flame, food and living plants.

Storage and Disposal
Do not contaminate water, food, or feed by storage or disposal.

Pesticide disposal: Pesticide wastes are toxic. Proper disposal of excess pesticide, spray mixture, or sludge is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the nearest waste representative at the nearest EPA Regional Office for guidance.

Container disposal: (Consult with FR Notice 83-) for appropriate language for non-hazardous container disposal.

Treated wood disposal: Wood which has been treated with this product should be disposed of by burial or ordinary trash collection. Do not burn treated wood in an open fire or in stoves or fireplaces because toxic chemicals may be produced as part of the smoke and ashes.

- EPA Reg. No. 1409-144
- EPA Est. No. 1409-MI-1
- EPA Est. No. 1409-TX-1
- EPA Est. No. 1409-WA-1
- EPA Est. No. 1409-PA-1
- EPA Est. No. 1409-GA-1

Manufactured by
Beecham Home Improvement Products Inc.
DAYTON, OHIO 45401
FOR INDUSTRIAL USE ONLY

Statement of Practical Treatments

If swallowed: Call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.
If in eyes: Flush with plenty of water. Get medical attention.
If on skin: Wash with plenty of soap and water. Get medical attention.
If inhaled: Remove victim to fresh air. Get medical attention.
NOTE TO PHYSICIAN: This product is a metabolic stimulant. Causes hyperkalemia. Treat symptomatically.

ACTIVE INGREDIENTS:	
*Pentachlorophenol	4.3%
Other Chlorophenols5%
INERT INGREDIENTS	95.2%
TOTAL	100.0%
*Equivalent to 5.0% technical grade pentachlorophenol in accordance with Fed. Spec. TT-W-570.	
MEETS FED. SPEC. TT-W-572B COMPOSITION A INDUSTRIAL STANDARD IS-4-70	

IMPORTANT NOTICE TO PURCHASER
Buyer assumes all risk of use, handling and storage of product not in strict accordance with label directions. No express warranties are given. Should defect occur, Seller's sole liability is to replace product or refund purchase price. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR USE IS LIMITED TO ONE YEAR FROM DATE OF PURCHASE. LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGE OR LOSS IS SPECIFICALLY EXCLUDED AT ALL TIMES. If used for other than personal, family or household purposes, any implied warranty of MERCHANTABILITY or FITNESS FOR PARTICULAR USE is excluded.

Roberts Consolidated Industries
Stock No. ...
Net Contents: 55 U.S. Gallons (208.2 Liters)
Made in U.S.A./Printed in U.S.A.

A C

Under Fungus as am registe EPA R

Apply this product is a violation of F manner inconsis

DESCRIPTION: Water non-swelling, pair for wood. It prote brown or white ro surface mold (like mildew) and d'me

PRODUCT USES: doors, structural ture.

Do not apply in interior locations except for treat the wall in areas, stabi door of insect infestat (e.g., doorframes, window treated wood should be e Sealers may be applied at

RETENTION: 3-mi MBM. 30-minute MBM. 24-hour im Brush application by species and co

PREPARATION: M as desired before ously finished or old finish. Do no clean and dry. H wood away from Fence posts, four members should seasoned.

APPLICATION: T rounding air mus immersion, Dri Va or brush. Any sur be retreated. For tions under "IMM

IMMERSION: Mill — 3 minutes for onds for plywood parts. Treatment dustrial Standard soil — immerse 2

FINISHING: Befo treatment should Allow 24-48 hour humidity conditio ductivity. Use a se lacquers.

CLEAN-UP: Use tanks, spray equi quer thinner m WOODLIFE from