ACCEPTED

MAR 1 2 1986

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 1409-21

1 of 1
Pmcl
1409-21

EPA-PR

Precautionary Statements: Hazards to Humans and Domestic Animals

Danger: May be fatal if swallowed, inhaled, or absorbed through skin. Do not get in eyes, on skin or on clothing. Causes delayed chemical burns. Do not take internally. Avoid breathing vapors, spray mist, or dust. Use with adequate ventilation. Wash thoroughly after skin contact, and before eating, drinking, use of tobacco products, or using restrooms.

The U.S. EPA has determined that pentachlorophenol can produce defects in the offspring of laboratory animals. Exposure to pentachlorophenol during pregnancy should be avoided.

Avoid inhaling vapors. If inhalation of vapors cannot avoided, applicators must wear a properly fitting, well-maintained half-mask canister or cartridge respirator which is NSHA/NIOSH-approved for polynuclear aromatics and organic vapors.

Applicators must wear gloves impervious to the wood treatment formulation in all situations where dermal contact is expected (for example, during the actual application process and when handling freshly treated wood).

Spray applicators must wear protective clothing (including overalls, jackets, gloves, boots, and head covering) impervious to the wood treatment formulation, and a respirator and goggles when spraying.

Applicators who apply pentachlorophenol by other application processes (e.g., brush on) must wear long sleeved shirts, long pants and an impermable apron. Launder work clothing separately from other household laundry.

Protective clothing must be changed when it shows signs of contamination. Launder non-disposable protective clothing separately from other household clothing. Dispose of worn-out protective clothing and waterproof or boots in any general landfill, in the trash, or in any other manner approved for pesticide disposal.

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation.

Do not apply where there may be direct contact with domestic animals or livestock, and where there may be contamination of food, feed, or drinking and irrigation water.

Do not apply pentachlorophenol to wood intended for farrowing or brooding facilities.

Do not apply pentachlorophenol to wood intended to be used in the interiors of farm building where there may be direct contact with domestic animals or livestock which may crib, bite, or lick the wood. Pentachlorophenol may be use to treat wood intended to be used in interiors of farm building where domestic animals or livestock are unlikely to crib or lick the wood, if two coats of an appropriate sealer will be applied. Sealers may be applied at the installation site.

Do not apply to wood intended to be used in a manner in which the preservative may become a component of food or animal feed. Examples of such sites would be structures or containers for storing silage or food.

Do not use this product to treat wood intended to be used for cutting boards or counter tops.

Do not use this product to treat wood intended for construction of those portions of beehives which may come into contact with the honey.

Do not use this product to treat wood intended for use where it may come into direct or indirect contact with drinking water for the public and domestic animals or livestock except for those uses involving incidental contact such as docks and bridges.

Wood to be treated with this product should be cut to size before treatment. If it is necessary to saw / machine wood after treatment, wear goggles to protect the eyes from flying particles and a dust mask to avoid inhaling sawdust from the treated wood. If only preservatives or sawdust accumulate on clothes, launder before re-use. Wash work clothes separately from other household laundry.

Contact with treated surfaces should be avoided even after the preservative has dried. When handling treated wood wear long-sleeved shirts, long pants and impervious gloves (e.g., vinyl coated). Wash exposed skin thoroughly after contact with treated wood and before eating, drinking or using tobacco products.

This product should not be used to treat wood which will be in frequent with skin, unless the wood will be treated with an effective sealer.

NOTE TO USER: As used on this label, the term "respirators" means properly fitting, well-maintained, half-mask canister or cartridge respirators which are NSHA/NIOSH-approved for polynuclear aromatics and organic vapors. Examples of acceptable materials for protective clothing (e.g., gloves, overalls, jackets, and hoods) required during application and handling of creosote are polyvinyl alcohols (PVA), polyvinyl chloride (PVC), neoprene, and NBR (Buna-N). Urethane, latex epoxy enamel, shellac, and varnish are acceptable sealers for all pentachlorophenol-treated wood.

RESTRICTED USE PESTICIDE

For sale to and use only by certified applicators or by persons under their direct supervision and only for those uses covered by the certified applicators' certification.

Weldwood®

WRP-146

WATER REPELLENT PRESERVATIVE FOR WOOD

READY TO USE – CLEAR

KEEP OUT OF REACH OF CHILDREN.

DANGER!

KEEP AWAY FROM HEAT OR OPEN FLAME.

Contains PETROLEUM SPIRITS. Keep contents and freshly treated articles away from flame food and living plants.

Storage and Disposal

Do not contaminate water, food, or feed by storage or disposal.

Pesticide disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container disposal: (Consult with PR Notice 83-3 for appropriate language for non-home container disposal).

Treated wood disposal: Wood which has been treated with this product should be disposed of by burial or ordinary trash collection. Do not burn treated wood in an outdoor fire or in stoves or fireplaces because toxic chemicals may be produced as part of the smoke and ashes.

Statement of Practical Treatments

If swallowed: Call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.
If in eyes: Flush with plenty of water. Get medical attention.
If on skin: Wash with plenty of soap and water. Get medical attention.
If inhaled: Remove victim to fresh air. Get medical attention.

NOTE TO PHYSICIAN: This product is a metabolic stimulant. Causes hyperthermia. Treat symptomatically.

ACTIVE INGREDIENTS:

*Pentachlorophenol	4.3%
Other Chlorophenols	.5%
INERT INGREDIENTS	95.2%
TOTAL	100.0%

*Equivalent to 5.0% technical grade pentachlorophenol in accordance with Fed. Spec. TT-W-570.

MEETS FED. SPEC. TT-W-572B COMPOSITION A
INDUSTRIAL STANDARD IS-4-70

IMPORTANT NOTICE TO PURCHASER

Buyer assumes all risk of use, handling and storage of product not in strict accordance with label directions. No express warranties are given. Should defect occur, Seller's sole liability is to replace product or refund purchase price. ☐ ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR USE IS LIMITED TO ONE YEAR FROM DATE OF PURCHASE. LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGE OR LOSS IS SPECIFICALLY EXCLUDED AT ALL TIMES. ☐ If used for other than personal, family or household purposes, any implied warranty of MERCHANTABILITY or FITNESS FOR PARTICULAR USE is excluded.

EPA Reg. No. 1409-21
EPA Est. No. 1409-MI-1 ☐
EPA Est. No. 1409-TX-1 ☐
EPA Est. No. 1409-WA-1 ☐
EPA Est. No. 1409-PA-1 ☐
EPA Est. No. 1409-GA-1 ☐

Manufactured by
Beecham Home Improvement Products Inc.
DAP
DAYTON, OHIO 45401

Roberts Consolidated Industries

Stock No.

Net Contents: 55 U.S. Gallons (208.2 Liters)

FOR INDUSTRIAL USE ONLY

Made in U.S.A./Printed in U.S.A.

DIRECTIONS

Apply this product only as specified on this label. It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

DESCRIPTION: WOODLIFE is a clean, penetrating, non-swelling, paintable, water repellent preservative for wood. It protects wood against decay fungi (like brown or white rot), staining fungi (like blue stain), surface mold (like a black, brown or other colored mildew) and dimensional change.

PRODUCT USES: Millwork, shingles, siding, windows, doors, structural lumber, fences and outdoor furniture.

Do not apply in interiors. Do not apply to wood intended for use in interiors except for those support structures which are in contact with the soil in barns, stables, and similar sites and which are subject to decay or insect infestation; and millwork which has outdoor surfaces (e.g., doorframes, windows and patio frames). Interior surfaces of the treated wood should be sealed with two coats of an appropriate sealer. Sealers may be applied at the installation site.

RETENTION: 3-minute immersion — 5-10 gallons per MBM. 30-minute immersion — 10-15 gallons per MBM. 24-hour immersion—15-25 gallons per MBM. Brush application — 150 sq. ft. per gallon; but varies by species and condition of wood.

PREPARATION: Machine cut, glue and sand wood as desired before treating. Do not use over previously finished or stained wood without stripping off old finish. Do not use steel wool. Wood must be clean and dry. Keep solution and freshly treated wood away from plastics and asphalt products. Fence posts, foundation timbers and heavy wooden members should be free of bark, dry and well-seasoned.

APPLICATION: Treating solution, wood and surrounding air must be above 40°F (4.4°C). Apply by immersion, Dri Vac vacuum, roller coater, flood spray or brush. Any surface cut after first treatment should be retreated. For wood in contact with soil, see directions under "IMMERSION" below.

IMMERSION: Millwork or other items to be painted — 3 minutes for batch or bundle treating, 30 seconds for plywood, 15 seconds for treating individual parts. Treatment should be in accordance with Industrial Standard 4-70. Wood to be in contact with soil — immerse 24 hours; posts for 48 hours.

FINISHING: Before glazing, painting or varnishing treatment should be completely dry and odor-free. Allow 24-48 hours under average temperature and humidity conditions. Can be heat-dried for plant production. Use a sealer such as shellac before using lacquers.

CLEAN-UP: Use mineral spirits to clean immersion tanks, spray equipment and surrounding area. Lacquer thinner may be required to remove dried WOODLIFE from floors and equipment.