


ACCEPTED
 SEP 20 1975
 Under the Federal Insecticide,
 Fungicide, and Rodenticide Act,
 as amended, for the pesticide
 registered under
 EPA Reg. No. 1409 ME 1



MARINE WOODLIFE®

Contains Copper Naphthenate

WATER REPELLENT PRESERVATIVE FOR WOOD

READY TO USE — MARINE

DO NOT DILUTE

CAUTION! COMBUSTIBLE!
 KEEP OUT OF REACH OF CHILDREN.
 KEEP AWAY FROM HEAT OR OPEN FLAME.
 HARMFUL OR FATAL IF SWALLOWED OR
 ABSORBED THROUGH SKIN.
 Contains Petroleum Distillate. Keep contents and freshly
 treated articles away from flame, food and living plants.
 Do not use, pour, spill or store near heat or open flame.
 Do not reuse empty drum. Return to drum conditioner
 or destroy by perforating or crushing and burying in a
 safe place away from water supplies.

Causes skin irritation. Do not breathe vapor or spray
 mist. Do not get in eyes or on skin or clothing. Use
 only in well ventilated area. Not for use or storage in
 or around the home.
 This product is toxic to fish. Keep out of lakes,
 streams or ponds. Do not contaminate water by
 cleaning of equipment or disposal of waste. Apply
 this product only as specified on this label.

FIRST AID: External — Wash with soap and
 water. Internal — Call a physician immediately. Force
 vomiting by drinking warm water mixed with a table
 spoon of salt, milk or egg white. Lie down and keep
 warm.

ACTIVE INGREDIENTS:	
Copper Naphthenate	13.0%
(Equiv. to 1.0% metallic copper)	
INERT INGREDIENTS	87.0%
TOTAL	100.0%

Conforms to TT-W 572B, Composition B.

NOTICE: SELLER MAKES NO WARRANTIES, EXPRESSED
 OR IMPLIED, IN LAW OR IN FACT, INCLUDING THE WAR-
 RANTIES OF MERCHANTABILITY AND FITNESS FOR PAR-
 TICULAR USE, except that specifically set forth on this
 label. Buyer assumes all risks of use, handling or storage
 of this product when such use, handling or storage is not
 in strict accordance with the provisions of this label.

DIRECTIONS

DESCRIPTION: MARINE WOODLIFE is a penetrating,
 non-swelling, paintable, water repellent preservative
 for wood. Protects against wood destroying fungi,
 staining fungi and dimensional change.

PRODUCT USES: Boats, docks, piers, structural lum-
 ber, all lumber and wood products in a marine en-
 vironment.

RETENTION: 3 minute immersion — 5-10 gallons
 per MBM. 30 minute immersion — 10-15 gallons per
 MBM. 24 hour immersion — 15-25 gallons per MBM.
 Brush application — 150 sq. ft. per gallon, but varies
 by species and condition of wood.

PREPARATION: Machine, cut, glue and sand wood,
 as desired, before treating. Do not use over previ-
 ously finished or stained wood without stripping off
 old finish. Wood must be clean and dry. Do not use
 steel wool. Keep solution and freshly treated wood
 away from plastics and asphalt products. Fence
 posts, foundation timbers and heavy wood members
 should be free of bark, dry and well-seasoned.

APPLICATION: Use only at 40°F. (4.4°C) surround-
 ing temperature or above. Apply by immersion, roller
 coater, flood spray or brush.

IMMERSION: Items to be painted or finished, im-
 merse for 3 minutes. Plywood for 30 seconds. Wood
 to be in contact with soil, immerse 24 hours, posts
 48 hours.

FINISHING: Before finishing, treatment should be
 completely dry and odor free. Allow at least 48 hours
 under average temperature and humidity conditions.
 Can be heat-dried for plant production. Use a sealer
 such as shellac before using lacquers. Green color
 may bleed through first coat of white paint, but finish
 coats will cover.

CLEAN-UP: Use mineral spirits to clean immersion
 tanks and surrounding area. Lacquer thinner may be
 required to remove dried MARINE WOODLIFE from
 floors and equipment.

Manufactured by
 **Roberts Consolidated Industries**
 Subsidiary of Champion International
 CITY OF INDUSTRY, CA 91749
 Net Contents: 55 Gallons
 U.S. Measure
 (208.2 Liters) **DO NOT REUSE CONTAINER — DESTROY WHEN EMPTY**
 EPA Est. No. 1409 ME 1
 EPA Reg. No. 1409 ME 1
 Made in U.S.A. / Printed in U.S.A.

ACCEPTED

SEP 26 1975

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 74071-277

WOODLIFE®

Contains Pentachlorophenol

WATER REPELLENT PRESERVATIVE FOR WOOD

READY TO USE - BLACK

DO NOT DILUTE

WARNING! COMBUSTIBLE!

KEEP OUT OF REACH OF CHILDREN. KEEP AWAY FROM HEAT OR OPEN FLAME. HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN.

Contains Petroleum Distillate. Keep contents and freshly treated articles away from flame, food and living plants. Do not use, pour, spill or store near heat or open flame. Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place away from water supplies.

Causes skin irritation. Do not breathe vapor or spray mist. Do not get in eyes or on skin or clothing. Use only in well-ventilated area.

Wear rubber gloves and protective clothing when handling the freshly treated lumber. Not for use or storage in or around the home.

This product is toxic to fish and wildlife. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this product only as specified on this label.

FIRST AID: External — Wash with soap and water. Internal — Call a physician immediately. Force vomiting by drinking warm water mixed with a tablespoon of salt, milk or egg white. Lie down and keep warm.

ACTIVE INGREDIENTS:	
Pentachlorophenol	4.3%
Other Chlorophenols	.5%
INERT INGREDIENTS	95.2%
TOTAL	100.0%

Equivalent to 5.0% technical grade pentachlorophenol in accordance with Fed. Spec. TT-W-570.

MEETS FED. SPEC. TT-W-572B COMPOSITION A INDUSTRIAL STANDARD IS-470

NOTICE: SELLER MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, IN LAW OR IN FACT, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR USE, except that specifically set forth on this label. Buyer assumes all risks of use, handling or storage of this product when such use, handling or storage is not in strict accordance with the provisions of this label.

Manufactured by



Roberts Consolidated Industries

Subsidiary of Champion International

CITY OF INDUSTRY, CA. 91749

Net Contents: 55 Gallons
U.S. Measure
(208.2 Liters)

DO NOT REUSE CONTAINER — DESTROY WHEN EMPTY

EPA Est. No. 1409-MI-1
EPA Reg. No. 1409-27
Made in U.S.A./Printed in U.S.A.

DIRECTIONS

DESCRIPTION: WOODLIFE Black is a clean, penetrating, non-swelling, paintable, water repellent preservative for wood. It protects against wood destroying fungi, staining fungi and dimensional change.

PRODUCT USES: Millwork, shingles, siding, structural lumber, fences, outside furniture, all lumber and wood products. Do not use on interior surfaces which are not to be finished.

RETENTION: 3-minute immersion — 5-10 gallons per MBM. 30-minute immersion — 10-15 gallons per MBM. 24 hours immersion — 15-25 gallons per MBM. Brush application — 150 sq. ft. per gallon; but varies by species and condition of wood.

PREPARATION: Machine cut, glue and sand wood, as desired, before treating. Do not use over previously finished or stained wood without stripping off old finish. Wood must be clean and dry. Do not use steel wool. Keep solution and freshly treated wood away from plastics and asphalt products. Fence posts, foundation timbers and heavy wooden members should be free of bark, dry and well seasoned.

APPLICATION: Use only at 40°F (4.4°C) surrounding temperature, or above. Apply by immersion, Dri-Vac vacuum, roller coater, flood spray or brush. For application by roller, spray or brush, two successive coats should be applied to all wood to be in contact with soil. Apply second coat before first coat is completely dry.

IMMERSION: Millwork or other items to be painted — 3 minutes for batch or bundle treating, 30 seconds for plywood, 15 seconds for treating individual parts. Treatment should be in accordance with Industrial Standard 470. Wood to be in contact with soil, immerse 24 hours, posts for 48 hours.

FINISHING: Before glazing, painting or varnishing, treatment should be completely dry and odor free. Allow 24-48 hours under average temperature and humidity conditions. Can be heat dried for plant production. Use a sealer such as shellac before using lacquers.

CLEAN-UP: Use mineral spirits to clean immersion tanks, spray equipment and surrounding area. Lacquer thinner may be required to remove dried WOODLIFE from floors and equipment.