

LIFEPRIME® REDWOOD

**PENETRATING, PAINTABLE
WATER REPELLENT PRESERVATIVE, PRIMER FOR WOOD**

CONCENTRATE
BEFORE USING DILUTE BY ADDING
4 PARTS MINERAL SPIRITS TO
1 PART CONCENTRATE

WARNING!

KEEP OUT OF REACH OF CHILDREN. HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN.

Contains Ethylene Distillate. Keep contents and recently treated articles away from flame, food and living plants. Do not use, pour, spill or store near heat or open flame.

Causes skin irritation. Do not breathe vapor or spray mist. Do not get in eyes or on skin or clothing. Use only in well ventilated area.

Wear rubber gloves and protective clothing when handling the freshly treated lumber. Not for use or storage in or around the home.

This product is toxic to fish and wildlife. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of waste.

ANTIDOTE:

External: Wash with soap and water.
Internal: Call a physician immediately. Force vomiting by drinking warm water mixed with a tablespoon of salt, milk or egg white. Lie down and keep warm.

Active ingredients:

Pentachlorophenol	30%
Tributylphenol	58%
Other chlorophenols	2%

Total active 90%

Inert ingredients:

Inert chlorophenols	8%
Other inert	2%

Total inert 10%

14 D equivalent to 11.6 technical grade pentachlorophenol in accordance with Fed. Spec. 11W-570

NOTICE: SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, BY LAW OR IN FACT, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR USE, except that are clearly set forth on this label. Buyer assumes all risk of use, handling or storage of this product when such use, handling or storage is not in strict accordance with the provisions of this label.

CHEMWARE

MINERAL CHEMICAL PRODUCTS

Net Contents: 55 Gallons
U.S. Measure

DO NOT REUSE CONTAINER — DESTROY WHEN EMPTY

EPA Reg. No. 1409-26

Printed in U.S.A.

DIRECTIONS

DESCRIPTION: A penetrating, paintable, non-swelling, pigmented water repellent preservative stain for wood. (If Concentrate see dilution directions on left panel.)

PRODUCT USE: Formulated especially for dip application of wood products such as fences, posts, guard rails, siding, shakes, etc.

PREPARATION: Machine, cut, glue and sand wood as desired before treating. For proper penetration, wood must be clean and dry (below 20% E.M.C.) and free of previous finish.

APPLICATION: Immersion, brushing or flooding spray. Use at 60°F. or above. Must be agitated during use.

For application by roller, spray or brush, two coats should be applied to all wood to be placed in contact with soil.

RETENTION: 2 minutes immersion — 1 gallon per MCM. Brush or spray — 1 gallon per gallon or 6 1/2 gallons per MCM.

FINISHING: Allow 24-48 hours to dry before finishing — can be used for fire protection.

CLEAN UP: Use mineral spirits to clean immersion tanks, spray equipment and finishing area. Lacquer thinner may be used to remove dried LIFEPRIME from surfaces and equipment.

Cameraman's Note
Poor Copy

1409-26