

USE
FOR
EPA

Precautionary Statements: Hazards to Humans and Domestic Animals

DANGER: May be fatal if swallowed, inhaled, or absorbed through skin. Do not get in eyes, on skin, or on clothing. Causes delayed chemical burns. Do not use internally. Avoid breathing vapors, spray mist, or dust. Use with adequate ventilation. Wash thoroughly after skin contact, and before eating, drinking, use of tobacco products, or using restrooms.

The U.S. EPA has determined that pentachlorophenol can produce defects in the offspring of laboratory animals. Exposure to pentachlorophenol during pregnancy should be avoided.

Avoid inhaling vapors. If inhalation of vapors cannot be avoided, applicators must wear a properly fitting, well-maintained half-mask canister or cartridge respirator which is NIOSH/MSHA-approved for polynuclear aromatics and organic vapors.

Applicators must wear gloves impervious to the wood treatment formulation in all situations where dermal contact is expected (for example, during the actual application process and when handling freshly treated wood).

Spray applicators must wear protective clothing (including overalls, jackets, gloves, boots, and head covering) impervious to the wood treatment formulation, and a respirator and goggles when spraying.

Applicators who apply pentachlorophenol by other application processes (e.g., brush on) must wear long sleeved shirts, long pants and an impervious apron. Launder work clothing separately from other household laundry.

Protective clothing must be changed when it shows signs of contamination. Launder non-removable protective clothing separately from other household clothing. Dispose of worn-out protective clothing and workboots or boots in any general landfill, in the trash, or in any other manner approved for pesticide disposal.

Applicators must not eat, drink, or use tobacco products during these parts of the application process that may expose them to the wood treatment formulation.

Do not apply where there may be direct contact with domestic animals or livestock, and where there may be contamination of food, feed, or drinking and irrigation water.

Do not apply pentachlorophenol to wood intended for farrowing or brooding facilities.

Do not apply pentachlorophenol to wood intended to be used in the interiors of farm buildings where there may be direct contact with domestic animals or livestock which may drink, sniff, or lick the wood. Pentachlorophenol may be used to treat wood intended to be used in interiors of farm buildings where domestic animals or livestock are unlikely to enter or lick the wood. If the coats of an appropriate sealer will be applied, sealers may be applied at the installation site.

Do not apply to wood intended to be used in a manner in which the preservative may become a component of food or animal feed. Samples of such sites would be structures or containers for storing silage or food.

Do not use this product to treat wood intended to be used for cutting boards or counter tops.

Do not use this product to treat wood intended for construction of those portions of beehives which may come into contact with the honey.

Do not use this product to treat wood intended for use where it may come into direct or indirect contact with drinking water for the public and domestic animals or livestock except for those uses involving incidental contact such as docks and bridges.

Wood to be treated with this product should be cut to size before treatment. If it is necessary to saw or machine wood after treatment, wear goggles to protect the eyes from flying particles and a dust mask to avoid breathing sawdust from the treated wood. If oily preservatives or sealants accumulate on clothes, launder before re-use. Wash work clothes separately from other household laundry.

Contact with treated surfaces should be avoided even after the preservative has dried. When handling treated wood wear long-sleeved shirts, long pants and impervious gloves (e.g., vinyl coated). Wash exposed skin thoroughly after contact with treated wood and before eating, drinking or using tobacco products.

This product should not be used to treat wood which will be in frequent with skin, unless the wood will be treated with an effective sealer.

NOTE TO USER: As used on this label, the term "respirators" means properly fitting, well-maintained, half-mask canister or cartridge respirators which are NIOSH/MSHA-approved for polynuclear aromatics and organic vapors. Examples of acceptable materials for protective clothing (e.g., gloves, boots, aprons, and head covering) during application and handling of wood preservatives are polyvinyl acetate (PVA), polyethylene (PE), neoprene, and 28 (Buna-N). Urethane, latex apron, smocks, and overalls are acceptable sealers for all pentachlorophenol-treated wood.

MSHA

**RESTRICTED USE
PESTICIDE**

For sale to and use only by certified applicators or by persons under their direct supervision and only for those uses covered by the certified applicators' certification.

**Weldwood®
WOODLIFE®**

(MILTREAT TYPE-E)

WATER REPELLENT PRESERVATIVE FOR WOOD

READY-TO-USE

**KEEP OUT OF REACH OF CHILDREN.
DANGER!**

KEEP AWAY FROM HEAT OR OPEN FLAME.

Contains PETROLEUM SPIRITS. Keep contents and freshly treated articles away from flame, food and living plants.

Storage and Disposal

Do not contaminate water, food, or feed by storage or disposal.

Pesticide disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or residue is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container disposal: (Consult with EPA Notice 81-3 for appropriate language for non-home container disposal).

Treated wood disposal: Wood which has been treated with this product should be disposed of by burial or ordinary trash collection. Do not burn treated wood in an outdoor fire or in stoves or fireplaces because toxic chemicals may be produced as part of the smoke and ashes.

EPA Reg. No. 1409-30
EPA Est. No. 1409-MI-1
EPA Est. No. 1409-TX-1
EPA Est. No. 1409-WA-1
EPA Est. No. 1409-PA-1
EPA Est. No. 1409-GA-1

Statement of Practical Treatments

If swallowed: Call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.

If in eyes: Flush with plenty of water. Get medical attention.

If on skin: Wash with plenty of soap and water. Get medical attention. If treated: Remove victim to fresh air. Get medical attention.

NOTE TO PESTICIDE: This product is a metabolic stimulant. Causes hyperthermia. Treat symptomatically.

ACTIVE INGREDIENTS:	
Bis (tributyltin) oxide	3%
Pentachlorophenol	1.8%
Other Chlorophenols	2%
INERT INGREDIENTS	97.7%
TOTAL	100.0%

IMPORTANT NOTICE TO PURCHASER

Buyer assumes all risk of use, handling and storage of product not in strict accordance with label directions. No express warranties are given. Should defect occur, Seller's sole liability is to replace product or refund purchase price. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR USE IS LIMITED TO ONE YEAR FROM DATE OF PURCHASE. LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGE OR LOSS IS SPECIFICALLY EXCLUDED AT ALL TIMES. If used for other than personal, family or household purposes, any implied warranty of MERCHANTABILITY or FITNESS FOR PARTICULAR USE is excluded.

Roberts Consolidated Industries

Manufactured by
Beecham Home Improvement Products Inc.
DAYTON, OHIO 45401

FOR INDUSTRIAL USE ONLY

Stock No.
Net Contents: 55 U.S. Gallons
(208.2 Liters)
Made in U.S.A./Printed in U.S.A.

Apply this product or is a violation of Federal manner inconsistent

DESCRIPTION: WOOD non-swelling, paintable for wood. It protects brown or white rot), surface mold (like a mildew) and dimensional

PRODUCT USES: Millwork, doors, structural lumber, etc.

Do not apply in interiors. Do not apply to wood which has been treated with other preservatives (e.g., borates, wood preservatives, etc.). Sealers may be applied at the time of application.

RETENTION: 3-minute immersion, 30-minute immersion, 24-hour immersion. Brush application—1 hour by species and conditions.

PREPARATION: Machine as desired before treatment. If previously finished or stained, sand old finish. Do not use clean and dry. Keep wood away from flames. Fence posts, foundation members should be seasoned.

APPLICATION: Treatment should be done in a well-ventilated area. Immersion air must be used. Dri Vac vacuum or brush. Any surface to be retreated. For wood joints under "IMMERSE"

IMMERSION: Millwork—3 minutes for battens, 15 minutes for plywood, 15 minutes for structural wood. Treatment should meet ASTM Industrial Standard 4-77. Immersion—immerse 24 hours.

FINISHING: Before treatment should be done. Allow 24-48 hours under humidity conditions. Use a sealer. Use a sealer. Use a sealer. Use a sealer.

CLEAN-UP: Use minimum water. Tanks, spray equipment, thinner may be used. WOODLIFE from floor