

105 /
PMA 1
1409-34

ACCEPTED

MAR 12 1986

Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 1409-34

Precautionary Statements: Hazards to Humans and Domestic Animals

Danger: May be fatal if swallowed, inhaled, or absorbed through skin. Do not get in eyes, on skin or on clothing. Causes serious chemical burns. Do not take internally. Avoid breathing vapors, spray mist, or dust. Use with adequate ventilation. Wash thoroughly after skin contact, and before eating, drinking, use of tobacco products, or using cosmetics.

The U.S. EPA has determined that pentachlorophenol can produce defects in the offspring of laboratory animals. Exposure to pentachlorophenol during pregnancy should be avoided.

Avoid inhaling vapors. If inhalation of vapors cannot be avoided, applicators must wear a properly fitting, well-ventilated half-face canister or cartridge respirator which is NIOSH/MSHA-approved for polynuclear aromatics and organic vapors.

Applicators must wear gloves impermeable to the wood treatment formulation. In all situations where direct contact is expected (for example, during the actual application process and when handling freshly treated wood).

Spray applicators must wear protective clothing (including overalls, jackets, gloves, boots, and head covering) impermeable to the wood treatment formulation, and a respirator and goggles when spraying.

Applicators who apply pentachlorophenol by other application processes (e.g., brush and) must wear long-sleeved shirts, long pants and an impermeable apron. Launder work clothing separately from other household laundry.

Protective clothing must be changed when it shows signs of contamination. After non-porous protective clothing separately from other household laundry. Dispose of worn-out protective clothing and containers or boats in an general landfill, in the trash, or in any other manner approved for pesticide disposal.

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation.

Do not apply where there may be direct contact with domestic animals or livestock, and where there may be contamination of food, feed, or drinking and irrigation water.

Do not apply pentachlorophenol to wood intended for furrowing or seeding facilities.

Do not apply pentachlorophenol to wood intended to be used in the structures of farm buildings, where there may be direct contact with domestic animals or livestock which may eat, bite, or lick the wood. Pentachlorophenol may be used to treat wood intended to be used in structures of farm buildings where domestic animals or livestock are unlikely to eat or bite the wood, if the coats of an appropriate sealer will be applied. Sealers may be applied at the installation site.

Do not apply to wood intended to be used in a manner in which the preservative may become a component of food or animal feed. Examples of such sites would be structures or containers for storing silage or food.

Do not use this product to treat wood intended to be used for cutting boards or counter tops.

Do not use this product to treat wood intended for construction of those portions of buildings which may come into contact with the honey.

Do not use this product to treat wood intended for use where it may come into direct or indirect contact with drinking water for the public and domestic animals or livestock except for those uses involving incidental use such as docks and bridges.

Wood to be treated with this product should be cut to size before treatment. If it is necessary to saw or machine wood after treatment, wear glasses to protect the eyes from flying particles and a dust mask to avoid inhaling sawdust from the treated wood. If oily preservatives or sealants accumulate on surfaces, launder before re-use. Launder work clothes separately from other household laundry.

Contact with treated surfaces should be avoided even after the preservative has dried. When handling treated wood wear long-sleeved shirts, long pants and impermeable gloves (e.g., vinyl coated), wash exposed skin thoroughly after contact with treated wood and before eating, drinking or using tobacco products.

This product should not be used to treat wood which will be in frequent with skin, unless the wood will be treated with an effective sealer.

NOTE TO USER: As used on this label, the term "respirators" means properly fitting, well-ventilated, half-face canister or cartridge respirators which are NIOSH/MSHA-approved for polynuclear aromatics and organic vapors. Examples of acceptable materials for protective clothing (e.g., gloves, overalls, jackets, and boots) required during application and handling of preservatives are polyvinyl acetate (PVA), polyvinyl chloride (PVC), neoprene, and TSP (Tetra-S). Waxes, latex, epoxy enamel, shellac, and varnishes are acceptable sealers for all pentachlorophenol-treated wood.

RESTRICTED USE PESTICIDE

For sale to and use only by certified applicators or by persons under their direct supervision and only for those uses covered by the certified applicators' certification.

Weldwood® **WOODLIFE®** (MILLTREAT TYPE-EC)

WATER REPELLENT PRESERVATIVE FOR WOOD READY - TO - USE

KEEP OUT OF REACH OF CHILDREN.

DANGER!

KEEP AWAY FROM HEAT OR OPEN FLAME.

Contains PETROLEUM SPIRITS. Keep contents and freshly treated articles away from flame food and living plants.

Storage and Disposal

Do not contaminate water, food, or feed by storage or disposal.

Pesticide disposal: Pesticide wastes are toxic. Improper disposal of excess pesticides, spray mixture, or残渣 is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

Container disposal: (Consult with EPA Notice 83-3 for appropriate language for non-hazardous container disposal).

Treated wood disposal: Wood which has been treated with this product should be disposed of by burial or ordinary trash collection. Do not burn treated wood in an outdoor fire or in stoves or fireplaces because toxic chemicals may be produced as part of the smoke and ash.

EPA Reg. No. 1409-34
EPA Est. No. 1409-MI-1
EPA Est. No. 1409-TX-1
EPA Est. No. 1409-WA-1
EPA Est. No. 1409-PA-1
EPA Est. No. 1409-GA-1

Manufactured by

Beecham Home Improvement Products Inc.

DAYTON, OHIO 45401

FOR INDUSTRIAL USE ONLY

Stock No. 55 U.S. Gallons
(208.2 Liters)
Made in U.S.A./Printed in U.S.A.

DIRECTIONS

Apply this product only as specified on this label. It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

DESCRIPTION: WOODLIFE is a clean, penetrating, non-swelling, paintable, water repellent preservative for wood. It protects wood against decay fungi (like brown or white rot), staining fungi (like blue stain), surface mold (like a black, brown or other colored mildew) and dimensional change.

PRODUCT USES: Millwork, shingles, siding, windows, doors, structural lumber, fences and outdoor furniture.

Do not apply in interiors. Do not apply to wood intended for use in interiors except for those specific applications which are consistent with the use of certain sealers, and situations where the surfaces to be treated are exterior. Applications to interior surfaces of the treated wood should be sealed with the coats of an appropriate sealer. Sealers are to be applied at the manufacturer's site.

RETENTION: 3-minute immersion — 5-10 gallons per MBM. 30-minute immersion — 10-15 gallons per MBM. 24-hour immersion — 15-25 gallons per MBM. Brush application — 150 sq. ft. per gallon; but varies by species and condition of wood.

PREPARATION: Machine cut, glue and sand wood as desired before treating. Do not use over previously finished or stained wood without stripping off old finish. Do not use steel wool. Wood must be clean and dry. Keep solution and freshly treated wood away from plastics and asphalt products. Fence posts, foundation timbers and heavy wooden members should be free of bark, dry and well-seasoned.

APPLICATION: Treating solution, wood and surrounding air must be above 40°F (4.4°C). Apply by immersion, Dri Vac vacuum, roller coater, flood spray or brush. Any surface cut after first treatment should be retreated. For wood in contact with soil, see directions under "IMMERSION" below.

IMMERSION: Millwork or other items to be painted — 3 minutes for batch or bundle treating, 30 seconds for plywood, 15 seconds for treating individual parts. Treatment should be in accordance with Industrial Standard 4-70. Wood to be in contact with soil — immerse 24 hours; posts for 48 hours.

FINISHING: Before glazing, painting or varnishing treatment should be completely dry and odor-free. Allow 24-48 hours under average temperature and humidity conditions. Can be heat-dried for plant production. Use a sealer such as shellac before using lacquers.

CLEAN-UP: Use mineral spirits to clean immersion tanks, spray equipment and surrounding area. Lacquer thinner may be required to remove dried WOODLIFE from floors and equipment.