


WOODLIFE®

(MILLTREAT TYPE-EC)

WATER REPELLENT PRESERVATIVE FOR WOOD



READY - TO - USE

DO NOT DILUTE

WARNING!

COMBUSTIBLE!

**KEEP OUT OF REACH OF CHILDREN.
KEEP AWAY FROM HEAT OR OPEN FLAME.
HARMFUL OR FATAL IF SWALLOWED OR
ABSORBED THROUGH SKIN.**

Contains Petroleum Distillate. Keep contents and freshly treated articles away from flame, food and living plants. Do not use, pour, spill or store near heat or open flame. Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place away from water supplies.

Causes skin irritation. Do not breathe vapor or spray mist. Do not get in eyes or on skin or clothing. Use only in well ventilated area.

Wear rubber gloves and protective clothing when handling the freshly treated lumber. Not for use or storage in or around the home.

This product is toxic to fish and wildlife. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this product only as specified on this label.

FIRST AID:

External — Wash with soap and water. Internal — Call a physician immediately. Force vomiting by drinking warm water mixed with a tablespoon of salt, milk or egg white. Lie down and keep warm.

ACTIVE INGREDIENTS:

Pentachlorophenol
Tetrachlorophenol

4.8%
.6%

INERT INGREDIENTS

95.2%

TOTAL

100.0%

Equivalent to 5.4% technical grade pentachlorophenol in accordance with Fed. Spec. TT-W-570B

NOTICE: SELLER MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, IN LAW OR IN FACT, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR USE, except that specifically set forth on this label. Buyer assumes all risks of use, handling or storage of this product when such use, handling or storage is not in strict accordance with the provisions of this label.

DIRECTIONS

DESCRIPTION: WOODLIFE MILLTREAT is a clean, penetrating, non-swelling, paintable water repellent preservative for wood. It protects against wood destroying fungi, staining fungi and dimensional change.

PRODUCT USES: A fast drying, water repellent preservative for the treatment of millwork in factory production.

RETENTION: 3 minute immersion — 5-10 gallons per MBM, 30 minute immersion — 10-15 gallons per MBM, 24 hour immersion — 15-25 gallons per MBM, brush application — 150 sq. ft. per gallon, but varies by species and condition of wood.

PREPARATION: Machine, cut, glue and sand wood, as desired, before treating. Do not use over previously finished or stained wood without stripping off old finish. Wood must be clean and dry. Do not use steel wool.

APPLICATION: Use only at 40°F. (4.4°C) surrounding temperature or above. Apply by immersion, Dri-Vac vacuum, roller coater, flood spray or brush.

IMMERSION: 3 minutes for batch or bundle treating, 30 seconds for plywood, 15 seconds for treating individual parts, or use Dri-Vac vacuum process. Treatment should be in accordance with Industrial Standard I.S. 4-70.

FINISHING: Before glazing, painting or varnishing, treatment should be completely dry and odor free. Allow 24-48 hours under average temperature and humidity conditions. Can be heat dried for plant production. Use a sealer such as shellac before using lacquers.

CLEAN-UP: Use mineral spirits to clean immersion tanks, spray equipment and surrounding area. Lacquer thinner may be required to remove dried WOODLIFE MILLTREAT from spray equipment.

Manufactured by:



Roberts Consolidated Industries

Subsidiary of Champion International

CITY OF INDUSTRY, CA 91749

Net Contents 55 Gallons
U.S. Measure
(208.2 Liters)

DO NOT REUSE CONTAINER — DESTROY WHEN EMPTY

EPA Est. No. 1409-ME1
EPA Reg. No. 1409-34
Made in U.S.A. Product of U.S.A.