


AC
Under the
Fungicide
as Amer
registers
EPA Reg.



Precautionary Statements: Hazards to Humans and Domestic Animals

DANGER: May be fatal if swallowed, inhaled, or absorbed through skin. Do not get in eyes, on face, or on clothing. Causes delayed chemical burns. Do not take internally. Avoid breathing vapors, spray mist, or dust. Use with adequate ventilation. Wash thoroughly after skin contact, and before eating, drinking, use of tobacco products, or using restrooms.

The U.S. EPA has determined that pentachlorophenol can produce defects in the offspring of laboratory animals. Exposure to pentachlorophenol during pregnancy should be avoided.

Avoid inhaling vapors. If inhalation of vapors cannot be avoided, applicators must wear a properly fitting, well-maintained half-mask canister or cartridge respirator which is NIOSH/NIOSH-approved for polynuclear aromatic and organic vapors.

Applicators must wear gloves impervious to the wood treatment formulation in all situations where dermal contact is expected (for example, during the actual application process and when handling freshly treated wood).

Spray applicators must wear protective clothing (including overalls, jackets, gloves, boots, and head covering) impervious to the wood treatment formulation, and a respirator and goggles when spraying.

Applicators who apply pentachlorophenol by other application processes (e.g., brush on) must wear long-sleeved shirts, long pants and an impervious apron. Launder work clothing separately from other household laundry.

Protective clothing must be changed when it shows signs of contamination. Launder non-disposable protective clothing separately from other household clothing. Dispose of worn-out protective clothing and workboots or boots in any general landfill, in the trash, or in any other manner approved for pesticide disposal.

Applicators must not eat, drink, or use tobacco products during these parts of the application process that may expose them to the wood treatment formulation.

Do not apply where there may be direct contact with domestic animals or livestock, and where there may be contamination of food, feed, or drinking and irrigation water.

Do not apply pentachlorophenol to wood intended for farming or brooding facilities.

Do not apply pentachlorophenol to wood intended to be used in the interiors of farm buildings where there may be direct contact with domestic animals or livestock which may come in contact with the wood. Pentachlorophenol may be used on wood intended to be used in interiors of farm buildings where domestic animals or livestock are unlikely to come in contact with the wood. If the coats of an appropriate sealer will be applied, sealers may be applied at the installation site.

Do not apply to wood intended to be used in a manner in which the preservative may become a component of food or animal feed. Examples of such sites would be structures or containers for storing storage of food.

Do not use this product to treat wood intended to be used for cutting boards or counter tops.

Do not use this product to treat wood intended for construction of those portions of beehives which may come into contact with the honey.

Do not use this product to treat wood intended for use where it may come into direct or indirect contact with drinking water for the public and domestic animals or livestock except for those uses involving incidental contact such as docks and bridges.

Wood to be treated with this product should be cut to size before treatment. If it is necessary to saw or machine wood after treatment, wear goggles to protect the eyes from flying particles and a dust mask to avoid breathing sawdust from the treated wood. If oily preservatives or sealers accumulate on clothes, launder before re-use. Wash work clothes separately from other household laundry.

Contact with treated surfaces should be avoided even after the preservative has dried. When handling treated wood wear long-sleeved shirts, long pants and impervious gloves (e.g., vinyl coated). Wash exposed skin thoroughly after contact with treated wood and before eating, drinking or using tobacco products.

This product should not be used to treat wood which will be in frequent contact with skin, unless the wood will be treated with an effective sealer.

NOTE TO USER: As used on this label, the term "respirators" means properly fitting, well-maintained, half-mask canister or cartridge respirators which are NIOSH/NIOSH-approved for polynuclear aromatic and organic vapors. Examples of acceptable material for protective clothing (e.g., gloves, overalls, jackets, and boots) required during application and handling of preservative are polyvinyl acetate (PVA), polybutyl acrylate (PBA), neoprene, and 100% (Dura-Mil, Urethane, latex epoxy enamel, and various other acceptable sealers for all pentachlorophenol-treated wood.

RESTRICTED USE PESTICIDE

For sale to and use only by certified applicators or by persons under their direct supervision and only for those uses covered by the certified applicators' certification.

Weldwood® WOODLIFE®

(MILTREAT TYPE-EC)

WATER REPELLENT PRESERVATIVE FOR WOOD

READY TO USE - DARK BROWN

KEEP OUT OF REACH OF CHILDREN.

DANGER!

KEEP AWAY FROM HEAT OR OPEN FLAME.

Contains PETROLEUM SPIRITS. Keep contents and freshly treated articles away from flame, food and young plants.

Storage and Disposal

Do not contaminate water, food, or feed by storage or disposal.

Pesticide disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or sludge is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the hazardous waste representative at the nearest EPA Regional Office for guidance.

Container disposal: (Consult with RC Notice 63-1) for appropriate language for non-haze container disposal.

Treated wood disposal: Wood which has been treated with this product should be disposed of by burial or ordinary trash collection. Do not burn treated wood in an outdoor fire or in stoves or fireplaces because toxic chemicals may be produced as part of the smoke and ashes.

Statement of Practical Treatments

If swallowed: Call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person. If in eyes: Flush with plenty of water. Get medical attention. If on skin: Wash with plenty of soap and water. Get medical attention. If inhaled: Remove victim to fresh air. Get medical attention.

NOTE TO USER: This product is a metabolic stimulant. Causes hypertension. Treat symptomatically.

ACTIVE INGREDIENTS:	
*Pentachlorophenol	4.3%
Other Chlorophenols5%
INERT INGREDIENTS	95.2%
TOTAL	100.0%

*Equivalent to 5.0% technical grade pentachlorophenol in accordance with Fed. Spec. TT-W-570.

MEETS FED. SPEC. TT-W-572B COMPOSITION A INDUSTRIAL STANDARD IS-4-70

IMPORTANT NOTICE TO PURCHASER

Buyer assumes all risk of use, handling and storage of product not in strict accordance with label directions. No express warranties are given. Should defect occur, Seller's sole liability is to replace product or refund purchase price. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR USE IS LIMITED TO ONE YEAR FROM DATE OF PURCHASE. LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGE OR LOSS IS SPECIFICALLY EXCLUDED AT ALL TIMES. If used for other than personal, family or household purposes, any implied warranty of MERCHANTABILITY or FITNESS FOR PARTICULAR USE is excluded.

Roberts Consolidated Industries

- EPA Reg. No. 1409-33
- EPA E-4 No. 1409-MI-1
- EPA Ex. No. 1409-TX-1
- EPA Est. No. 1409-WA-1
- EPA Est. No. 1409-PA-1
- EPA Est. No. 1409-GA-1



Made by **Beecham Home Improvement Products Inc.**

DAYTON, OHIO 45401

FOR INDUSTRIAL USE ONLY

Stock No. **Net Contents: 55 U.S. Gallons (208.2 Liters)**

Made in U.S.A./Printed in U.S.A.

Apply this product in a manner inconsistent with the label is a violation of Federal law.

DESCRIPTION: Water non-swelling, paint for wood. It protects brown or white rot surface mold (like mildew) and dimer.

PRODUCT USES: Mill doors, structural lumber.

Do not apply to interiors. Intentional except for those uses only on doors, stairs, porches or ladders. Infestation (e.g., termites, wood-boring insects) treated wood should be sealed. Sealers may be applied at 1.

RETENTION: 3-min MBM, 30-minute MBM, 24-hour immersion. Brush application - by species and color.

PREPARATION: Material as desired before finishing. Finish as desired before finishing. Do not clean and dry. Keep wood away from fence posts, fence members should be seasoned.

APPLICATION: Trimming air must immersion, Dri Vac or brush. Any surface be retreated. For water conditions under "IMMERSION".

IMMERSION: Millwork - 3 minutes for 1 coats for plywood, 1 parts. Treatment standard industrial Standard 4 soil - immerse 24

FINISHING: Before treatment should 1 Allow 24-48 hours humidity condition. Use a sea lacquers.

CLEAN-UP: Use milk tanks, spray equipment thinner may WOODLIFE from floor